Document Title	Specification of Operating System
Document Owner	AUTOSAR
Document Responsibility	AUTOSAR
Document Identification No	034
Document Classification	Standard

Document Version	4.0.0
Document Status	Final
Part of Release	4.0
Revision	1

Document Change History			
Date	**Version**	**Changed by**	**Change Description**
30.11.2009	4.0.0	AUTOSAR Administration	• Extension of services (Chapter 12) • States in OS- Applications • Active termination of other OS-Applications in possible (Chapter8) • Legal disclaimer revised • Chapter 10.3 revised
15.01.2009	3.1.0	AUTOSAR Administration	• Changes in OS configuration: - removed "OsAppModeId" Parameter from OsAppModeContainer added optional references from OsAppModeContainer to OsAlarm, OsTask and OsScheduleTable
04.08.2008	3.0.2	AUTOSAR Administration	Legal Disclaimer revised
17.04.2008	3.0.1	AUTOSAR Administration	• Added “OsScheduleTableDuration” parameter to configuration specification chapter
07.12.2007	3.0.0	AUTOSAR Administration	• Changed methods for timing protection • Moved configuration from OIL to AUTOSAR XML • Clarrified description for synchronization and schedule tables • Document meta information extended • Small layout adaptations made

火龙果•整理
uml.org.cn

Document Change History

Date	Version	Changed by	Change Description
31.01.2007	2.1.0	AUTOSAR Administration	• Added support for SoftwareFreeRunningTimer (SWFRT) incl. 2 new APIs • Added API to start a schedule table synchron • Misc. Corrections, Clarification and further explanations • Legal disclaimer revised • Release Notes added • “Advice for users” revised • “Revision Information” added
28.04.2006	2.0.0	AUTOSAR Administration	Document structure adapted to common Release 2.0 SWS Template. • Major changes in chapter 10 • Structure of document changed partly • Other changes see chapter 14
28.06.2005	1.0.0	AUTOSAR Administration	Initial Release

火龙果•整理
uml.org.cn

Disclaimer

This specification and the material contained in it, as released by AUTOSAR, is for the purpose of information only. AUTOSAR and the companies that have contributed to it shall not be liable for any use of the specification.

The material contained in this specification is protected by copyright and other types of Intellectual Property Rights. The commercial exploitation of the material contained in this specification requires a license to such Intellectual Property Rights.

This specification may be utilized or reproduced without any modification, in any form or by any means, for informational purposes only.
For any other purpose, no part of the specification may be utilized or reproduced, in any form or by any means, without permission in writing from the publisher.

The AUTOSAR specifications have been developed for automotive applications only. They have neither been developed, nor tested for non-automotive applications.

The word AUTOSAR and the AUTOSAR logo are registered trademarks.

Advice for users

AUTOSAR specifications may contain exemplary items (exemplary reference models, "use cases", and/or references to exemplary technical solutions, devices, processes or software).

Any such exemplary items are contained in the specifications for illustration purposes only, and they themselves are not part of the AUTOSAR Standard. Neither their presence in such specifications, nor any later documentation of AUTOSAR conformance of products actually implementing such exemplary items, imply that intellectual property rights covering such exemplary items are licensed under the same rules as applicable to the AUTOSAR Standard.

火龙果•整理
uml.org.cn

Table of Content

1 Introduction and functional overview ... 8

2 Acronyms and abbreviations ... 9

2.1 Glossary of Terms ... 9

3 Related documentation ... 13

3.1 Input documents ... 13
3.2 Related standards and norms ... 14
3.2.1 OSEK/VDX ... 14
3.2.2 HIS ... 14
3.2.3 ISO/IEC ... 14
3.3 Company Reports, Academic Work, etc. ... 15

4 Constraints and assumptions ... 16

4.1 Existing Standards ... 16
4.2 Terminology ... 16
4.3 Interaction with the RTE ... 16
4.4 Operating System Abstraction Layer (OSAL) ... 17
4.5 Limitations ... 18
4.5.1 Hardware ... 18
4.5.2 Programming Language ... 18
4.5.3 Miscellaneous ... 19
4.6 Applicability to car domains ... 19

5 Dependencies to other modules ... 20

5.1 File structure ... 20
5.1.1 Code file structure ... 20
5.1.2 Header file structure ... 20

6 Requirements Traceability ... 22

6.1 General Requirements on Basic Software Modules ... 22
6.2 Requirements on Software Free-Running Timer ... 27
6.3 AUTOSAR SRS OS Requirements ... 28
6.4 AUTOSAR SWS Service Requirements to API ... 29

7 Functional specification ... 31

7.1 Core OS ... 31
7.1.1 Background & Rationale ... 31
7.1.2 Requirements ... 31
7.1.2.1 Restrictions on OSEK OS ... 31
7.1.2.2 Undefined Behaviour in OSEK OS ... 32
7.1.2.3 Extensions to OSEK OS ... 33
7.2 Software Free Running Timer ... 34
7.3 Schedule Tables ... 35
7.3.1 Background & Rationale ... 35
7.3.2 Requirements ... 35
7.3.2.1 Structure of a Schedule Table ... 35

火龙果•整理
uml.org.cn

7.3.2.2 Constraints on Expiry Points ... 36
7.3.2.3 Processing Schedule Tables ... 36
7.3.2.4 Repeated Schedule Table Processing ... 38
7.3.2.5 Controlling Schedule Table Processing ... 38
7.4 Schedule Table Synchronization ... 41
7.4.1 Background & Rationale ... 41
7.4.2 Requirements ... 43
7.4.2.1 Implicit Synchronization ... 43
7.4.2.2 Explicit Synchonization ... 44
7.4.2.3 Performing Synchronization ... 48
7.5 Stack Monitoring Facilities ... 50
7.5.1 Background & Rationale ... 50
7.5.2 Requirements ... 51
7.6 OS-Application ... 51
7.6.1 Background & Rationale ... 51
7.6.2 Requirements ... 53
7.7 Protection Facilities ... 55
7.7.1 Memory Protection ... 55
7.7.1.1 Background & Rationale ... 55
7.7.1.2 Requirements ... 56
7.7.2 Timing Protection ... 57
7.7.2.1 Background & Rationale ... 57
7.7.2.2 Requirements ... 61
7.7.2.3 Implementation Notes ... 62
7.7.3 Service Protection ... 63
7.7.3.1 Invalid Object Parameter or Out of Range Value ... 63
7.7.3.2 Service Calls Made from Wrong Context ... 64
7.7.3.3 Services with Undefined Behaviour ... 65
7.7.3.4 Service Restrictions for Non-Trusted OS-Applications ... 67
7.7.3.5 Service Calls on Objects in Different OS-Applications ... 68
7.7.4 Protecting the Hardware used by the OS ... 68
7.7.4.1 Background & Rationale ... 68
7.7.4.2 Requirements ... 69
7.7.4.3 Implementation Notes ... 69
7.7.5 Providing »Trusted Functions« ... 69
7.7.5.1 Background & Rationale ... 69
7.7.5.2 Requirements ... 70
7.8 Protection Error Handling ... 70
7.8.1 Background & Rationale ... 70
7.8.2 Requirements ... 71
7.9 System Scalability ... 73
7.9.1 Background & Rationale ... 73
7.9.2 Requirements ... 74
7.10 Hook Functions ... 75
7.10.1 Background & Rationale ... 75
7.10.2 Requirements ... 75
7.11 Error classification ... 76
7.12 Debug support ... 77

8 API specification ... 78

火龙果•整理
uml.org.cn

8.1 Constants ... 78
8.1.1 Error codes of type StatusType ... 78
8.2 Macros ... 78
8.3 Type definitions ... 78
8.3.1 ApplicationType (for OS-Applications) ... 78
8.3.2 ApplicationStateType ... 78
8.3.3 ApplicationStateRefType ... 79
8.3.4 TrustedFunctionIndexType ... 79
8.3.5 TrustedFunctionParameterRefType ... 79
8.3.6 AccessType ... 79
8.3.7 ObjectAccessType ... 79
8.3.8 ObjectTypeType ... 79
8.3.9 MemoryStartAddressType ... 79
8.3.10 MemorySizeType ... 80
8.3.11 ISRType ... 80
8.3.12 ScheduleTableType ... 80
8.3.13 ScheduleTableStatusType ... 80
8.3.14 ScheduleTableStatusRefType ... 80
8.3.15 CounterType ... 80
8.3.16 ProtectionReturnType ... 81
8.3.17 RestartType ... 81
8.3.18 PhysicalTimeType ... 81
8.4 Function definitions ... 81
8.4.1 GetApplicationID ... 81
8.4.2 GetISRID ... 82
8.4.3 CallTrustedFunction ... 82
8.4.4 CheckISRMemoryAccess ... 84
8.4.5 CheckTaskMemoryAccess ... 84
8.4.6 CheckObjectAccess ... 85
8.4.7 CheckObjectOwnership ... 86
8.4.8 StartScheduleTableRel ... 87
8.4.9 StartScheduleTableAbs ... 88
8.4.10 StopScheduleTable ... 89
8.4.11 NextScheduleTable ... 89
8.4.12 StartScheduleTableSynchron ... 91
8.4.13 SyncScheduleTable ... 92
8.4.14 SetScheduleTableAsync ... 93
8.4.15 GetScheduleTableStatus ... 94
8.4.16 IncrementCounter ... 95
8.4.17 GetCounterValue ... 96
8.4.18 GetElapsedValue ... 97
8.4.19 TerminateApplication ... 97
8.4.20 AllowAccess ... 99
8.4.21 GetApplicationState ... 99
8.5 Hook functions ... 101
8.5.1 Protection Hook ... 101
8.5.2 Application specific StartupHook ... 101
8.5.3 Application specific ErrorHook ... 102
8.5.4 Application specific ShutdownHook ... 102

火龙果•整理
uml.org.cn

9 Sequence diagrams ... 104
9.1 Sequence chart for calling trusted functions ... 104
9.2 Sequence chart for usage of ErrorHook ... 105
9.3 Sequence chart for ProtectionHook ... 106
9.4 Sequence chart for StartupHook ... 107
9.5 Sequence chart for ShutdownHook ... 108
10 Configuration Specification ... 109
10.1 How to read this chapter ... 109
10.1.1 Configuration and configuration parameters ... 109
10.1.2 Variants ... 109
10.1.3 Containers ... 110
10.1.4 Rules for paramters ... 110
10.2 Containers and configuration parameters ... 110
10.2.1 Variants ... 110
10.3 Published Information ... 138
11 Generation of the OS ... 139
11.1 Read in configuration ... 139
11.2 Consistency check ... 139
11.3 Generating operating system ... 140
12 Application Notes ... 142
12.1 Hooks ... 142
12.2 Providing Trusted Functions ... 142
12.3 Migration hints for OSEKtime OS users ... 144
12.4 Software Components and OS-Applications ... 146
12.5 Global Time Synchronization ... 147
12.6 Working with FlexRay ... 147
12.7 Migration from OIL to XML ... 148
12.8 Migrating RES_SCHEDULER in AUTOSAR OS ... 148
12.9 Debug support ... 149
13 AUTOSAR Service implemented by the OS ... 150
13.1 Scope of this Chapter ... 150
13.1.1 Package ... 150
13.2 Overview ... 150
13.3 Specification of the Ports and Port Interfaces ... 151
13.3.1 Data Types and Port Interface ... 151
13.3.1.1 General Approach ... 151
13.3.1.2 Data Types ... 151
13.3.1.3 Port Interface ... 151
13.3.1.4 Ports ... 152
14 Outlook on Memory Protection Configuration ... 153
14.1 Configuration Approach ... 153
15 Changes to Release 3.0/3.1 ... 154

火龙果•整理
uml.org.cn

1 Introduction and functional overview

This document describes the essential requirements on the AUTOSAR Operating System to satisfy the top-level requirements presented in the AUTOSAR SRS [2].

In general, operating systems can be split up in different groups according to their characteristics, e.g. statically configured vs. dynamically managed. To classify the AUTOSAR OS, here are the basic features: the OS

- is configured and scaled statically
- is amenable to reasoning of real-time performance
- provides a priority-based scheduling policy
- provides protective functions (memory, timing etc.) at run-time
- is hostable on low-end controllers and without external resources

This feature set defines the type of OS commonly used in the current generation of automotive ECUs, with the exception of Telematic/Infotainment systems. It is assumed that Telematic/Infotainment systems will continue to use proprietary Oss under the AUTOSAR framework (e.g. Windows CE, VxWorks, QNX, etc.). In the case where AUTOSAR components are needed to run on these proprietary Oss, the interfaces defined in this document should be provided as an Operating System Abstraction Layer (OSAL).

This document uses the industry standard OSEK OS [14] (ISO 17356-3) as the basis for the AUTOSAR OS. The reader should be familiar with this standard before reading this document.

This document describes extensions to, and restrictions of, this OSEK OS.

火龙果•整理
uml.org.cn

2 Acronyms and abbreviations

Abbreviation	Description
API	Application Programming Interface
BSW	Basic Software
BSWMD	Basic Software Module Description
COM	Communication
ECU	Electronic Control Unit
HIS	Hersteller Initiative Software
ISR	Interrupt Service Routine
MCU	Microcontroller Unit
MPU	Memory Protection Unit
OIL	OSEK Implementation Language
OS	Operating System
OSEK/VDX	Offene Systeme und deren Schnittstellen für die Elektronik im Kraftfahrzeug
SWC	Software Component
SWFRT	Software FreeRunningTimer

2.1 Glossary of Terms

Term:	Definition	
Access Right	An indication that an object (e.g. Task, ISR, hook function) of an OS-Application has the permission of access or manipulation with respect to memory, OS services or (set of) OS objects.	
Cardinality	The number of items in a set.	
Counter	An operating system object that registers a count in ticks. There are two types of counters:	
	Hardware Counter	A counter that is advanced by hardware (e.g. timer). The count value is maintained by the peripheral “in hardware”.
	Software Counter	A counter which is incremented by making the `IncrementCounter()` API call (see OS399). The count value is maintained by the operating system “in software”.
Deadline	The time at which a Task/Category 2 ISR must reach a certain point during its execution defined by system design relative to the stimulus that triggered activation. See Figure 2.1	
Delay	The number of ticks between two adjacent expiry points on a schedule table. A pair of expiry points X and Y are said to be adjacent when: • There is no expiry point Z such that X.Offset < Z.Offset < Y.Offset. In this case the Delay = Y.Offset-X.Offset • X and Y are the Final Expiry Point and the Initial Expiry Point respectively. In this case Delay = (Duration-X.Offset)+Y.Offset When used in the text, Delay is a relative number of ticks measured from a specified expiry point. For example: X.Delay is the delay from X to the next expiry point.	
Deviation	The minimum number of ticks between the current position on an explicitly synchronized schedule table and the value of the synchronization count modulo the duration of the schedule table.	
Duration	The number of ticks from a notional zero at which a schedule table wraps.	
Execution Time	Tasks: The net time a task spends in the `RUNNING` state without entering the `SUSPENDED` or `WAITING` state excluding all preemptions due to ISRs	

火龙果•整理
uml.org.cn

	which preempt the task. An extended task executing the `WaitEvent()` API call to wait on an event which is already set notionally enters the `WAITING` state. For multiple activated basic tasks the net time is per activation of a task. ISRs: The net time from the first to the last instruction of the user provided Category 2 interrupt handler excluding all preemptions due to higher priority ISRs executing in preference. Execution time includes the time spent in the error, pretask and posttask hooks and the time spent making OS service calls.	
Execution Budget	Maximum permitted execution time for a Task/ISR.	
Expiry Point	The offset on a Schedule Table, measured from zero, at which the OS activates tasks and/or sets events.	
	Initial Expiry Point	The expiry point with the smallest offset
	Final Expiry Point	The expiry point with the largest offset
Hook Function	A Hook function is implemented by the user and invoked by the operating system in the case of certain incidents. In order to react to these on system or application level, there are two kinds of hook functions	
	Application-specific	Hook functions within the scope of an individual OS-Application.
	System-specific	Hook functions within the scope of the complete system (in general provided by the integrator).
Initial Offset	The smallest expiry point offset on a schedule table. This can be zero.	
Interarrival Time	Basic Tasks The time between successively entering the `READY` state from the `SUSPENDED` state. Activation of a task always represents a new arrival. This applies in the case of multiple activations, even if an existing instance of the task is in the `RUNNING` or `READY` state. Extended Tasks: The time between successively entering the `READY` state from the `SUSPENDED` or `WAITING` states. Setting an event for a task in the `WAITING` state represents a new arrival if the task is waiting on the event. Waiting for an event in the `RUNNING` state which is already set represents a new arrival. ISRs: The time between successive occurrences of an interrupt. See Figure 2.1.	
Interrupt Lock Time	The time for which a Task/ISR executes with Category 1 interrupts disabled/suspended and/or Category 2 interrupts disabled/suspended .	
Interrupt Source Enable	The switch which enables a specific interrupt source in the hardware.	
Interrupt Vector Table	Conceptually, the interrupt vector table contains the mapping from hardware interrupt requests to (software) interrupt service routines. The real content of the Interrupt Vector Table is very hardware specific, e.g. it can contain the start addresses of the interrupt service routines.	
Final Delay	The difference between the Final Expiry Point offset and the duration on a schedule table in ticks. This value defines the delay from the Final Expiry Point to the logical end of the schedule table for single-shot and “nexted” schedule tables.	
Forced OS-Application Termination	The operating system frees all system objects, e.g. forcibly terminates Tasks, disables interrupts, etc., which are associated to the OS-Application. OS-Application and internal variables are potentially left in an undefined state.	
Forced Termination	The OS terminates the Task/Category 2 ISR and does ”unlock” its held resources. For details see OS108 and OS109.	

火龙果•整理
uml.org.cn

Linker File	File containing linking settings for the linker. The syntax of the linker file depends on the specific linker and, consequently, definitions are stored “linker-specific” in the linker file.	
Lock Budget	Maximum permitted Interrupt Lock Time or Resource Lock Time.	
Memory Protection Unit	A Memory Protection Unit (MPU) enables memory partitioning with individual protection attributes. This is distinct from a Memory Management Unit (MMU) that provides a mapping between virtual addresses and physical memory locations at runtime. Note that some devices may realise the functionality of an MPU in an MMU.	
Mode	Describes the permissions available on a processor.	
	Privileged	In general, in »privileged mode« unrestricted access is available to memory as well as the underlying hardware.
	Non-privileged	In »non-privileged mode« access is restricted.
Modulus	The number of ticks required to complete a full wrap of an OSEK counter. This is equal to `OsCounterMaxAllowedValue` +1 ticks of the counter.	
OS-Application	A collection of OS objects	
	Trusted	An OS-Application that is executed in privileged mode and has unrestricted access to the API and hardware resources. Only trusted applications can provide trusted functions.
	Non-trusted	An OS-Application that is executed in non-privileged mode has restricted access to the API and hardware resources.
OS object	Object that belongs to a single OS-Application: Task, ISR, Alarm, Event, Schedule Table, Resource, Trusted Function, Counter, Applicaton-specific hook.	
OS Service	OS services are the API of the operating system.	
Protection Error	Systematic error in the software of an OS-Application.	
	Memory access violation	A protection error caused by access to an address in a manner for which no access right exists.
	Timing fault	A protection error that violates the timing protection.
	Illegal service	A protection error that violates the service protection, e.g. unauthorized call to OS service.
	Hardware exception	division by zero, illegal instruction etc.
Resource Lock Time	The time an OSEK resource is held by a Task/ISR (excluding the preemptions of the Task/ISR by higher prior Tasks/ISRs).	
Response Time	The time between a Task/ISR being made ready to execute and generating a specified response. The time includes all preemptions. See Figure 2.1	
Restart an OS-Application	An OS-Application can be restarted after self-termination or being forcibly terminated because of a protection error. When an OS-Application is restarted, the OS activates the configured `OsRestartTask`.	
Scalability Class	The features of the OS (e.g. Memory Protection or Timing Protection), described by this document, can be grouped together to customize the operating system to the needs of the application. There are 4 defined groups of features which are named scalability classes. For details see Chapter 7.9	
Schedule Table	Encapsulation of a statically defined set of expiry points.	
Section	Part of an object file in which instructions or data are combined to form a unit (contiguous address space in memory allocated for data or code). A section in an object file (object file format) has a name and a size. From the linker perspective, two different sides can be distinguished:	
	Input section	memory section in an input object file of the linker.
	Output section	memory section in an output object file of the linker.
Set (of OS objects)	This document uses the term set, indicating a collection of the same type of OS objects, in the strict mathematical sense, i.e.: - a set contains zero or more OS objects (this means a set can be empty) - the OS objects in the set are unique (this means there cannot be duplicate OS objects in the set)	
Symbol	Address label that can be imported/used by software modules and resolved by the linker. The precise syntax of the labels is linker-specific. Here, these address labels are used to identify the start and end of memory sections.	

火龙果•整理
uml.org.cn

	Start symbol	Tags the start of a memory section
	End symbol	Tags the end of a memory section
Synchronization of schedule tables with a synchronization counter	Synchronization with a synchronization counter is achieved, if the expiry points of the schedule table are processed within an absolute deviation from the synchronization counter that is smaller than or equal to a precision threshold.	
Synchronization Counter	The “Synchronization Counter”, distinct from an OS counter object, is an external counter, external to the OS, against which expiry points of a schedule table are synchronized	
Task	A Task is the object which executes (user) code and which is managed by the OS. E.g. the OS switches between different Tasks (“schedules”). There are 2 types of Tasks; for more details see [14].	
	Basic Task	A Task which can not block by itself. This means that it can not wait for (OS) event(s).
	Extended Task	A Task which can block by itself and wait for (OS) event(s).
Time Frame	The minmum inter-arrival time for a Task/ISR.	
Trusted Function	A service provided by a trusted OS-Application that can be used by other OS-Applications (trusted or non-trusted).	
Worst case execution time (WCET)	The longest possible execution time.	
Write access	Storing a value in a register or memory location. All memory accesses that have the consequence of writing (e.g. reads that have the side effect of writing to a memory location) are treated as write accesses.	

Figure 2.1: Definition of Timing Terminology

火龙果•整理
uml.org.cn

3 Related documentation

3.1 Input documents

[1] Layered Software Architecture
AUTOSAR_EXP_LayeredSoftwareArchitecture.pdf

[2] Requirements on Operating System
AUTOSAR_SRS_OS.pdf

[3] General Requirements on Basic Software Modules
AUTOSAR_SRS_BSWGeneral.pdf

[4] Specification of the Virtual Functional Bus
AUTOSAR_EXP_VFB.pdf

[5] Requirements on Software FreeRunningTimer
AUTOSAR_SRS_FreeRunningTimer.pdf

[6] Specification of GPT Driver
AUTOSAR_SWS_GPTDriver.pdf

[7] Specification of Standard Types
AUTOSAR_SWS_StandardTypes.pdf

[8] Specification of Memory Mapping
AUTOSAR_SWS_MemoryMapping.pdf

[9] Specification of RTE
AUTOSAR_SWS_RTE.pdf

[10] Specification of ECU Configuration
AUTOSAR_TPS_ECUConfiguration.pdf

[11] Basic Software Module Description Template,
AUTOSAR_TPS_BSWModuleDescriptionTemplate.pdf

[12] Specification of Multi-Core OS Architecture,
AUTOSAR_SWS_MultiCoreOS.pdf

[13] List of Basic Software Modules,
AUTOSAR_TR_BSWModuleList.pdf

火龙果•整理
uml.org.cn

3.2 Related standards and norms

3.2.1 OSEK/VDX

The OSEK/VDX specifications are publicly available from www.osek-vdx.org

[14] Operating System
Version 2.2.3
17th February 2005

[15] Time-Triggered Operating System
Version 1.0
24th July 2001

[16] System Generation OIL: OSEK Implementation Language
Version 2.5
1st July 2004

[17] OSEK RunTime Interface (ORTI) Part A: Language Specification
Version 2.2
14th November 2005

[18] OSEK Run Time Interface (ORTI) Part B: OSEK Objects and Attributes
Version 2.2
25th November 2005

[19] Binding Specification
Version 1.4.2
15th July 2004

3.2.2 HIS

The HIS (Hersteller Initiative Software) documents are publicly available from www.automotive-his.de

[20] Requirements for Protected Applications under OSEK
Version 1
25th September 2002.

[21] OSEK OS Extensions for Protected Applications
Version 1.0
27th July 2003

3.2.3 ISO/IEC

[22] ISO/IEC 9899:1990 Programming Language – C

火龙果•整理
uml.org.cn

(Remark: The international ISO standard ISO/IEC 9899:1990, also sometimes simply called »C90«, describes the language C. It was introduced in 1990 and replaced the ANSI C standard that was introduced only one year before, that's why it is also called »C89«. C89 differs from ISO/IEC 9899:1990 essentially only by the copyright note.)

[23] ISO/IEC 9899:1999 Programming Language – C

(Remark: A revised version of the standard was published in 1999. It is officially ISO/IEC 9899:1999, but is more often referred to as »C99«.)

3.3 Company Reports, Academic Work, etc.

[24] Extensions of OSEK OS for Protected Applications
OSEK Support Project DC058_02
DaimlerChrysler AG

火龙果•整理
uml.org.cn

4 Constraints and assumptions

4.1 Existing Standards

This document makes the following assumptions about the referenced related standards and norms:

- OSEK OS [14] provides a sufficiently flexible scheduling policy to schedule AUTOSAR systems.
- OSEK OS [14] is a mature specification and implementations are used in millions of ECUs worldwide.
- OSEK OS [14] does not provide sufficient support for isolating multi-source software components at runtime.
- OSEK OS [14] does not provide sufficient runtime support for demonstrating the absence of some classes of fault propagation in a safety-case.
- OSEKtime OS [15] and the HIS Protected OSEK [21] are immature specifications that contain concepts necessary for AUTOSAR and satisfy specific application domains. It is the purpose of this document to identify these needs and to recommend the use of parts (or all) of these specifications as appropriate.

4.2 Terminology

The specification uses the following operators when requirements specify multiple terms:

NOT : negation of a single term e.g. NOT Weekend
AND : conjunction of two terms e.g. Weekend AND Saturday
OR : disjunction of two terms e.g. Monday OR Tuesday

A requirement comprising multiple terms is evaluated left to right.

The precedence rules are:

Highest Precedence	**NOT**
Lowest Precedence	**AND OR**

The expression NOT X AND Y means (NOT X) AND (Y)

Where operators of the same precedence are used in the same sentence, commas are used to disambiguate. The expression X AND Y, OR Z means (X AND Y) OR Z.

4.3 Interaction with the RTE

The configuration of an AUTOSAR system [4] maps the »runnables« of a »software component« to (one or more) tasks that are scheduled by the operating system. All runnables in a task share the same protection boundary. In AUTOSAR, a software component must not include an interrupt handler. A software component is therefore implemented as runnables executing within the body of a task, or set of tasks, only.

火龙果•整理
uml.org.cn

Runnables get access to hardware-sourced data through the AUTOSAR RTE. The RTE provides the runtime interface between runnables and the basic software modules. The basic software modules also comprise a number of tasks and ISRs that are scheduled by the operating system.

It is assumed that the software component templates and the description of the basic software modules provide sufficient information about the required runtime behavior to be able to specify the attributes of tasks required to configure the OS.

4.4 Operating System Abstraction Layer (OSAL)

Systems that do not use the OS defined in AUTOSAR can provide a platform for the execution of AUTOSAR software components using an Operating System Abstraction Layer. The interface to the OSAL is exactly that defined for the AUTOSAR OS.

火龙果•整理
uml.org.cn

4.5 Limitations

4.5.1 Hardware

The core AUTOSAR operating system assumes free access to hardware resources, which are managed by the OS itself. This includes, but is not limited to, the following hardware:

- interrupt control registers
- processor status words
- stack pointer(s)

Specific (extended) features of the core operating system extend the requirements on hardware resource. The following list outlines the features that have requirements on the hardware. Systems that do not use these OS features do not have these hardware requirements.

- Memory Protection: A hardware memory protection unit is required. All memory accesses that have the consequence of writing (e.g. reads that have the side effect of writing to a memory location) shall be treated as writes.

- Time Protection: Timer Hardware for monitoring execution times and arrival rates.

- »Privileged« and »non-privileged« modes on the MCU: to protect the OS against internal corruption caused by writes to OS controlled registers. This mode must not allow OS-Applications to circumvent protection (e.g. write registers which govern memory protection, write to processor status word etc.). The privileged mode must be under full control of the protected OS which uses the mode internally and to transfer control back and forth from a non-trusted OS-Application to a trusted OS-Application. The microprocessor must support a controlled means which moves a processor into this privileged mode.

- Local/Global Time Synchronization: A global time source is needed.

In general hardware failures in the processor are not detected by the operating system. In the event of hardware failure, correct operation of the OS cannot be guaranteed.

The resources managed by a specific OS implementation have to be defined within the appropriate configuration file of the OS.

4.5.2 Programming Language

The API of the operating system is defined as C89 [22] function calls or macros. If other languages are used they must adapt to the C interface. This is because C99 [23] allows for internal dynamic memory allocation during subroutine calls. Most automotive applications are static (non-heap based).

火龙果•整理
uml.org.cn

4.5.3 Miscellaneous

The operating system does not provide services for dynamic memory management.

This specification handles only single core MCUs (this means one single thread of execution at one time). If you need support for multi-core MCUs please see [12].

If you are using a multi processor system and want to use this operating system, each processor has to run its own operating system. (e.g. a multi-processor system must use a different OS image for each processor.

4.6 Applicability to car domains

The operating system has the same design constraints regarding size and scalability under which the OSEK OS was designed. The immediate domain of applicability is therefore currently body, chassis and power train ECUs. However, there is no reason that the OS cannot be used to implement ECUs for infotainment applications.

火龙果•整理
uml.org.cn

5 Dependencies to other modules

There are no forced dependencies on other modules, however:

- It is assumed that the operating system may use timer units directly to drive counters.
- If the user needs to drive scheduling directly from global time, then a global time interrupt is required.
- If the user needs to synchronize the processing of a schedule table to a global time, the operating system needs to be told the global time using the `SyncScheduleTable()` service.

5.1 File structure

5.1.1 Code file structure

The code file structure of the Operating system module is not fixed, besides the requirements in the General SRS.

5.1.2 Header file structure

Figure 5:1: Header File Structure for the OS

The figure above contains the defined AUTOSAR header file hierarchy of the Operating System module.

OS546: OS implementer shall provide a header file structure, so that users of the Operating System module needs only to include the **Os.h** file

火龙果•整理
uml.org.cn

If an implementation of the Operating System module requires additional header files, it is free to include them. The header files are self contained, that means they will include all other header files which are required by them.

[**OS552**:The Operating System module shall avoid the integration of incompatible (c or h) files by the following pre-processor checks:

For included (external) header files:

- `<MODULENAME>_AR_RELEASE_MAJOR_VERSION`
- `<MODULENAME>_AR_RELEASE_MINOR_VERSION`

shall be verified.

For the module internal c and h files:

- `OS_SW_MAJOR_VERSION`
- `OS_SW_MINOR_VERSION`
- `OS_AR_RELEASE_MAJOR_VERSION`
- `OS_AR_RELEASE_MINOR_VERSION`
- `OS_AR_RELEASE_REVISION_VERSION`

shall be verified.

If the values are not identical to the values expected by the Operating System module, an error shall be reported.

火龙果•整理
uml.org.cn

6 Requirements Traceability

This chapter contains references to requirements of other AUTOSAR documents.

6.1 General Requirements on Basic Software Modules

Requirement	***Satisfied by***
Functional Requirements – Configuration	
[BSW00344] Reference to link time configuration	Not applicable (AUTOSAR OS is a statically configured Operating System.)
[BSW00404] Reference to post build time configuration	Not applicable (AUTOSAR OS does not support post build time configuration.)
[BSW00405] Reference to multiple configuration sets	Not applicable (AUTOSAR OS does not support post build time configuration.)
[BSW00345] Pre—compile—time configuration	See Chapter 5
[BSW159] Tool-based configuration	OS uses standard XML, so various tools may be used to configure the OS
[BSW167] Static configuration checking	See Chapter 11.2
[BSW171] Configurability of optional functionality	See Chapter 10. Requirement focuses on implementation.
[BSW170] Data for reconfiguration of AUTOSAR SW-Components	Not applicable
[BSW00380] Separate C-Files for configuration parameters	Not applicable (Requirement for implementation)
[BSW00419] Separate C-Files for pre-compile time configuration parameters	Not applicable (Requirement for implementation)
[BSW00381] Separate configuration header file for pre-compile time parameters	Not applicable (Requirement for implementation)
[BSW00412] Separate H-File for configuration parameters	Not applicable (Requirement for implementation)
[BSW00383] List dependencies of configuration files	Not applicable (SWS has no dependencies for configuration files.)
[BSW00384] List dependencies to other modules	Not applicable (SWS has no dependencies to other modules.)
[BSW00387] Specify the configuration class of callback function	See Chapter 8.5 for details.
[BSW00388] Introduce containers	See Chapter 10.2.
[BSW00389] Containers shall have names	See Chapter 10.2.
[BSW00390] Parameter content shall be unique within the module	See Chapter 10.2.
[BSW00391] Parameter shall have unique names	See Chapter 10.2.
[BSW00392] Parameters shall have a type	See Chapter 10.2.

火龙果•整理
uml.org.cn

Requirement	***Satisfied by***
[BSW00393] Parameters shall have a range	See Chapter 10.2.
[BSW00394] Specify the scope of the parameters	See Chapter 10.2.
[BSW00395] List the required parameters (per parameter)	See Chapter 10.2.
[BSW00396] Configuration classes	See Chapter 10.2.
[BSW00397] Pre-compile-time parameters	See Chapter 10.2.
[BSW00398] Link-time parameters	See Chapter 10.2.
[BSW00399] Loadable Post-build time parameters	See Chapter 10.2.
[BSW00400] Selectable Post-build time parameters	See Chapter 10.2.
[BSW00438] Post-build configuration data structure	See Chapter 10.2.
[BSW00402] Published information	See Chapter 10.2.
Functional Requirements – Wake Up	
[BSW00375] Notification of wake-up reason	Not applicable
Functional Requirements – Initialization	
[BSW101] Initialization interface	`StartOS()`
[BSW00416] Sequence of Initialization	`StartOS()` is called by the user. Sequence of calls with other modules is not affected.
[BSW00406] Check module initialization	Not applicable (Requirement for implementation)
[BSW00437] NoInit—Area in RAM	N/A – The OS only covers it's own data areas.
Functional Requirements – Normal Operation	
[BSW168] Diagnostic interface of SW components	Not applicable
[BSW00407] Function to read out published parameters	Not applicable (Requirement for implementation)
[BSW00423] Usage of SW-C template to describe BSW modules with AUTOSAR Interface	Not applicable (AUTOSAR OS does not interact directly with SW-C.)
[BSW00424] BSW main processing function task allocation	Requirement for users of AUTOSAR OS together with the RTE.
[BSW00425] Trigger conditions for schedulable objects	Requirement for users of AUTOSAR OS together with the RTE.
[BSW00426] Exclusive areas in BSW modules	Requirement for users of AUTOSAR OS together with the RTE.
[BSW00427] ISR description for BSW modules	Requirement for users of AUTOSAR OS together with the RTE.
[BSW00428] Execution order dependencies of main processing functions	Requirement for users of AUTOSAR OS together with the RTE.
[BSW00429] Restricted BSW OS functionality access	Requirement for users of AUTOSAR OS together with the RTE.
[BSW00431] The BSW Scheduler module implements task bodies	Requirement for users of AUTOSAR OS together with the RTE.
[BSW00432]	Requirement for users of AUTOSAR OS together

火龙果•整理
uml.org.cn

Requirement	***Satisfied by***
Modules should have separate main processing functions for read/receive and write/transmit data path	with the RTE.
[BSW00433] Calling of main processing functions	Requirement for users of AUTOSAR OS together with the RTE.
[BSW00434] The Schedule Module shall provide an API for exclusive areas	Requirement for users of AUTOSAR OS together with the RTE.
Functional Requirements – Shutdown Operation	
[BSW00336] Shutdown Interface	`ShutdownOS()`
Functional Requirements – Fault Operation and Error Detection	
[BSW00337] Classification of errors	Not applicable (AUTOSAR OS does not distinguish between “development” and “production” errors. See Section 7.11.
[BSW00338] Detection and Reporting of development errors	Not applicable (AUTOSAR OS calls the ErrorHook (defined by the OSEK OS specification [14]) and the ProtectionHook (see Section 7.8) in case of errors. It is possible to call Debug Error Tracer from these hook routines.)
[BSW00369] Do not return development error codes via API	Not applicable (AUTOSAR OS does not distinguish between “development” and “production” errors. In accordance with OSEK OS all possible errors are reported via the `ErrorHook()` and as return values of system services.)
[BSW00339] Reporting of production relevant error status	Not applicable (AUTOSAR OS calls the `ErrorHook()` (defined by the OSEK OS specification [14]) and the `ProtectionHook()` (see Section 7.8) in case of errors. It is possible to call the function inhibition or diagnostic event manager (DEM) and handle the debouncing from these hook routines.)
[BSW00422] Debouncing of production relevant error status	Not applicable (AUTOSAR OS calls the `ErrorHook()` (defined by the OSEK OS specification [14]) and the `ProtectionHook()` (see Section 7.8) in case of errors. It is possible to call the function inhibition or diagnostic event manager (DEM) and handle the debouncing from these hook routines.)
[BSW00417] Reporting of Error Events by Non-Basic Software	Not applicable (e.g. this module does not provide any wake-up reason)
[BSW00323] API parameter checking	See Section 7.7.3
[BSW004] Version check	Not applicable (Requirement for implementation)
[BSW00409] Header files for production code error IDs	Not applicable (AUTOSAR OS does not distinguish between “development” and “production” errors. See Section 7.11.
[BSW00385] List possible error notifications	Not applicable (AUTOSAR OS does not distinguish between “development” and “production” errors. See Section 7.11.

火龙果•整理
uml.org.cn

Requirement	***Satisfied by***
[BSW00386] Configuration for detecting an error	Not applicable (AUTOSAR OS calls the `ErrorHook()` (defined by the OSEK OS specification [14]) and the `ProtectionHook()` (see Section 7.8) in case of errors. It is possible to call the function inhibition or diagnostic event manager (DEM) and handle the debouncing from these hook routines.)
Non-functional Requirements – Software Architecture Requirements	
[BSW161] Microcontroller Abstraction	N/A
[BSW162] ECU Layout Abstraction	N/A
[BSW005] No hard coded horizontal interfaces within MCAL	OS does not belong to MCAL
[BSW00415] User dependant include files	N/A – OS is used by several BSWs and SWCs
Non-functional Requirements – Software Integration Requirements	
[BSW164] Implementation of interrupt service routines	OK – OS is allowed to implement interrupt service routines
[BSW00325] Runtime of interrupt service routines	N/A
[BSW00326] Transition of ISRs to OS tasks	N/A
[BSW00342] Usage of source code and object code	N/A
[BSW00343] Specification and configuration of time	OS supports ticks for OSEK compatibility and physical times (with convert macros)
[BSW160] Human-readable configuration data	OS is using XML
Software Module Design Requirements	
[BSW007] HIS MISRA C	N/A – Requirement on implementation
[BSW00300] Module naming conventions	See Chapter 5
[BSW00413] Accessing instances of BSW modules	N/A – Only one instance of the OS is possible
[BSW00347] Naming seperation of different instances of BSW drivers	N/A – OS is not a driver
[BSW00441] Enumeration literals and #define naming convention	N/A – OS follows the OSEK OS naming scheme since it is based on OSEK OS API
[BSW00305] Data types naming convention	N/A – OS follows the OSEK OS naming scheme since it is based on OSEK OS API
[BSW00307] Global variables naming convention	N/A – AUTOSAR SWS OS does not offer global variables.
[BSW00310] API naming convention	N/A – OS follows the OSEK OS naming scheme since it is based on OSEK OS API
[BSW00373] Main processing function naming convention	N/A – OS has no main function
[BSW00327] Error values naming convention	N/A – OS follows the OSEK OS naming scheme since it is based on OSEK OS API
[BSW00335] Status values naming convention	N/A – OS follows the OSEK OS naming scheme since it is based on OSEK OS API
[BSW00350] Development error detection keyword	N/A – Requirement on implementation
[BSW00408]	See Chapter 10

火龙果•整理
uml.org.cn

Requirement	***Satisfied by***
Configuration parameter naming convention	
[BSW00410] Compiler switches shall have defined values	N/A – Requirement on implementation
[BSW00411] Get version info keyword	N/A – Requirement on implementation
[BSW00346] Basic set of module files	See Chapter 5
[BSW158] Separation of configuration from implementation	See Chapter 5
[BSW00314] Separation of interrupt frames and service routines	N/A – Requirement on implementation
[BSW00370] Separation of callback interface from API	N/A – Requirement on implementation
[BSW00435] Module Header File Structure for the Basic Software Scheduler	N/A – OS does not use the BSW Scheduler
[BSW00436] Module Header File Structure for the Basic Software Memory Mapping	N/A – Requirement on implementation
[BSW00348] Standard type header	See Chapter 5
[BSW00353] Platform specific type header	See Chapter 5
[BSW00361] Compiler specific language extention header	N/A – Requirement on implementation
[BSW00301] Limit imported information	N/A – Requirement on implementation
[BSW00302] Limit exported information	N/A – Requirement on implementation
[BSW00328] Avoid duplication of code	N/A – Requirement on implementation
[BSW00312] Shared code shall be reentrant	N/A – Requirement on implementation
[BSW006] Platform independency	N/A – The OS depends on the used µC and the used compiler (e.g. because of the calling conventions)
[BSW00439] Declaration of interrupt handlers and ISRs	N/A – OS is no MCAL module
[BSW00357] Standard API return type	N/A – OS follows the OSEK OS naming scheme since it is based on OSEK OS API
[BSW00377] Module specific API return type	N/A – OS follows the OSEK OS naming scheme since it is based on OSEK OS API
[BSW00304] AUTOSAR integer data types	N/A – OS follows the OSEK OS naming scheme since it is based on OSEK OS API
[BSW00355] Do not redefine AUTOSAR integer data types	N/A – OS follows the OSEK OS naming scheme since it is based on OSEK OS API
[BSW00378] AUTOSAR boolean type	N/A – OS has no boolean parameters, etc.
[BSW00306] Avoid direct us eof compiler and platform specific keywords	N/A – Requirement on implementation
[BSW00308] Definition of global data	N/A – Requirement on implementation
[BSW00309] Global data with read—only constraint	N/A – Requirement on implementation
[BSW00371] Do not pass function pointers via API	OS does not allow this

火龙果•整理
uml.org.cn

Requirement	Satisfied by
[BSW00358] Return type of `init()` functions	N/A – `StartOS()` does not return
[BSW00414] Parameter of init function	N/A – `StartOS()` is an OSEK OS function
[BSW00376] Return type and parameters of main processing functions	N/A – OS has no main function
[BSW00359] Return type of callback functions	See Chapter 8
[BSW00360] Parameters of callback functions	See Chapter 8
[BSW00440] Function prototype for callback functions of AUTOSAR Services	N/A – OS offers no callbacks as AUTOSAR services
[BSW00329] Avoidance of generic interfaces	N/A
[BSW00330] Usage of macros / inline functions instead of functions	N/A – Requirement on implementation
[BSW00331] Separation of error and status values	OS does not mix error and status values
Non-functional Requirements – Software Documentation Requirements	
[BSW009] User Module Documentation	N/A
[BSW00401] Documentation of multiple instance of configuration parameters	N/A
[BSW172] Compatibility and documentation of scheduling strategy	N/A
[BSW010] Memory resource documentation	N/A
[BSW00333] Documentation of callback function context	N/A
[BSW00374] Module vendor identification	N/A
[BSW00379] Module identification	N/A
[BSW003] Version identification	N/A
[BSW00318] Format of module version numbers	N/A
[BSW00321] Enumeration of module version numbers	N/A
[BSW00341] Microcontroller compatibility documentation	N/A
[BSW00334] Provision of XML file	N/A

6.2 Requirements on Software Free-Running Timer

Requirement	Satisfied by
[SWFRT00019] Configure HW Timer Type	See chapter 10.2

火龙果•整理
uml.org.cn

Requirement	Satisfied by
[SWFRT00020] Configuration/initialization of HW Timer	OS374
[SWFRT00021] Import Used HW Timer's Configuration	GPT is not used by OS. See chapter 10.2 for details.
[SWFRT00022] State which HW Timer is used	OS370
[SWFRT00023] Set up Duration of one Tick	Possible via `OsSecondsPerTick`
[SWFRT00024] Support different Ranges/Resolutions	The setup of different ranges/resolutions is up to the timer driver
[SWFRT00025] Set up Access Methods	OS383, OS392
[SWFRT00026] Set up Target Count Values	OS386_Conf
[SWFRT00028] Ensure Continuous Running Mode	GPT is not used by OS.
[SWFRT00029] Init Function	The init function of the OS is the `StartOS()` service.
[SWFRT00030] Start with Zero	OS384
[SWFRT00031] Increment Counter	OS384
[SWFRT00032] Wrap Around	N/A. This requirement targets specific timer features. The OS should minimize the software access to timers (e.g. by using automatic reload features of the hardware).
[SWFRT00033] Read out Ticks	OS377
[SWFRT00034] Calculate Ticks Elapsed since given value	OS382
[SWFRT00041] Shutdown Function	There is no function to shutdown the timers which drive counters
[SWFRT00047] Convert Ticks to Time	OS393
[SWFRT00048] EcuM Modes	The OS is not aware of any EcuM modes and switching modes which influences timers (e.g. stop them or slow down counting) is neither recognized nor handled by the OS. It is the responsibility of the user to take care of this affects.

6.3 AUTOSAR SRS OS Requirements

Requirement	Satisfied by
[BSW097] Existing OSEK OS	OS001
[BSW11001] Object Grouping	OS114_Conf, OS056
[BSW098] Table based schedules	OS002, OS007
[BSW099] Switchable schedules	OS191
[BSW11002] Synchronization with global time	OS206, OS201, OS013, OS199, OS227
[BSW11003]	OS067, OS068

火龙果•整理
uml.org.cn

Requirement	Satisfied by
Stack Monitoring	
[BSW11005] Memory Write Access	OS207, OS208, OS195
[BSW11006] Data exchange	OS086, OS196, OS087
[BSW11007] Code Sharing	OS081
[BSW11000] Memory read access	OS026
[BSW11008] Timing Protection	OS028, OS089, OS033, OS037, OS048, OS064, OS465, OS469, OS470, OS471, OS472, OS473, OS474
[BSW11009] Protection of the OS	OS051, OS088, OS052, OS069, OS070, OS092, OS093
[BSW11010] Protection of OS-Applications	OS056
[BSW11011] Protecting the OS managed hardware	OS096, OS245
[BSW11012] Scalable Protection	OS241, OS240
[BSW11016] Scalability of the OS	OS241, OS240
[BSW11013] Error Notification	OS068, OS044, OS210, OS033, OS037, OS064, OS051, OS088, OS070, OS093, OS056, OS246
[BSW11014] Protection Error Handling	OS033, OS037, OS106, OS107, OS108, OS109, OS110, OS243, OS244,
[BSW11018] Interrupt services	OS299
[BSW11020] Interface for ticking counters	OS286
[BSW11021] Cascading counters	OS301
[BSW11019] Creation of Interrupt Vector Table	OS336

6.4 AUTOSAR SWS Service Requirements to API

Requirement	Associated API
OS016	8.4.1
OS097	8.4.3
OS358	8.4.9
OS347	8.4.8
OS006	8.4.10
OS191	8.4.11
OS399	8.4.16
OS199	8.4.13, 8.4.14
OS227, OS359	8.4.15
OS099	8.4.4,8.4.5,8.4.2
OS256	8.4.6
OS017	8.4.7
OS258	8.4.19
OS383, OS392	8.4.17
OS201	8.4.12
OS501	8.4.20

火龙果•整理
uml.org.cn

Requirement	***Associated API***
OS499	8.4.21

火龙果•整理
uml.org.cn

7 Functional specification

7.1 Core OS

7.1.1 Background & Rationale

The OSEK/VDX Operating System [14] is widely used in the automotive industry and has been proven in use in all classes of ECUs found in modern vehicles. The concepts that OSEK OS has introduced are widely understood and the automotive industry has many years of collective experience in engineering OSEK OS based systems.

OSEK OS is an event-triggered operating system. This provides high flexibility in the design and maintenance of AUTOSAR based systems. Event triggering gives freedom for the selection of the events to drive scheduling at runtime, for example angular rotation, local time source, global time source, error occurrence etc.

For these reasons the core functionality of the AUTOSAR OS shall be based upon the OSEK OS. In particular OSEK OS provides the following features to support concepts in AUTOSAR:

- fixed priority-based scheduling
- facilities for handling interrupts
- only interrupts with higher priority than tasks
- some protection against incorrect use of OS services
- a startup interface through `StartOS()` and the `StartupHook()`
- a shutdown interface through `ShutdownOS()` and the `ShutdownHook()`

OSEK OS provides many features in addition to these. Readers should consult the OSEK specification [14] for details.

Basing AUTOSAR OS on OSEK OS means that legacy applications will be backward compatible – i.e. applications written for OSEK OS will run on AUTOSAR OS. However, some of the features introduced by AUTOSAR OS require restrictions on the use of existing OSEK OS features or extend existing OSEK OS features.

7.1.2 Requirements

OS001: The Operating System module shall provide an API that is backward compatible with the OSEK OS API [14].

7.1.2.1 Restrictions on OSEK OS

It is too inefficient to achieve timing and memory protection for alarm callbacks. They are therefore not allowed in specific scalability classes (OS242)

火龙果•整理
uml.org.cn

OS242: The Operating System module shall only allow Alarm Callbacks in Scalability Class 1.

OSEK OS is required to provide functionality to handle inter-task (internal) communication according to the OSEK COM specification when internal communication only is required in the system. In AUTOSAR, internal communication is provided by the AUTOSAR RTE or by AUTOSAR COM at least one of which will be present for all AUTOSAR ECUs.

AUTOSAR OS, when used in an AUTOSAR system, therefore does not need to support internal communication.

An OSEK OS must implement internal communication if the symbol `LOCALMESSAGESONLY` is defined. AUTOSAR OS can deprecate the need to implement OSEK COM functionality and maintain compatibility with OSEK suite of specifications by ensuring that AUTOSAR OS always exists in an environment where `LOCALMESSAGESONLY` is undefined. This leads to the following requirement:

OS398: The Operating System module shall not define the symbol `LOCALMESSAGESONLY`

OSEK OS has one special resource called `RES_SCHEDULER`. This resource has 2 specific aspects:

1. It is always present in the system, even if it is not configured. This means that the `RES_SCHEDULER` is always known by the OS.
2. It has always the highest Task priority. This means a Task which allocates this resource can not be preempted by other Tasks.

Since special cases are always hard to handle (e.g. in this case with respect to timing protection) AUTOSAR OS handles `RES_SCHEDULER` as any other resource. This means that the `RES_SCHEDULER` is not automatically created. However, a configuration attribute allows that a resource in AUTOSAR OS can optionally be assigned the priority of the highest priority task in the system.

For backwards compatibility with OSEK OS systems, see Chapter 12.8 on how to configure a standard resource called `RES_SCHEDULER` in a way that make it compatible with the resource of the same name which is declared automatically in OSEK OS.

7.1.2.2 Undefined Behaviour in OSEK OS

There are a number of cases where the behaviour of OSEK OS is undefined. These cases represent a barrier to portability. AUTOSAR OS tightens the OSEK OS specification by defining the required behaviour.

OS304: If in a call to `SetRelAlarm()` the parameter “increment” is set to zero, the service shall return `E_OS_VALUE` in standard and extended status .

OS424: The first call to `StartOS()` (for starting the Operating System) shall not return.

火龙果•整理
uml.org.cn

OS425: If `ShutdownOS()` is called and `ShutdownHook()` returns then the Operating System module shall disable all interrupts and enter an endless loop.

7.1.2.3 Extensions to OSEK OS

OS299: The Operating System module shall provide the services `DisableAllInterrupts()`, `EnableAllInterrupts()`, `SuspendAllInterrupts()`, `ResumeAllInterrupts()` prior to calling `StartOS()` and after calling `ShutdownOS()`.

It is assumed that the static variables of the functions mentioned in OS299 are initialized.

OS301: The Operating System module shall provide the ability to increment a software counter as an alternative action on alarm expiry.

The Operating System module provides API service `IncrementCounter()` (see OS399) to increment a software counter.

OS476: The Operating System module shall allow to automatically start preconfigured absolute alarms during the start of the Operating System.

OS476 is an extension to OSEK OS which allows this only for relative alarms.

火龙果•整理
uml.org.cn

7.2 Software Free Running Timer

Due to the fact that the number of timers is often very limited, some functionality and configuration is added to extend the reuse of timers. E.g. this allows timer measurements. For more details see also [5] (SWFRT).

OS374: The Operating System module shall handle all the initialization and configuration of timers used directly by the Operating System module and not handled by the GPT driver.

The Operating System module provides API service `GetCounterValue()` (see OS383) to read the current count value of a counter (returning either the hardware timer ticks if counter is driven by hardware or the software ticks when user drives counter).

The Operating System module provides API service `GetElapsedValue()` (see OS392) to get the number of ticks between the current tick value and a previously read tick value.

OS384: The Operating System module shall adjust the read out values of hardware timers (which drive counters) in such that the lowest value is zero and consecutive reads return an increasing count value until the timer wraps at its modulus.

火龙果•整理
uml.org.cn

7.3 Schedule Tables

7.3.1 Background & Rationale

It is possible to implement a statically defined task activation mechanism using an OSEK counter and a series of auto started alarms. In the simple case, this can be achieved by specifying that the alarms are not modified once started. Run-time modifications can only be made if relative synchronization between alarms can be guaranteed. This typically means modifying the alarms while associated counter tick interrupts are disabled.

Schedule Tables address the synchronization issue by providing an encapsulation of a statically defined set of expiry points. Each expiry point defines:

- one or more actions that must occur when it is processed where an action is the activation of a task or the setting of an event.
- An offset in ticks from the start of the schedule table

Each schedule table has a duration in ticks. The duration is measured from zero and defines the modulus of the schedule table.

At runtime, the Operating System module will iterate over the schedule table, processing each expiry point in turn. The iteration is driven by an OSEK counter. It therefore follows that the properties of the counter have an impact on what is possible to configure on the schedule table.

7.3.2 Requirements

7.3.2.1 Structure of a Schedule Table

Figure 7.1: Anatomy of a Schedule Table

火龙果•整理
uml.org.cn

OS401: A schedule table shall have at least one expiry point.

OS402: An expiry point shall contain a (possibly empty) set of tasks to activate.

OS403: An expiry point shall contain a (possibly empty) set of events to set.

OS404: An expiry point shall contain an offset in ticks from the start of the schedule table.

7.3.2.2 Constraints on Expiry Points

There is no use case for an empty expiry point, so each one must define at least one action.

OS407: An expiry point shall activate at least one task OR set at least one event.

The OS needs to know the order in which expiry points are processed. It is therefore necessary to ensure that the expiry points on a schedule table can be totally ordered. This is guaranteed by forcing each expiry point on a schedule table to have a unique offset.

OS442: : Each expiry point on a given schedule table shall have a unique offset.

Iteration over expiry points on a schedule table is driven by an OSEK counter. The characteristics of the counter – `OsCounterMinCycle` and `OsCounterMaxAllowedValue` – place constraints on expiry point offsets.

OS443: The Initial Offset shall be zero OR in the range `OsCounterMinCycle` .. `OsCounterMaxAllowedValue` of the underlying counter.

Simlarly, constraints apply to the delays between of adjacent expiry points and the delay to the logical end of the schedule table.

OS408: The delay between adjacent expiry points shall be in the range `OsCounterMinCycle` .. `OsCounterMaxAllowedValue` of the underlying counter.

7.3.2.3 Processing Schedule Tables

OS002: The Operating System module shall process each expiry point on a schedule table from the Initial Expiry Point to the Final Expiry Point in order of increasing offset.

OS007: The Operating System module shall permit multiple schedule tables to be processed concurrently.

火龙果•整理
uml.org.cn

OS409: A schedule table of the Operating System module shall be driven by exactly one counter.

OS410: The Operating System module shall be able to process at least one schedule table per counter at any given time.

OS411: The Operating System module shall make use of ticks so that one tick on the counter corresponds to one tick on the schedule table.

It is possible to activate a task and set (one or more unique) events for the same task at the same expiry point. The ordering of task activations and event settings performed from the expiry point could lead to different implementations exhibiting different behaviour (for example, activating a suspended task and then setting and event on the task would succeed but if the ordering was reversed then the event setting would fail). To prevent such non-determinism, it is necessary to enforce a strict ordering of actions on the expiry point.

OS412: The Operating System module shall process all task activations on an expiry point first and then set events.

A schedule table always has a defined state and the following figure illustrates the different states (for a non-synchronized schedule table) and the transitions between them.

Figure 7.2: States of a schedule table

If a schedule table is not active – this means that is not processed by the Operating System – the state is `SCHEDULETABLE_STOPPED`. After starting a schedule tables enters the `SCHEDULETABLE_RUNNING` state where the OS processes the expiry points. If the service to switch a schedule table is called a schedule table enters the the `SCHEDULETABLE_NEXT` state and waits until the “current” schedule table ends.

火龙果•整理
uml.org.cn

7.3.2.4 Repeated Schedule Table Processing

A schedule table may or may not repeat after the final expiry point is processed. This allows two types of behaviour:

1. single-shot – the schedule table processes each expiry point in sequence and then stops at the end. This is useful for triggering a phased sequence of actions in response to some trigger

2. repeating – the schedule table processes each expiry point in turn, After processing the final expiry point, it loops back to the initial expirt point. This is useful for building applications that perform repeated processing or system which need to synchronise processing to a driver source.

A repeating schedule table means that each expiry point is repeated at a period equal to the schedule table duration.

OS413: The schedule table shall be configurable as either single-shot or repeating.

OS009: If the schedule table is single-shot, the Operating System module shall stop the processing of the schedule table Final Delay ticks after the Final Expiry Point is processed.

OS427: If the schedule table is single-shot, the Operating System module shall allow a Final Delay between 0 .. `OsCounterMaxAllowedValue` of the underlying counter.

OS444: For periodic schedule tables the value of Final Delay shall be in the range `OsCounterMinCycle` .. `OsCounterMaxAllowedValue` of the underlying counter.

OS194: After processing the Final Expiry Point, and if the schedule table is repeating, the Operating System shall process the next Initial Expiry Point, after Final Delay plus Initial Offset ticks have elapsed.

7.3.2.5 Controlling Schedule Table Processing

The application is responsible for starting and stopping the processing of a schedule table.

The Operating System module provides the service `StartScheduleTableAbs()` (see OS358) to start the processing of a schedule table at an absolute value “Start” on the underlying counter. (The Initial Expiry Point has to be processed when the value of the underlying counter equals Start + InitialOffset).

The Operating System module provides the service `StartScheduleTableRel()` (see OS347) to start the processing of a schedule table at “Offset” relative to the “Now” value on the underlying counter (The Initial Expiry Point shall be processed when the value of the underlying counter equals Now + Offset + InitialOffset).

火龙果•整理
uml.org.cn

The figure below illustrates the two different methods for a schedule table driven by a counter with a modulus of 65536 (i.e. an `OsCounterMaxAllowedValue = 65535`).

Figure 7.3: Starting a Schedule Table at an Absolute and a Relative Count

The Operating System module provides the service `StopScheduleTable()` (see OS006) to cancel the processing of a schedule table immediately at any point while the schedule table is running.

OS428: If schedule table processing has been cancelled before reaching the Final Expiry Point and is subsequently restarted then OS358/OS347 means that the re-start occurs from the start of the schedule table.

火龙果•整理
uml.org.cn

The Operating System module provides the service `NextScheduleTable()` (see OS191) to switch the processing from one schedule table to another schedule table.

OS414: When a schedule table switch is requested, the Operating System module shall continue to process expiry points on the current schedule table up and including the Final Expiry Point then delay for Final Delay ticks before processing the Initial Expiry Point on the switched-to schedule table (after the initial offset).

The Operating System module provides the service `GetScheduleTableStatus()` (see OS227) to query the state of a schedule table.

Schedule tables can be configured (see chapter 10) to start automatically during start of the Operating System module (like Tasks and Alarms in OSEK OS). OSEK OS defines a specific order: Autostart of Tasks is performed before autostart of alarms. AUTOSAR OS extends this with schedule tables.

OS510: The Operating System module shall perform the autostart of schedule tables during startup after the autostart of Tasks and Alarms.

火龙果•整理
uml.org.cn

7.4 Schedule Table Synchronization

7.4.1 Background & Rationale

The absolute time at which the Initial Expiry Point on a schedule table is processed is under user control. However, if the schedule table repeats then it is not guaranteed that the absolute count value at which the initial expiry point was first processed is the same count value at which it is subsequently processed. This is because the duration of the schedule table need not be equal to the counter modulus.

In many cases it may be important that schedule table expiry points are processed at specific absolute values of the underlying counter. This is called **synchronization**. Typical use-cases include:

- Synchronization of expiry points to degrees of angular rotation for motor management

- Synchronizing the computation to a global (network) time base. Note that in AUTOSAR, the Operating System does not provide a global (network) time source because

  1. a global time may not be needed in many cases
  2. other AUTOSAR modules, most notably FlexRay, provide this independently to the Operating System
  3. if the Operating System is required to synchronize to multiple global (network) time sources (for example when building a gateway between two time-triggered networks) the Operating System cannot be the source of a unique global time.

AUTOSAR OS provides support for synchronization in two ways:

1. implicit synchronization – the counter driving the schedule table is the counter with which synchronization is required. This is typically how synchronization with time-triggered networking technologies (e.g. FlexRay, TTP) is achieved – the underlying hardware manages network time synchronization and simply presents time as an output/compare timer interface to the Operating System. The following figure shows the possible states for schedule tables with implicit synchronization.

火龙果•整理
uml.org.cn

Figure 7.4: States of an implicit synchronized schedule table

2. explicit synchronization – the schedule table is driven by an Operating System counter which is **not** the counter with which synchronization is required. The Operating System provides additional functionality to keep schedule table processing driven by the Operating System counter synchronized with the synchronization counter. This is typically how synchronization with periodically broadcast global times works. The next figure shows the states of such schedule tables.

火龙果•整理
uml.org.cn

Figure 7.5: States of an explicit synchronized schedule table (not all conditions for transitions are shown in the picture)

7.4.2 Requirements

OS013: The Operating System module shall provide the ability to synchronize the processing of schedule table to known counter values.

7.4.2.1 Implicit Synchronization

The Operating System module does not need to provide any additional support for implicit synchronization of schedule tables. However, it is necessary to constrain configuration and runtime control of the schedule table so that ticks on the configured schedule table can be aligned with ticks on the counter. This requires the range of the schedule table to be identical to the range of the counter (the equality of tick resolution of each is guaranteed by the requirements on the schedule table / counter interaction):

OS429: A schedule table of the Operating System module that is implicitly synchronized shall have a Duration equal to `OsCounterMaxAllowedValue + 1` of its associated OSEK OS counter.

To synchronize the processing of the schedule table it must be started at a known counter value. The implication of this is that a schedule table requiring implicit

火龙果•整理
uml.org.cn

synchronization must only be started at an absolute counter value and cannot be started at a relative count value.

OS430: The Operating System module shall prevent a schedule table that is implicitly synchronized from being started at a relative count value.

When the schedule table is started at an absolute counter value each expiry point will be processed when the counter equals the value specified in the service call plus expiry point's offset. The common use-case is to ensure that the offsets specified in the schedule table configuration correspond to absolute values of the underlying counter. This is achieved trivially using `StartScheduleTable(Tbl,0)` as shown below.

Figure 7.6: Example for implicit synchronized schedule table

7.4.2.2 Explicit Synchonization

An explicitly synchronized schedule table requires additional support from the Operating System module. The schedule table is driven by an Operating System module's counter as normal (termed the "drive counter") but processing needs to be synchronized with a different counter (termed the "synchronization counter") which is not an Operating System module's counter object.

The following constraints must be enforced between the schedule table, the Operating System module's counter and the synchronization counter:

Constraint1:

OS431: A schedule table that is explicitly synchronized shall have a duration no greater than modulus of the drive counter.

Constraint2:

OS462: A schedule table that is explicitly synchronized shall have a duration equal to the modulus of the synchronization counter.

火龙果•整理
uml.org.cn

Constraint3:

OS463: The synchronization counter shall have the same resolution as the drive counter associated with the schedule table. This means that a tick on the schedule table has the same duration as a tick on the synchronization counter.

Note that it is in the responsibility of the Operating System module user to verify that Constraints 2 and 3 are satisfied by their system.

The function of explicit synchronization is for the Operating System module to keep processing each expiry point at absolute value of the synchronization counter equal to the expiry point's offset. This means that explicit synchronization always assumes that the notional zero of the schedule table has to be synchronized with absolute value zero on the synchronization counter.

To achieve this, the Operating System module must be told the value of the synchronization counter by the user. As the modulus of the synchronization counter and the schedule table are identical, the Operating System module can use this information to calculate drift. The Operating System module then automatically adjusts the delay between specially configured expiry points, retarding them or advancing them as appropriate, to ensure that synchronization is maintained.

7.4.2.2.1 Startup

There are two options for starting an explicitly synchronized schedule table:

1. Asynchronous start: Start the schedule table at an arbitrary value of the synchronization counter.
2. Synchronous start: Start the schedule table at absolute value zero of the synchronization counter only after a synchronization count has been provided. This may mean waiting for first synchronization indefinitely.

Asynchronous start is provided by the existing absolute and relative schedule table start services. Both of these services set the point at which the initial expiry point is processed with respect to the driver counter not the synchronization counter. This allows the schedule table to start running before the value of the synchronization counter is known.

Synchronous start requires an additional service that starts the schedule table only after the Operating System module is told the value of the synchronization counter.

The Operating System module provides the service `StartScheduleTableSynchron()` (see OS201) to start an explicitly synchronized schedule table synchronously. The Initial Expiry Point will be processed after (Duration – Value) + Initial Offset ticks of the driver counter have elapsed where Value is the absolute value of the synchronization counter provided to the schedule table.

火龙果•整理
uml.org.cn

OS435: If an explicitly synchronized schedule table was started synchronously, then the Operating System module shall guarantee that it has state “waiting” when the call of service `StartScheduleTableSynchron()` returns.

7.4.2.2.2 Providing a Synchronization Count

The Operating System module must be told the value of the synchronization counter. Since the schedule table duration is equal to the modulus of the synchronization counter, the Operating System module can use this to determine the drift between the current count value on the schedule table time and the synchronization count and decide whether (or not) any action to achieve synchronization is required.

The Operating System module provides the service `SyncScheduleTable()` (see OS199) to provide the schedule table with a synchronization count and start synchronization.

7.4.2.2.3 Specifying Synchronization Bounds

A schedule table defaults to denying adjustment at all expiry points. Adjustment is allowed only when explicitly configured. The range of adjustment that the Operating System module can make at an adjustable expiry point is controlled by specifying:

- `OsScheduleTableMaxRetard` : the maximum value that can be subtracted from the expiry offset
- `OsScheduleTableMaxAdvance`: the maximum value that can be added to the expiry point offset

The following figure illustrates the behaviour depending on `OsScheduleTableMaxRetard` and `OsScheduleTableMaxAdvance`:

火龙果•整理
uml.org.cn

Figure 7.7: Adjustment of Exipry Points

火龙果•整理
uml.org.cn

So called “hard” and “smooth” synchronization from OSEKtime [15] are supported by this single unified concept in AUTOSAR OS. “Smooth” synchronization may be emulated by setting the small adjustment values on the final expiry point. “Hard” synchronization may be emulated by setting large adjustment values on the final expiry point.

OS415: An expiry point shall permit the configuration of a `OsScheduleTableMaxRetard` that defines the maximum number of ticks that can be subtracted from expiry point offset.

OS416: An expiry point shall permit the configuration of a `OsScheduleTableMaxAdvance` that defines the maximum number of ticks that can be added to expiry point offset.

When performing synchrioniszation it is important that the expiry points on the schedule table are processed according to the total ordering defined by their offsets. This means that the range of permitted values for `OsScheduleTableMaxRetard` and `OsScheduleTableMaxAdvance` must ensure that the next expiry point is not retarded into the past or advanced beyond more than one iteration of the schedule table.

OS436: The value of (Offset – `OsScheduleTableMaxRetard`) of an expiry point shall be greater than (Offset + `OsCounterMinCycle`) of the pervious expiry point.

OS437: The value of (`OsScheduleTableMaxAdvance + delay_to_next_EP`) of an expiry point shall be less than the duration of the schedule table.

Explicitly synchronized schedule tables allow the tolerance of some drift between the schedule table value and the synchronization counter value. This tolerance can be zero, indicating that the schedule table is not considered synchronized unless the values are indentical..

OS438: A schedule table shall define a precision bound with a value in the range 0 to duration.

7.4.2.3 Performing Synchronization

The Operating System module uses the synchronization count to support (re-)synchronization of a schedule table at each expiry point by calculating an adjustment to the delay to the next expiry point. This provides faster re-synchronization of the schedule table than doing the action on the final expiry point.

OS206: When a new synchronization count is provided, the Operating System module shall calculate the current deviation between the explicitly synchronized scheduled table and the synchronization count.

火龙果•整理
uml.org.cn

It is meaningless to try and synchronise an explicitly synchronized schedule table before a synchronization count is provided.

OS417: The Operating System module shall start to synchronise an explicitly synchronized schedule table after a synchronization count is provided AND shall continue to adjust expiry points until synchronized.

OS418: The Operating System module shall set the state of an explicitly synchronized schedule table to “running and synchronous” if the deviation is less than or equal to the configured `OsScheduleTblExplicitPrecision` threshold.

OS419: The Operating System module shall set the state of an explicitly synchronized schedule table to “running” if the deviation is greater than the configured `OsScheduleTblExplicitPrecision` threshold.

OS420: IF the deviation is non-zero AND the next expiry point is adjustable AND the table is ahead of the sync counter (TableTicksAheadOfSyncCounter <= TableTicksBehindOfSyncCounter) THEN the OS shall set the next EP to expire delay - min(MaxRetard, Deviation) ticks from the current expiry.

OS421: IF the deviation is non-zero AND the next expiry point is adjustable AND the table is behind the sync counter (TableTicksAheadOfSyncCounter > TableTicksBehindOfSyncCounter) THEN the OS shall set the next EP to expire delay + min(MaxAdvance, Deviation) ticks from the current expiry.

Figure 7.8: shows explicit synchronization of a schedule table. It assumes the following:

- EP1-3 have `OsScheduleTableMaxAdvance`=2
- EP1-3 have `OsScheduleTableMaxRetard` =1

火龙果•整理
uml.org.cn

Figure 7.8: Explict Schedule Table Synchronization

The Operating System module provides the service `SetScheduleTableAsync()` (see OS422) to cancel synchronization being performed at adjustable expiry points on a schedule table.

The Operating System module provides the service `GetScheduleTableStatus()` (see OS227) to query the state of a schedule table also with respect to synchronization.

7.5 Stack Monitoring Facilities

7.5.1 Background & Rationale

On processors that do not provide any memory protection hardware it may still be necessary to provide a “best effort with available resources” scheme for detectable classes of memory faults. Stack monitoring will identify where a task or ISR has exceeded a specified stack usage at context switch time. This may mean that there is considerable time between the system being in error and that fault being detected. Similarly, the error may have been cleared at the point the fault is notified (the stack may be less than the specified size when the context switch occurs).

It is not usually sufficient to simply monitor the entire stack space for the system because it is not necessarily the Task/ISR that was executing that used more than stack space than required – it could be a lower priority object that was pre-empted.

火龙果•整理
uml.org.cn

Significant debugging time can be saved by letting the Operating System correctly identify the Task/Category 2 ISR in error.

Note that for systems using a MPU and scalability class 3 or 4 a stack overflow may cause a memory exception before the stack monitoring is able to detect the fault.

7.5.2 Requirements

OS067: The Operating System module shall provide a stack monitoring which detects possible stack faults of Task(s)/Category 2 ISR(s).

OS068: If a stack fault is detected by stack monitoring AND the configured scalability class is 1 or 2, the Operating System module shall call the `ShutdownOS()` service with the status `E_OS_STACKFAULT`.

OS396: If a stack fault is detected by stack monitoring AND the configured scalability class is 3 or 4, the Operating System module shall call the `ProtectionHook()` with the status `E_OS_STACKFAULT`.

7.6 OS-Application

7.6.1 Background & Rationale

An AUTOSAR OS must be capable of supporting a collection of Operating System objects (Tasks, ISRs, Alarms, Schedule tables, Counters, Resources) that form a cohesive functional unit. This collection of objects is termed an *OS-Application*.

The Operating System module is responsible for scheduling the available processing resource between the OS-Applications that share the processor. If OS-Application(s) are used, all Tasks, ISRs, Resources, Counters, Alarms and Schedule tables must belong to an OS-Application. All objects which belong to the same OS-Application have access to each other. The right to access objects from other OS-Applications may be granted during configuration. An event is accessible if the task for which the event can be set is accessible. Access means that these Operating System objects are allowed as parameters to API services.

There are two classes of OS-Application:

(1) Trusted OS-Applications are allowed to run with monitoring or protection features disabled at runtime. They may have unrestricted access to memory, the Operating System module's API, and need not have their timing behaviour enforced at runtime. They are allowed to run in privileged mode when supported by the processor.

(2) Non-Trusted OS-Applications are not allowed to run with monitoring or protection features disabled at runtime. They have restricted access to

火龙果•整理
uml.org.cn

memory, restricted access to the Operating System module's API and have their timing behaviour enforced at runtime. They are not allowed to run in privileged mode when supported by the processor.

It is assumed that the Operating System module itself is trusted.

There are services offered by the AUTOSAR OS which give the caller information about the access rights and the membership of objects. These services are intended to be used in case of an inter-OS-Application call for checking access rights and arguments.

The running OS-Application is defined as the OS-Application to which the currently running Task or ISR belongs. In case of a hook routine the Task or ISR which caused the call of the hook routine defines the running OS-Application.

Figure 7.9: UML-model of OS-Application

OS-Applications have a state which defines the scope of accessability of its Operating System objects from other OS-Applications. Each OS-Application is always in one of the following states:

火龙果•整理
uml.org.cn

- Active and accessible (APPLICATION_ACCESSIBLE): Operating System objects may be accessed from other OS-Applications. This is the default state at startup.
- Currently in restart phase (APPLICATION_RESTART). Operating System objects can not be accessed from other OS-Applications. State is valid until the OS-Application calls AllowAccess().
- Terminated and not accessible (APPLICATION_TERMINATED): Operating System objects can not be accessed from other OS-Applications. State will not change.

The following figure shows the states and the possible transitions:

Figure 7.13: States of OS-Applications

7.6.2 Requirements

OS445: The Operating System module shall support OS-Applications which are a configurable selection of Trusted Functions, Tasks, ISRs, Alarms, Schedule tables, Counters, Resources, hooks (for startup, error and shutdown).

OS446: The Operating System module shall support the notion of trusted and non-trusted OS-Applications.

OS464: Trusted OS-Applications may offer services ("trusted services") to other (even non-trusted) OS-Applications.

火龙果•整理
uml.org.cn

The Operating System module provides the service `GetApplicationID()` (see OS016) to determine the currently running OS-Application (a unique identifier shall be allocated to each application).

The Operating System module provides the service `CheckObjectOwnership()` (see OS017) to determine to which OS-Application a given Task, ISR, Resource, Counter, Alarm or Schedule Table belongs.

The Operating System module provides the service `CheckObjectAccess()` (see OS256) to determine which OS-Applications are allowed to use the IDs of a Task, ISR, Resource, Counter, Alarm or Schedule Table in API calls.

The Operating System module provides the service `TerminateApplication()` (see OS258) to terminate the OS-Application to which the calling Task/Category 2 ISR/application specific error hook belongs. (This is an OS-Application level variant of the `TerminateTask()` service)

The Operating System provides the service `TerminateApplication()` (see OS258) to terminate another OS-Application AND calls to this service shall be ignored if the caller does not belong to a trusted OS-Application.

OS447: If the Operating System module terminates an OS-Application, then it shall:

- terminate all running, ready and waiting Tasks/ISRs of the OS-Application AND
- disable all interrupts of the OS-Application AND
- stop all active alarms of the OS-Applications AND
- stop all schedule tables of the OS-Application.

OS448: The Operating System module shall prevent access of OS-Applications, trusted or non-trusted, to objects not belonging to this OS-Application, except access rights for such objects are explicitly granted by configuration.

The Operating System provides the service `GetApplicationState()` (see OS499) to request the current state of an OS-Application.

OS500: The Operating System module shall set the state of all OS-Applications after the call of `StartOS()` and before any StartupHook is called to `APPLICATION_ACCESSIBE`.

The Operating System module provides the service `AllowAccess()` (see OS501) to set the own state of an OS-Application from `APPLICATION_RESTARTING` to `APPLICATION_ACCESSIBLE`.

OS502: If an OS-Application is terminated (e.g. through a service call or via protection hook) and no restart is requested, then the Operating System module shall set the state of this OS-Application to `APPLICATION_TERMINATED`.

火龙果•整理
uml.org.cn

OS503: If an OS-Application is terminated (e.g. through a service call or via protection hook) and a restart is requested, then the Operating System module shall set the state of this OS-Application to `APPLICATION_RESTARTING`.

OS504: The Operating System module shall deny access to Operating System objects from other OS-Applications to an OS-Application which is not in state `APPLICATION_ACCESSIBLE`.

OS509: If a service call is made on an Operating System object that is owned by another OS-Application without state `APPLICATION_ACCESSIBLE`, then the Operating System module shall return `E_OS_ACCESS`.

An example for OS509 is a call to ActivateTask() for a task in an OS-Application that is restarting.

7.7 Protection Facilities

Protection is only possible for Operating System managed objects. This means that:

- It is not possible to provide protection during runtime of Category 1 ISRs, because the operating system is not aware of any Category 1 ISRs being invoked. Therefore, if any protection is required, Category 1 ISRs have to be avoided. If Category 1 interrupts AND OS-Applications are used together then all Category 1 ISR must belong to a trusted OS-Application.

- It is not possible to provide protection between functions called from the body of the same Task/Category 2 ISR.

7.7.1 Memory Protection

7.7.1.1 Background & Rationale

Memory protection will only be possible on processors that provide hardware support for memory protection.

The memory protection scheme is based on the (data, code and stack) sections of the executable program.

Stack: An OS-Application comprises a number of Tasks and ISRs. The stack for these objects, by definition, belongs only to the owner object and there is therefore no need to share stack data between objects, even if those objects belong to the same OS-Application.
Memory protection for the stacks of Tasks and ISRs is useful mainly for two reasons:

火龙果•整理
uml.org.cn

(1) Provide a more immediate detection of stack overflow and underflow for the Task or ISR than can be achieved with stack monitoring
(2) Provide protection between constituent parts of and OS-Application, for example to satisfy some safety constraints.

Data: OS-Applications can have private data sections and Tasks/ISRs can have private data sections. OS-Application's private data sections are shared by all Tasks/ISRs belonging to that OS-Application.

Code: Code sections are either private to an OS-Application or can be shared between all OS-Applications (to use shared libraries). In the case where code protection is not used, executing incorrect code will eventually result in a memory, timing or service violation.

7.7.1.2 Requirements

Data Sections and Stack

OS198: The Operating System module shall prevent write access to its own data sections and its own stack from non-trusted OS-Applications.

Private data of an OS-Application

OS026: The Operating System module may prevent read access to an OS-Application's data section attempted by other non-trusted OS-Applications.

OS086: The Operating System module shall permit an OS-Application read and write access to that OS-Application's own private data sections.

OS207: The Operating System module shall prevent write access to the OS-Application's private data sections from other non-trusted OS-Applications.

Private Stack of Task/ISR

OS196: The Operating System module shall permit a Task/Category 2 ISR read and write access to that Task's/Category 2 ISR's own private stack.

OS208: The Operating System module may prevent write access to the private stack of Tasks/Category 2 ISRs of a non-trusted application from all other Tasks/ISRs in the same OS-Application.

OS355: The Operating System module shall prevent write access to all private stacks of Tasks/Category 2 ISRs of an OS-Application from other non-trusted OS-Applications.

Private data of a Task/ISR

火龙果•整理
uml.org.cn

OS087: The Operating System module shall permit a Task/Category 2 ISR read and write access to that Task's/Category 2 ISR's own private data sections.

OS195: The Operating System module may prevent write access to the private data sections of a Task/Category 2 ISR of a non-trusted application from all other Tasks/ISRs in the same OS-Application.

OS356: The Operating System module shall prevent write access to all private data sections of a Task/Category 2 ISR of an OS-Application from other non-trusted OS-Applications.

Code Sections

OS027: The Operating System module may provide an OS-Application the ability to protect its code sections against executing by non-trusted OS-Applications.

OS081: The Operating System module shall provide the ability to provide shared library code in sections that are executable by all OS-Applications.

Peripherals

OS209: The Operating System module shall permit trusted OS-Applications read and write access to peripherals.

OS083: The Operating System module shall allow non-trusted OS-Applications to write to their assigned peripherals only (incl. reads that have the side effect of writing to a memory location).

Memory Access Violation

OS044: If a memory access violation is detected, the Operating System module shall call the Protection Hook with status code `E_OS_PROTECTION_MEMORY`.

7.7.2 Timing Protection

7.7.2.1 Background & Rationale

A timing fault in a real-time system occurs when a task or interrupt misses its deadline at runtime.

AUTOSAR OS does not offer deadline monitoring for timing protection. Deadline monitoring is insufficient to correctly identify the Task/ISR causing a timing fault in an AUTOSAR system. When a deadline is violated this may be due to a timing fault introduced by an unrelated Task/ISR that interferes/blocks for too long. The fault in this case lies with the unrelated Task/ISR and this will propagate through the system until a Task/ISR misses its deadline. The Task/ISR that misses a deadline is therefore not necessarily the Task/ISR that has failed at runtime, it is simply the earliest point that a timing fault is detected.

火龙果•整理
uml.org.cn

If action is taken based on a missed deadline identified with deadline monitoring this would potentially use false evidence of error to terminate a correct OS-Application in favour of allowing an incorrect OS-Application to continue running. The problem is best illustrated by example. Consider a system with the following configuration:

TaskID	Priority	Execution Time	Deadline (=Period)
A	High	1	5
B	Medium	3	10
C	Low	5	15

Assuming that all tasks are ready to run at time zero, the following execution trace would be expected and all tasks would meet their respective deadlines.

Figure 7.10: Example execution trace

Now consider the case when tasks A and B behave incorrectly. The figure below shows both task A and task B executing for longer than specified and task B arriving 2 ticks earlier than specified. Both tasks A and B meet their deadlines. Task C however, behaves correctly but it fails to meet its deadline because of the incorrect execution of Tasks A and B. This is fault propagation – a fault in an unrelated part of the system is causing a correctly functioning part of the system to fail.

火龙果•整理
uml.org.cn

Figure 7.11: Insufficiency of Deadline Monitoring

Whether a task or ISR meets its deadline in a fixed priority preemptive operating system like AUTOSAR OS is determined by the following factors:

(1) the execution time of Task/ISRs in the system

(2) the blocking time that Task/ISRs suffers from lower priority Tasks/ISRs locking shared resources or disabling interrupts

(3) the interarrival rate of Task/ISRs in the system

For safe and accurate timing protection it is necessary for the operating system to control these factors at runtime to ensure that Tasks/ISRs can meet their respective deadlines.

AUTOSAR OS prevents timing errors from (1) by using *execution time protection* to guarantee a statically configured upper bound, called the Execution Budget, on the execution time of:

- Tasks
- Category 2 ISRs

AUTOSAR OS prevents timing errors from (2) by using *locking time protection* to guarantee a statically configured upper bound, called the Lock Budget, on the time that:

- Resources are held by Tasks/Category 2 ISRs
- OS interrupts are suspended by Tasks/Category 2 ISRs
- ALL interrupts are suspended/disabled by Tasks/Category 2 ISRs

AUTOSAR OS prevents timing errors from (3) by using *inter-arrival time protection* to guarantee a statically configured lower bound, called the Time Frame, on the time between:

火龙果•整理
uml.org.cn

- A task being permitted to transition into the `READY` state due to:
  - Activation (the transition from the `SUSPENDED` to the `READY` state)
  - Release (the transition from the `WAITING` to the `READY` state)
- A Category 2 ISR arriving
  An arrival occurs when the Category 2 ISR is recognized by the OS

Inter-arrival time protection for basic tasks controls the time between successive activations, irrespective of whether activations are queued or not. In the case of queued activations, activating a basic task which is in the `READY` or `RUNNING` state is a new activation because it represents the activation of a new instance of the task. Inter-arrival time protection therefore interacts with queued activation to control the rate at which the queue is filled.

Inter-arrival time protection for extended tasks controls the time between successive activations *and* releases. When a task is in the `WAITING` state and multiple events are set with a single call to `SetEvent()` this represents a single release. When a task waits for one or more events which are already set this represents a notional Wait/Release/Start transition and therefore is considered as a new release.

The following figure shows how execution time protection and inter-arrival time protection interact with the task state transition model for AUTOSAR OS.

Figure 7.12: Time protection interaction with the task state transition model

Notes:

火龙果•整理
uml.org.cn

1. Inter-arrival time enforcement on Category 2 ISRs can be used to protect an ECU from a “babbling idiot” source of interrupts (e.g. a CAN controller taking an interrupt each time a frame is received from another ECU on the network) and provides the type of protection given by the OSEKtime Interrupt re-enable schedule event [15].
2. Timing protection only applies to Tasks or Category 2 ISRs. There is no protection for Category 1 ISRs. If timing protection error occurs during a category 1 ISR, consistency of the Operating System module can not be guaranteed. Therefore we discourage timing protection in systems with category 1 interrupts.
3. Timing protection does not apply before the Operating System module is started.
4. In the case of trusted OS-Applications it is essential that all timing information is correct, otherwise the system may fail at run-time. For a non-trusted OS-Application, timing protection can be used to enforce timing boundaries between executable objects.

7.7.2.2 Requirements

OS028: In a non-trusted OS-Application, the Operating System module shall apply timing protection to every Task/Category 2 ISR of this non-trusted OS-Application.

OS089: In a trusted OS-Application, the Operating System module shall provide the ability to apply timing protection to Tasks/Category 2 ISRs of this OS-Application.

OS397: If no OS-Application is configured, the Operating System module shall be able to apply timing protection to Tasks/Category 2 ISRs.

Timing Protection: Tasks

OS064: If a task’s OsTaskExecutionBudget is reached then the Operating System module shall call the `ProtectionHook()` with `E_OS_PROTECTION_TIME`.

OS473: The Operating System module shall reset a task’s OsTaskExecutionBudget on a transition to the `SUSPENDED` or `WAITING` states.

OS465: The Operating System module shall limit the inter-arrival time of tasks to one per OsTaskTimeFrame.

OS469: The Operating System module shall start an OsTaskTimeFrame when a task is activated successfully.

OS472: The Operating System module shall start an OsTaskTimeFrame when a task is released successfully.

OS466: If an attempt is made to activate a task before the end of an OsTaskTimeFrame then the Operating System module shall not perform the activation AND shall call the `ProtectionHook()` with `E_OS_PROTECTION_ARRIVAL`.

火龙果•整理
uml.org.cn

OS467: If an attempt is made to release a task before the end of an OsTaskTimeFrame then the Operating System module shall not perform the release AND shall call the `ProtectionHook()` with `E_OS_PROTECTION_ARRIVAL`.

Timing Protection: ISRs

OS210: If a Category 2 ISR's OsIsrExecutionBudget is reached then the Operating System module shall call the `ProtectionHook()` with `E_OS_PROTECTION_TIME`.

OS474: The Operating System module shall rest an ISR's OsIsrExecutionBudget when the ISR returns control to the Operating terminates.

OS470: The Operating System module shall limit the inter-arrival time of Category 2 ISRs to one per OsIsrTimeFrame.

OS471: The Operating System module shall measure the start of an OsIsrTimeFrame from the point at which it recognises the interrupt (i.e. in the Operating System interrupt wrapper).

OS048: If Category 2 interrupt occurs before the end of the OsIsrTimeFrame then the Operating System module shall not execute the user provided ISR AND shall call the `ProtectionHook()` with `E_OS_PROTECTION_ARRIVAL`.

Timing Protection: Resource Locking and Interrupt Disabling

OS033: If a Task/Category 2 ISR holds an OSEK Resource and exceeds the Os[Task|Isr]ResourceLockBudget, the Operating System module shall call the `ProtectionHook()` with `E_OS_PROTECTION_LOCKED`.

OS037: If a Task/Category 2 ISR disables interrupts (via `Suspend/Disable|All/OS|Interrupts()`) and exceeds the configured Os[Task|Isr][All|OS]InterruptLockBudget, the Operating System module shall call the `ProtectionHook()` with `E_OS_PROTECTION_LOCKED`.

7.7.2.3 Implementation Notes

Execution time enforcement requires hardware support, e.g. a timing enforcement interrupt. If an interrupt is used to implement the time enforcement, the priority of this interrupt has to be high enough to "interrupt" the supervised tasks or ISRs.

Depending on the real hardware support this could mean that DisableAllInterrupts and SuspendAllInterrupts disable not all interrupts (e.g. all interrupts except of the interrupt used for timing protection) or that the usage of Category 1 ISRs – which bypass the Operating System (and also the timing protection) – is limited somehow.

The implementation has to document such implementation specific behaviour (e.g. the limitations when timing protection is used).

火龙果•整理
uml.org.cn

7.7.3 Service Protection

Background & Rationale

As OS-Applications can interact with the Operating System module through services, it is essential that the service calls will not corrupt the Operating System module itself. Service Protection guards against such corruption at runtime.

There are a number of cases to consider with Service Protection: An OS-Application makes an API call

(1) with an invalid handle or out of range value.

(2) in the wrong context, e.g. calling `ActivateTask()` in the `StartupHook()`.

(3) or fails to make an API call that results in the OSEK OS being left in an undefined state, e.g. it terminates without a `ReleaseResource()` call

(4) that impacts on the behaviour of every other OS-Application in the system, e.g. `ShutdownOS()`

(5) to manipulate Operating System objects that belong to another OS-Application (to which it does not have the necessary permissions), e.g. an OS-Application tries to execute `ActivateTask()` on a task it does not own.

The OSEK OS already provides some service protection through the status codes returned from service calls and this will provide the basis for service protection. This means that service protection will only apply for the extended status of OSEK OS.

However, OSEK OS does not cover all the cases outlined above. The following sections describe – besides the mandatory extended status – the additional protection requirements to be applied in each of these cases.

7.7.3.1 Invalid Object Parameter or Out of Range Value

7.7.3.1.1 Background & Rationale

The current OSEK OS' service calls already return `E_OS_ID` on invalid objects (i.e. objects not defined in the OIL file) and `E_OS_VALUE` for out of range values (e.g. setting an alarm cycle time less than `OsCounterMinCycle`).

7.7.3.1.2 Requirements

OS051: If an invalid address (address is not writable by this OS-Application) is passed as an out-parameter to an Operating System service, the Operating System module shall return the status code `E_OS_ILLEGAL_ADDRESS`.

火龙果•整理
uml.org.cn

7.7.3.2 Service Calls Made from Wrong Context

7.7.3.2.1 Background & Rationale

The current OSEK OS defines the valid calling context for service calls ([14], Fig. 12-1), however protects against only a small set of these invalid calls, e.g. calling `TerminateTask()` from a Category 2 ISR.

Service	Task	Cat1 ISR	Cat2 ISR	Error Hook	PreTask Hook	PostTask Hook	Startup Hook	Shutdown Hook	Alarm Callback	Protection Hook
ActivateTask	✓		✓							
TerminateTask	✓		C							
ChainTask	✓		C							
Schedule	✓		C							
GetTaskID	✓		✓	✓	✓	✓				✓
GetTaskState	✓		✓	✓	✓	✓				
DisableAllInterrupts	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
EnableAllInterrupts	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SuspendAllInterrupts	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
ResumeAllInterrupts	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SuspendOSInterrupts	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
ResumeOSInterrupts	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
GetResource	✓		✓							
ReleaseResource	✓		✓							
SetEvent	✓		✓							
ClearEvent	✓		C							
GetEvent	✓		✓	✓	✓	✓				
WaitEvent	✓		C							
GetAlarmBase	✓		✓	✓	✓	✓				
GetAlarm	✓		✓	✓	✓	✓				
SetRelAlarm	✓		✓							
SetAbsAlarm	✓		✓							
CancelAlarm	✓		✓							
GetActiveApplicationMode	✓		✓	✓	✓	✓	✓	✓		
StartOS										
ShutdownOS	✓		✓	✓			✓			
GetApplicationID	✓		✓	✓	✓	✓	✓	✓		✓
GetISRID	✓		✓	✓						✓
CallTrustedFunction	✓		✓							
CheckISRMemoryAccess	✓		✓	✓						✓
CheckTaskMemoryAccess	✓		✓	✓						✓
CheckObjectAccess	✓		✓	✓						✓
CheckObjectOwnership	✓		✓	✓						✓
StartScheduleTableRel	✓		✓							
StartScheduleTableAbs	✓		✓							
StopScheduleTable	✓		✓							

火龙果•整理
uml.org.cn

Service	Task	Cat1 ISR	Cat2 ISR	Error Hook	PreTask Hook	PostTask Hook	Startup Hook	Shutdown Hook	Alarm Callback	Protection Hook
NextScheduleTable	✓		✓							
StartScheduleTableSynchron	✓		✓							
SyncScheduleTable	✓		✓							
GetScheduleTableStatus	✓		✓							
SetScheduleTableAsync	✓		✓							
IncrementCounter	✓		✓							
GetCounterValue	✓		✓							
GetElapsedValue	✓		✓							
TerminateApplication	✓		✓	✓[1]						
AllowAccess	✓		✓							
GetApplicationState	✓		✓	✓	✓	✓	✓	✓		✓

Tab. 1: Allowed Calling Context for OS Service Calls

In the table above "C" indicates that validity is only "Checked in Extended status by E_OS_CALLEVEL" (see [12], section 13.1).

7.7.3.2.2 Requirements

OS088: If an OS-Application makes a service call from the wrong context AND is currently not inside a Category 1 ISR the Operating System module shall not perform the requested action (the service call shall have no effect), and return E_OS_CALLEVEL (see [12], section 13.1) or the "invalid value" of the service.

7.7.3.3 Services with Undefined Behaviour

7.7.3.3.1 Background & Rationale

There are a number of situations where the behaviour of OSEK OS is undefined in extended status. This is unacceptable when protection is required as it would allow the Operating System module to be corrupted through its own service calls. The implementation of service protection for the Operating System module must therefore describe and implement a behaviour that does not jeopardise the integrity of the system or of any OS-Application which did not cause the specific error.

7.7.3.3.2 Requirements

[1] Only in case of self termination.

火龙果•整理
uml.org.cn

Tasks ends without calling a `TerminateTask()` or `ChainTask()`

OS052: If a task returns from its entry function without making a `TerminateTask()` or `ChainTask()` call, the Operating System module shall terminate the task (and call the `PostTaskHook()` if configured).

OS069: If a task returns from its entry function without making a `TerminateTask()` or `ChainTask()` call AND the error hook is configured, the Operating System module shall call the `ErrorHook()` (this is done regardless of whether the task causes other errors, e.g. `E_OS_RESOURCE`) with status `E_OS_MISSINGEND` before the task leaves the `RUNNING` state.

OS070: If a task returns from the entry function without making a `TerminateTask()` or `ChainTask()` call and still holds OSEK Resources, the Operating System module shall release them.

OS239: If a task returns from the entry function without making a `TerminateTask()` or `ChainTask()` call and interrupts are still disabled, the Operating System module shall enable them.

Category 2 ISR ends with locked interrupts or allocated resources

OS368: If a Category 2 ISR calls `DisableAllInterupts()` / `SuspendAllInterrupts()` / `SuspendOSInterrupts()` and ends (returns) without calling the corresponding `EnableAllInterrupts()` / `ResumeAllInterrupts()` / `ResumeOSInterrupts()`, the Operating System module shall perform the missing service and shall call the `ErrorHook()` (if configured) with the status `E_OS_DISABLEDINT`.

OS369: If a Category 2 ISR calls `GetResource()` and ends (returns) without calling the corresponding `ReleaseResource()`, the Operating System module shall perform the `ReleaseResource()` call and shall call the `ErrorHook()` (if configured) with the status `E_OS_RESOURCE` (see [12], section 13.1).

PostTaskHook called during ShutdownOS()

OS071: If the `PostTaskHook()` is configured, the Operating System module shall not call the hook if `ShutdownOS()` is called.

Tasks/ISRs calls EnableAllInterrupts/ResumeAllInterrupts/ResumeOSInterrupts without a corresponding disable

OS092: If `EnableAllInterrupts()` / `ResumeAllInterrupts()` / `ResumeOSInterrupts()` are called and no corresponding `DisableAllInterupts()` / `SuspendAllInterrupts()` / `SuspendOSInterrupts()` was done before, the Operating System module shall not perform this Operating System service.

火龙果•整理
uml.org.cn

Tasks/ISRs calling OS services when DisableAllInterupts/SuspendAllInterrupts/SuspendOSInterrupts called

OS093: If interrupts are disabled/suspended by a Task/ISR and the Task/ISR calls any Operating System service (excluding the interrupt services) then the Operating System module shall ignore the service AND shall return `E_OS_DISABLEDINT` if the service returns a `StatusType` value.

7.7.3.4 Service Restrictions for Non-Trusted OS-Applications

7.7.3.4.1 Background & Rationale

The Operating System service calls available are restricted according to the calling context (see Section 7.7.3.2). In a protected system, additional constraints need to be placed to prevent non-trusted OS-Applications executing API calls that can have a global effect on the system. Each level of restriction is a proper subset of the previous level as shown in the figure below.

Figure 7.13: API Restrictions

There are two defined integrity levels:

1. Trusted
2. Non-Trusted

that correspond exactly with trusted and non-trusted OS-Applications.

7.7.3.4.2 Requirements

火龙果•整理
uml.org.cn

OS054: The Operating System module shall ignore calls to `ShutdownOS()` from non-trusted OS-Applications.

7.7.3.5 Service Calls on Objects in Different OS-Applications

7.7.3.5.1 Background

Section 7.7.3.1 stated that `E_OS_ID` is returned by OSEK OS service calls when the object is invalid. Under the protection scheme a service call can be invalid because the caller does not have valid permissions for the object (a new meaning for multi-OS-Application systems).
This is a similar case to an object not being accessible in OSEK OS (for example, when a task tries to get a resource which exists in the system but has not been configured as used by the task).

7.7.3.5.2 Requirements

OS056: If an OS-object identifier is the parameter of an Operating System module's system service, and no sufficient access rights have been assigned to this OS-object at configuration time (Parameter `Os[...]AccessingApplication`) to the calling Task/Category 2 ISR, the Operating System module's system service shall return `E_OS_ACCESS`.

OS449: CheckTaskMemoryAccess and CheckIsrMemoryAccess check the memory access. Memory access checking is possible for all OS-Applications and from all OS-Applications and does not need granted rights.

OS449 is an exception to OS056.

OS450: CheckObjectAccess checks the access rights for Operating System objects. Checking object access is possible for all OS-Applications and from all OS-Applications and does not need granted rights.

OS450 is an exception to OS056.

7.7.4 Protecting the Hardware used by the OS

7.7.4.1 Background & Rationale

Where a processor supports privileged and non-privileged mode it is usually the case that certain registers, and the instructions to modify those registers, are inaccessible outside the privileged mode.

On such hardware, executing the Operating System module in privileged mode and Tasks/ISRs in non-privileged mode protects the registers fundamental to Operating System module operation from inadvertent corruption by the objects executing in

火龙果•整理
uml.org.cn

non-privileged mode. The Operating System module's services will need to execute in privileged mode as they will need to modify the registers that are protected outside this mode.

The Operating System module can use the control registers of the MPU, timer unit(s), interrupt controller, etc. and therefore it is necessary to protect those registers against non-trusted OS-Applications.

7.7.4.2 Requirements

OS058: If supported by hardware, the Operating System module shall execute non-trusted OS-Applications in non-privileged mode.

OS096: As far as supported by hardware, the Operating System module shall not allow non-trusted OS-Applications to access control registers managed by the Operating System module.

OS245: If an instruction exception occurs (e.g. division by zero) the Operating System module shall call the protection hook with `E_OS_PROTECTION_EXCEPTION`.

7.7.4.3 Implementation Notes

When the Operating System module is running non-trusted OS-Applications, the Operating System module's treatment of interrupt entry and hook routines must be carefully managed.

Interrupt handling: Where the MCU supports different modes (as discussed in this section) ISRs will require the Operating System module to do extra work in the `ISR()` wrapper. ISRs will typically be entered in privileged mode. If the handler is part of a non-trusted OS-Application then the `ISR()` wrapper must make sure that a switch to non-privileged mode occurs before the handler executes.

7.7.5 Providing »Trusted Functions«

7.7.5.1 Background & Rationale

An OS-Application can invoke a Trusted Function provided by (another) trusted OS-Application. That can require a switch from non-privileged to privileged mode. This is typically achieved by these operations:

(1) Each trusted OS-Application may export services which are callable from other OS-Applications.
(2) During configuration these trusted services must be configured to be called from a non-trusted OS-Application.
(3) The call from the non-trusted OS-Application to the trusted service is using a mechanism (e.g. trap/software interrupt) provided by the Operating System.

火龙果•整理
uml.org.cn

The service is passed as an identifier that is used to determine, in the trusted environment, if the service can be called.

(4) The Operating System offers services to check if a memory region is write/read/execute accessible from an OS-Application. It also returns information if the memory region is part of the stack space.

The Operating System software specification does not provide support for »non-trusted services«.

7.7.5.2 Requirements

OS451: The Operating System module shall allow exporting services from trusted OS-Applications.

The Operating System module provides the service `CallTrustedFunction()` (see OS097) to call a trusted function from a (trusted or non-trusted) OS-Application.

OS100: If `CallTrustedFunction()` is called and the called trusted function is not configured the Operating System module shall call the ErrorHook with `E_OS_SERVICEID`.

The Operating System module provides the services `CheckISRMemoryAccess()` and `CheckTaskMemoryAccess()` (see OS512 and OS513) for OS-Applications to check if a memory region is write/read/execute accessible from a Task/Category 2 ISR and also return information if the memory region is part of the stack space.

7.8 Protection Error Handling

7.8.1 Background & Rationale

The Operating System can detect protection errors based on statically configured information on what the constituent parts of an OS-Application can do at runtime. See Section 7.7.

Unlike monitoring, protection facilities will trap the erroneous state at the point the error occurs, resulting in the shortest possible time between transition into an erroneous state and detection of the fault. The different kinds of protection errors are described in the glossary. If a protection error occurs before the Operating System module is started the behaviour is not defined. If a protection error happens during shutdown, e.g. in the application-specific shutdown hook, an endless loop between the shutdown service and the protection hook may occur.

In the case of a protection error, the Operating System module calls a user provided Protection Hook for the notification of protection errors at runtime. The Protection Hook runs in the context of the Operating System module and must therefore be trusted code.

火龙果•整理
uml.org.cn

The Operating System module itself needs only to detect an error and provide the ability to act. The Protection Hook can select one out of four options the Operating System module provides, which will be performed after returning from the Protection Hook, depending on the return value of the Protection Hook. The options are:

1. do nothing
2. forcibly terminate the faulty Task/Category 2 ISR
3. forcibly terminate all tasks and ISRs in the faulty OS-Application
    a. without restart of the OS-Application
    b. with restart of the OS-Application
4. shutdown the Operating System module.

Requirements OS243 and OS244 define the order of the default reaction if no faulty Task/Category 2 ISR or OS-Application can be found, e.g. in the system specific hook routines. Also OS-Applications are only mandatory in Scalability Classes 3 and 4, therefore in other Scalability Classes OS-Applications need not be defined.

Note that forcibly terminating interrupts is handled differently in “forcibly terminate the faulty ISR” and “forcibly terminate the OS-Application”. If a faulty ISR is forcibly terminated, the current invocation of the ISR is terminated. A subsequent invocation is allowed. If the OS-Application is forcibly terminated, then the interrupt source is also disabled, preventing subsequent interrupts.

7.8.2 Requirements

OS211: The Operating System module shall execute the `ProtectionHook()` with the same permissions as the Operating System module.

OS107: If no `ProtectionHook()` is configured and a protection error occurs, the Operating System module shall call `ShutdownOS()`.

OS106: If the `ProtectionHook()` returns `PRO_IGNORE` and was called with `E_OS_PROTECTION_ARRIVAL` the Operating System module shall return control to the user application.

OS553: If the `ProtectionHook()` returns `PRO_TERMINATETASKISR` the Operating System module shall forcibly terminate the faulty Task/Category 2 ISR.

OS554: If the `ProtectionHook()` returns `PRO_TERMINATEAPPL` the Operating System module shall forcibly terminate the faulty OS-Application.

OS555: If the `ProtectionHook()` returns `PRO_TERMINATEAPPL_RESTART` the Operating System module shall forcibly terminate the faulty OS-Application and afterwards restart the OS-Application.

OS556: If the `ProtectionHook()` returns `PRO_SHUTDOWN` the Operating System module shall call the `ShutdownOS()`.

火龙果•整理
uml.org.cn

OS506: If the `ProtectionHook()` is called with `E_OS_PROTECTION_ARRIVAL` the only valid return values are `PRO_IGNORE` or `PRO_SHUTDOWN` [2]. Returning other values will result in a call to `ShutdownOS()`.

OS475: If the `ProtectionHook()` returns `PRO_IGNORE` and the `ProtectionHook()` was not called with `E_OS_PROTECTION_ARRIVAL` then the Operating System module shall call `ShutdownOS()`.

OS243: If the `ProtectionHook()` returns `PRO_TERMINATETASKISR` and no Task or ISR can be associated with the error, the running OS-Application is forcibly terminated by the Operating System module. If even no OS-Application can be assigned, `ShutdownOS()` is called.

OS244: If the `ProtectionHook()` returns `PRO_TERMINATEAPPL` or `PRO_TERMINATEAPPL_RESTART` and no OS-Application can be assigned, `ShutdownOS()` is called.

sOS557: If the `ProtectionHook()` returns `PRO_TERMINATEAPPL_RESTART` and no `OsRestartTask` was configured for the faulty OS-Application, `ShutdownOS()` is called.

OS108: If the Operating System module forcibly terminates a task, it terminates the task, releases all allocated OSEK resources and calls `EnableAllInterrupts()`/ `ResumeOSInterrupts()` / `ResumeAllInterrupts()` if the Task called `DisableAllInterrupts()` / `SuspendOSInterrupts()` / `SuspendAllInterrupts()` before without the corresponding `EnableAllInterrupts()`/ `ResumeOSInterrupts()` / `ResumeAllInterrupts()` call.

OS109: If the Operating System module forcibly terminates an interrupt service routine, it clears the interrupt request, aborts the interrupt service routine (The interrupt source stays in the current state.) and releases all OSEK resources the interrupt service routine has allocated and calls `EnableAllInterrupts()` / `ResumeOSInterrupts()` / `ResumeAllInterrupts()` if the interrupt called `DisableAllInterrupts()` / `SuspendOSInterrupts()` / `SuspendAllInterrupts()` before without the corresponding `EnableAllInterrupts()`/ `ResumeOSInterrupts()` / `ResumeAllInterrupts()` call.

OS110: If the Operating System module shall forcibly terminates an OS-Application, it:shall

- forcibly terminate all Tasks/ISRs of the OS-Application AND
- cancel all alarms of the OS-Application AND
- stop schedule tables of the OS-Application AND
- disable interrupt sources of Category 2 ISRs belonging to the OS-Application

[2] The reason for this case is that the Task which is supervised is not necessary active (and can not be e.g. terminated) and it can be that the caller of the activation is the real problem.

火龙果•整理
uml.org.cn

OS111: When the Operating System module restarts an OS-Application, it shall activate the configured `OsRestartTask`.

7.9 System Scalability

7.9.1 Background & Rationale

In order to customize the operating system to the needs of the user and to take full advantage of the processor features the operating system can be scaled according to the following scalability classes

Feature	Described in Section	Scalability Class 1	Scalability Class 2	Scalability Class 3	Scalability Class 4	Hardware requirements
OSEK OS (all conformance classes)	7.1	✓	✓	✓	✓	
Counter Interface	8.4.16	✓	✓	✓	✓	
SWFRT Interface	8.4.17, 8.4.18	✓	✓	✓	✓	
Schedule Tables	7.3	✓	✓	✓	✓	
Stack Monitoring	7.5	✓	✓	✓	✓	
ProtectionHook	7.8		✓	✓	✓	
Timing Protection	7.7.2		✓		✓	Timer(s) with high priority interrupt
Global Time /Synchronization Support	7.4		✓		✓	Global time source
Memory Protection	7.7.1, 7.7.4			✓	✓	MPU
OS-Applications	7.6, 7.10			✓	✓	
Service Protection	7.7.3			✓	✓	
CallTrustedFunction	7.7.5			✓	✓	(Non-)privileged Modes

Tab. 2: Scalability classes

Feature	Scalability Class 1	Scalability Class 2	Scalability Class 3	Scalability Class 4
Minimum number of Schedule	2	8	2	8

火龙果•整理
uml.org.cn

Tables supported				
Minimum number of OS-Applications supported	0	0	2	2
Minimum number of software Counters supported	8	8	8	8

Tab. 3: Minimum requirements of scalability classes

7.9.2 Requirements

OS240: If an implementation of a lower scalability class supports features of higher classes then the interfaces for the features must comply with this Operating System software specification.

OS241: The Operating System module shall support the features according to the configured scalability class. (See Tab. 2)

OS327: The Operating System module shall always use extended status in Scalability Class 3 and 4.

火龙果•整理
uml.org.cn

7.10 Hook Functions

7.10.1 Background & Rationale

Hook routines as defined in OSEK OS run at the level of the Operating System module and therefore can only belong to the trusted environment. Furthermore, these hook routines are global to the system (system-specific) and will probably be supplied by the ECU integrator.

In AUTOSAR however, each OS-Application may have the need to execute application specific code e.g. initialize some hardware in its own additional (application-specific) startup hook. These are called application specific hook routines. In general the application specific hooks have the same properties as the hook routines described in the OSEK OS specification. Differences are described below.

7.10.2 Requirements

OS439: The Operating System module shall provide the OSEK error macros (`OSError…()`) to all configured error hooks AND there shall be two (like in OIL) global configuration parameters to switch these macros on or off.

<u>StartupHook</u>

OS060: If an application-specific startup hook is configured for an OS-Application `<App>`, the Operating System module shall call `StartupHook_<App>` on startup of the Operating System module.

OS226: The Operating System module shall execute an application-specific startup hook with the access rights of the associated OS-Application.

OS236: If both a system-specific and one (or more) application specific startup hook(s) are configured, the Operating System module shall call the system-specific startup hook before the application-specific startup hook(s).

<u>ShutdownHook</u>

OS112: If an application-specific shutdown hook is configured for an OS-Application `<App>`, the Operating System module shall call `ShutdownHook_<App>` on shutdown of the OS.

OS225: The Operating System module shall execute an application-specific shutdown hook with the access rights of the associated OS-Application.

OS237: If both a system-specific and one (or more) application specific shutdown hook(s) are configured, the Operating System module shall call the system-specific shutdown hook after the application-specific shutdown hook(s).

火龙果•整理
uml.org.cn

Error Hook

OS246: When an error occurs AND an application-specific error hook is configured for the faulty OS-Application `<App>`, the Operating System module shall call that application-specific error hook `ErrorHook_<App>` after the system specific error hook is called (if configured).

OS085: The Operating System module shall execute an application-specific error hook with the access rights of the associated OS-Application.

OS367: Operating System module's services which do not return a `StatusType` shall not raise the error hook(s).

7.11 Error classification

Instead of specifying two versions for production and development errors the AUTOSAR OS provides a finer granularity to adjust the error handling to specific needs, e.g. Scalability Classes, standard and extended status, switching on/off of hook routines.

Type or error	*Relevance*	*Related error code*	*Value*
Service can not be called.	Production	`E_OS_SERVICEID`	`Assigned by implementation`
An invalid address is given as a parameter to a service.	Production	`E_OS_ILLEGAL_ADDRESS`	`Assigned by implementation`
Tasks terminates without a `TerminateTask()` or `ChainTask()` call.	Production	`E_OS_MISSINGEND`	`Assigned by implementation`
A service of the OS is called inside an interrupt disable/enable pair.	Production	`E_OS_DISABLEDINT`	`Assigned by implementation`
A stack fault detected via stack monitoring by the OS	Production	`E_OS_STACKFAULT`	`Assigned by implementation`
A memory access violation occurred	Production	`E_OS_PROTECTION_MEMORY`	`Assigned by implementation`
A Task exceeds its execution time budget	Production	`E_OS_PROTECTION_TIME`	`Assigned by implementation`
A Category 2 ISR exceeds its execution time budget			
A Task/Category 2 ISR arrives before its timeframe has expired	Production	`E_OS_PROTECTION_ARRIVAL`	`Assigned by implementation`
A Task/Category 2 ISR blocks for too long	Production	`E_OS_PROTECTION_LOCKED`	`Assigned by implementation`
A trap occurred	Production	`E_OS_PROTECTION_EXCEPTION`	`Assigned by implementation`

火龙果•整理
uml.org.cn

7.12 Debug support

In order to support debugging AUTOSAR implementations must publish information which can be used for debugging purpose.

OS551: Each variable that shall be accessible by AUTOSAR Debugging, shall be defined as global variable.

OS550: All type definitions of variables which shall be debugged, shall be accessible by the header file Os.h.

OS549:The declaration of variables in the header file shall be such, that it is possible to calculate the size of the variables by C-"sizeof".

火龙果•整理
uml.org.cn

8 API specification

This chapter contains the APIs offered by the operating system. Note that not all services are available in all scalability classes, and that the behavior of some services is extended for specific scalability classes. For example, API to relatively start a schedule table has an additional check if the schedule table allows implicit synchronization. This check is only performed in SC2 and SC4 where synchronization of schedule tables is supported.

8.1 Constants

8.1.1 Error codes of type StatusType

See Section 7.11 and [14].

8.2 Macros

```
OSMEMORY_IS_READABLE(<AccessType>)
OSMEMORY_IS_WRITEABLE(<AccessType>)
OSMEMORY_IS_EXECUTABLE(<AccessType>)
OSMEMORY_IS_STACKSPACE(<AccessType>)
```

These macros return a value not equal to zero if the memory is readable / writable / executable or stack space. The argument of the macros must be of type AccessType. Typically the return value of the service `Check[Task|ISR]MemoryAccess()` is used as argument for these macros.

8.3 Type definitions

8.3.1 ApplicationType (for OS-Applications)

Type:	Scalar
Description:	This data type identifies the OS-Application.
Constants of this Type:	`INVALID_OSAPPLICATION`

8.3.2 ApplicationStateType

Type:	Scalar
Description:	This data type identifies the state of an OS-Application.

Constants of this Type:	`APPLICATION_ACCESSIBLE`
	`APPLICATION_RESTARTING`
	`APPLICATION_TERMINATED`

火龙果•整理
uml.org.cn

8.3.3 ApplicationStateRefType

Type:	Pointer
Description:	This data type points to location where a ApplicationStateType can be stored.

8.3.4 TrustedFunctionIndexType

Type:	Scalar
Description:	This data type identifies a trusted function.

8.3.5 TrustedFunctionParameterRefType

Type:	Pointer
Description:	This data type points to a structure which holds the arguments for a call to a trusted function.

8.3.6 AccessType

Type:	Integral
Description:	This type holds information how a specific memory region can be accessed.

8.3.7 ObjectAccessType

Type :	Scalar
Description:	This data type identifies if an OS-Application has access to an object.
Constants of this Type:	`ACCESS` `NO_ACCESS`

8.3.8 ObjectTypeType

Type :	Scalar
Description :	This data type identifies an object.

Constants of this Type:	`OBJECT_TASK`
	`OBJECT_ISR`
	`OBJECT_ALARM`
	`OBJECT_RESOURCE`
	`OBJECT_COUNTER`
	`OBJECT_SCHEDULETABLE`

8.3.9 MemoryStartAddressType

Type:	Pointer
Description:	This data type is a pointer which is able to point to any location in the MCU address space.

火龙果•整理
uml.org.cn

8.3.10 MemorySizeType

Type:	Scalar
Description:	This data type holds the size (in bytes) of a memory region.

8.3.11 ISRType

Type:	Scalar
Description:	This data type identifies an interrupt service routine (ISR).
Constants of this Type:	`INVALID_ISR`

8.3.12 ScheduleTableType

Type:	Scalar
Description:	This data type identifies a schedule table.

8.3.13 ScheduleTableStatusType

Type:	Scalar
Description:	This type describes the status of a schedule. The status can be one of the following: o The schedule table is not started (`SCHEDULETABLE_STOPPED`) o The schedule table will be started after the end of currently running schedule table (schedule table was used in `NextScheduleTable()` service) (`SCHEDULETABLE_NEXT`) o The schedule table uses explicit synchronization, has been started and is waiting for the global time. (`SCHEDULETABLE_WAITING`) o The schedule table is running, but is currently not synchronous to a global time source (`SCHEDULETABLE_RUNNING`) o The schedule table is running and is synchronous to a global time source (`SCHEDULETABLE_RUNNING_AND_SYNCHRONOUS`)

Constants of this Type:	`SCHEDULETABLE_STOPPED`
	`SCHEDULETABLE_NEXT`
	`SCHEDULETABLE_WAITING`
	`SCHEDULETABLE_RUNNING`
	`SCHEDULETABLE_RUNNING_AND_SYNCHRONOUS`

8.3.14 ScheduleTableStatusRefType

Type:	Pointer
Description:	This data type points to a variable of the data type ScheduleTableStatusType.

8.3.15 CounterType

Type:	Scalar

火龙果•整理
uml.org.cn

Description:	This data type identifies a counter.

8.3.16 ProtectionReturnType

Type:	Scalar
Description:	This data type identifies a value which controls further actions of the OS on return from the protection hook.

Constants of this Type:	`PRO_IGNORE`
	`PRO_TERMINATETASKISR`
	`PRO_TERMINATEAPPL`
	`PRO_TERMINATEAPPL_RESTART`
	`PRO_SHUTDOWN`

8.3.17 RestartType

Type:	Scalar
Description:	This data type defines the use of a Restart Task after terminating an OS-Application.
Constants of this Type:	`RESTART` `NO_RESTART`

8.3.18 PhysicalTimeType

Type:	Scalar
Description:	This data type is used for values returned by the conversion macro (see OS393()) `OS_TICKS2<Unit>_<Counter>()`.

8.4 Function definitions

The availability of the following services is defined in Tab. 2. The use of these services may be restricted depending on the context they are called from. See Tab. 1 for details.

8.4.1 GetApplicationID

OS016:

Service name:	GetApplicationID

Syntax:	`ApplicationType GetApplicationID(`
	`void`
	`)`

Service ID[hex]:	0x00
Sync/Async:	Synchronous
Reentrancy:	Reentrant
Parameters (in):	None
Parameters (inout):	None

火龙果•整理
uml.org.cn

Parameters (out):	None	
Return value:	ApplicationType	<identifier of running OS-Application> or INVALID_OSAPPLICATION
Description:	This service determines the currently running OS-Application (a unique identifier has to be allocated to each application).	

OS261: `GetApplicationID()` shall return the application identifier to which the executing Task/ISR/hook belongs.

OS262: If no OS-Application is running, `GetApplicationID()` shall return `INVALID_OSAPPLICATION`.

OS514: Availability of `GetApplicationID()`: Available in Scalability Classes 3 and 4.

8.4.2 GetISRID

OS511:

Service name:	GetISRID	
Syntax:	`ISRType GetISRID( void )`	
Service ID[hex]:	0x01	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	None	
Parameters (inout):	None	
Parameters (out):	None	
Return value:	ISRType	<Identifier of running ISR> or INVALID_ISR
Description:	This service returns the identifier of the currently executing ISR.	

OS263: If called from category 2 ISR (or Hook routines called inside a category 2 ISR), `GetISRID()` shall return the identifier of the currently executing ISR.

OS264: If its caller is not a category 2 ISR (or Hook routines called inside a category 2 ISR), `GetISRID()` shall return `INVALID_ISR`.

OS515: Availability of `GetISRID()`: Available in all Scalability Classes.

8.4.3 CallTrustedFunction

OS097:

Service name:	CallTrustedFunction
Syntax:	`StatusType CallTrustedFunction( TrustedFunctionIndexType FunctionIndex, TrustedFunctionParameterRefType FunctionParams )`
Service ID[hex]:	0x02
Sync/Async:	Depends on called function. If called function is synchronous then service is

火龙果•整理
uml.org.cn

	synchronous. May cause rescheduling.	
Reentrancy:	Reentrant	
Parameters (in):	FunctionIndex	Index of the function to be called.
	FunctionParams	Pointer to the parameters for the function - specified by the FunctionIndex - to be called. If no parameters are provided, a NULL pointer has to be passed.
Parameters (inout):	None	
Parameters (out):	None	
Return value:	StatusType	E_OK: No Error E_OS_SERVICEID: No function defined for this index
Description:	A (trusted or non-trusted) OS-Application uses this service to call a trusted function	

OS265: If <FunctionIndex> is a defined function index, `CallTrustedFunction()` shall switch the processor into privileged mode AND shall call the function <FunctionIndex> out of a list of implementation specific trusted functions with disabled memory protection AND shall return `E_OK` after completion.

OS312: Caveats of `CallTrustedFunction()`:

- The called trusted function must conform to the following C prototype: `void TRUSTED_<name_of_the_trusted_service>( TrustedFunctionIndexType,TrustedFunctionParameterRefType);` (The arguments are the same as the arguments of CallTrustedFunction).
- Normally, a user will not directly call this service, but it will be part of some standard interface, e.g. a standard I/O interface.
- It is the duty of the called trusted function to check rights of passed parameters, especially if parameters are interpreted as out parameters.
- It should be noted that the `CallTrustedFunction()` does not disable timing protection for the task which called the service. This may lead to timing faults (calls of the `ProtectionHook()`) even inside of a trusted OS-Application. It is therefore recommended to use `CallTrustedFunction()` only for stateless functions (e.g. functions which do not write or do not have internal states)

OS266: When `CallTrustedFunction()` calls the function <FunctionIndex>, that function shall be executed with the same processor mode and memory protection boundaries as the OS-Application to which it belongs. It shall however retain the timing protection and service protection limitations of the calling Task or ISR, and the notion of "current application" shall remain that of the calling Task or Category 2 ISR.

OS364: If `CallTrustedFunction()` calls the trusted function from a Category 2 ISR context, that function shall continue to run on the same interrupt priority and be allowed to call all system services defined for Category 2 ISR (see table in chapter 7.7.3.2).

OS365: If `CallTrustedFunction()` calls the trusted function from a task context, that function shall continue to run on the same priority and be allowed to call all system services defined for tasks (see table in chapter 7.7.3.2).

火龙果•整理
uml.org.cn

OS292: If the function index <FunctionIndex> in a call of `CallTrustedFunction()` is undefined, `CallTrustedFunction()` shall return `E_OS_SERVICEID`.

OS516: Availability of `CallTrustedFunction()`: Available in Scalability Classes 3 and 4.

8.4.4 CheckISRMemoryAccess

OS512:

Service name:	CheckISRMemoryAccess	

Syntax:	`AccessType CheckISRMemoryAccess(`
	`  ISRType ISRID,`
	`  MemoryStartAddressType Address,`
	`  MemorySizeType Size`
	`)`	

Service ID[hex]:	0x03	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	ISRID	ISR reference
	Address	Start of memory area
	Size	Size of memory area
Parameters (inout):	None	
Parameters (out):	None	
Return value:	AccessType	Value which contains the access rights to the memory area.
Description:	This service checks if a memory region is write/read/execute accessible and also returns information if the memory region is part of the stack space.	

OS267: If the ISR reference <ISRID> in a call of `CheckISRMemoryAccess()` is valid, `CheckISRMemoryAccess()` shall return the access rights of the ISR on the specified memory area.

OS313: If an access right (e.g. “read”) is not valid for the whole memory area specified in a call of `CheckISRMemoryAccess()`, `CheckISRMemoryAccess()` shall yield no access regarding this right.

OS268: If the ISR reference <ISRID> is not valid, `CheckISRMemoryAccess()` shall yield no access rights.

OS517: Availability of `CheckISRMemoryAccess()`: Available in Scalability Classes 3 and 4.

8.4.5 CheckTaskMemoryAccess

OS513:

Service name:	CheckTaskMemoryAccess

Syntax:	`AccessType CheckTaskMemoryAccess(`
	`  TaskType TaskID,`
	`  MemoryStartAddressType Address,`

火龙果•整理
uml.org.cn

	`MemorySizeType Size`)	
Service ID[hex]:	0x04	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	TaskID	Task reference
	Address	Start of memory area
	Size	Size of memory area
Parameters (inout):	None	
Parameters (out):	None	
Return value:	AccessType	Value which contains the access rights to the memory area.
Description:	This service checks if a memory region is write/read/execute accessible and also returns information if the memory region is part of the stack space.	

OS269: If the Task reference <TaskID> in a call of `CheckTaskMemoryAccess()` is valid, `CheckTaskMemoryAccess()` shall return the access rights of the task on the specified memory area.

OS314: If an access right (e.g. “read”) is not valid for the whole memory area specified in a call of `CheckTaskMemoryAccess()`, `CheckTaskMemoryAccess()` shall yield no access regarding this right.

OS270: If the Task reference <TaskID> in a call of `CheckTaskMemoryAccess()` is not valid, `CheckTaskMemoryAccess()` shall yield no access rights.

OS518: Availability of `CheckTaskMemoryAccess()`: Available in Scalability Classes 3 and 4

8.4.6 CheckObjectAccess

OS256:

Service name:	CheckObjectAccess	

Syntax:	`ObjectAccessType CheckObjectAccess(`
	`ApplicationType ApplID,`
	`ObjectTypeType ObjectType,`
	`void ...`
	)	

Service ID[hex]:	0x05	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	ApplID	OS-Application identifier
	ObjectType	Type of the following parameter
	...	The object to be examined
Parameters (inout):	None	
Parameters (out):	None	
Return value:	ObjectAccessType	ACCESS if the ApplID has access to the object NO_ACCESS otherwise
Description:	This service determines if the OS-Applications, given by ApplID, is allowed to use the IDs of a Task, ISR, Resource,	

火龙果•整理
uml.org.cn

	Counter, Alarm or Schedule Table in API calls.

OS271: If the OS-Application <ApplID> in a call of `CheckObjectAccess()` has access to the queried object, `CheckObjectAccess()` shall return `ACCESS`.

OS272: If the OS-Application <ApplID> in a call of `CheckObjectAccess()` has no access to the queried object, `CheckObjectAccess()` shall return `NO_ACCESS`.

OS423: If in a call of `CheckObjectAccess()` the object to be examined is not a valid object OR <ApplID> is invalid OR <ObjectType> is invalid THEN `CheckObjectAccess()` shall return `NO_ACCESS`.

OS519: Availability of `CheckObjectAccess()`: Available in Scalability Classes 3 and 4.

8.4.7 CheckObjectOwnership

OS017:

Service name:	CheckObjectOwnership	

Syntax:	`ApplicationType CheckObjectOwnership(`
	`  ObjectTypeType ObjectType,`
	`  void ...`
	`)`	

Service ID[hex]:	0x06	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	ObjectType	Type of the following parameter
	...	The object to be examined
Parameters (inout):	None	
Parameters (out):	None	
Return value:	ApplicationType	<OS-Application>: the OS-Application to which the object ObjectType belongs or INVALID_OSAPPLICATION if the object does not exists
Description:	This service determines to which OS-Application a given Task, ISR, Resource, Counter, Alarm or Schedule Table belongs	

OS273: If the object ObjectType specified in a call of `CheckObjectOwnership()` exists, `CheckObjectOwnership()` shall return the identifier of the OS-Application to which the object belongs.

OS274: If in a call of `CheckObjectOwnership()` the specified object ObjectType is invalid OR the argument of the type (the "…") is invalid, `CheckObjectOwnership()` shall return `INVALID_OSAPPLICATION`.

OS520: Availability of `CheckObjectOwnership()`:Available in Scalability Classes 3 and 4.

火龙果•整理
uml.org.cn

8.4.8 StartScheduleTableRel

OS347:

Service name:	StartScheduleTableRel	
Syntax:	`StatusType StartScheduleTableRel( ScheduleTableType ScheduleTableID, TickType Offset )`	
Service ID[hex]:	0x07	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	ScheduleTableID	Schedule table to be started
	Offset	Number of ticks on the counter before the the schedule table processing is started
Parameters (inout):	None	
Parameters (out):	None	
Return value:	StatusType	E_OK: No Error E_OS_ID (only in EXTENDED status): ScheduleTableID not valid. E_OS_VALUE (only in EXTENDED status): Offset is greater than (OsCounterMaxAllowedValue - InitialOffset) or is equal to 0. E_OS_STATE: Schedule table was already started.
Description:	This service starts the processing of a schedule table at "Offset" relative to the "Now" value on the underlying counter.	

OS275: If the schedule table <ScheduleTableID> in a call of `StartScheduleTableRel()` is not valid, `StartScheduleTableRel()` shall return `E_OS_ID`.

OS452: If the schedule table <ScheduleTableID> in a call of `StartScheduleTableRel()` is implicitely synchronized (`OsScheduleTblSyncStrategy = IMPLICIT`), `StartScheduleTableRel()` shall return `E_OS_ID`.

OS332: If <Offset> in a call of `StartScheduleTableRel()` is zero `StartScheduleTableRel()` shall return `E_OS_VALUE`.

OS276: If the offset <Offset>) is greater than `OsCounterMaxAllowedValue` of the underlying counter minus the Initial Offset, `StartScheduleTableRel()` shall return `E_OS_VALUE`.

OS277: If the schedule table <ScheduleTableID> in a call of `StartScheduleTableRel()` is not in the state `SCHEDULETABLE_STOPPED`, `StartScheduleTableRel()` shall return `E_OS_STATE`.

OS278: If the input parameters of `StartScheduleTableRel()` are valid and the state of schedule table <ScheduleTableID> is `SCHEDULETABLE_STOPPED`, then `StartScheduleTableRel()` shall start the processing of a schedule table <ScheduleTableID>. The Initial Expiry Point shall be processed after <Offset> + Initial Offset ticks have elapsed on the underlying counter. The state of

火龙果•整理
uml.org.cn

<ScheduleTableID> is set to SCHEDULETABLE_RUNNING before the service returns to the caller.

OS521: Availability of StartScheduleTableRel(): Available in all Scalability Classes.

8.4.9 StartScheduleTableAbs

OS358:

Service name:	StartScheduleTableAbs	

Syntax:	`StatusType StartScheduleTableAbs(`
	`  ScheduleTableType ScheduleTableID,`
	`  TickType Start`
	`)`	

Service ID[hex]:	0x08	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	ScheduleTableID	Schedule table to be started
	Start	Absolute counter tick value at which the schedule table is started
Parameters (inout):	None	
Parameters (out):	None	
Return value:	StatusType	E_OK: No Error E_OS_ID (only in EXTENDED status): ScheduleTableID not valid E_OS_VALUE (only in EXTENDED status): Tickvalue is greater than OsCounterMaxAllowedValue E_OS_STATE: Schedule table was already started
Description:	This service starts the processing of a schedule table at an absolute value "Start" on the underlying counter.	

OS348: If the schedule table <ScheduleTableID> in a call of StartScheduleTableAbs() is not valid, StartScheduleTableAbs() shall return E_OS_ID.

OS349: If the <Start> in a call of StartScheduleTableAbs() is greater than the OsCounterMaxAllowedValue of the underlying counter, StartScheduleTableAbs() shall return E_OS_VALUE.

OS350: If the schedule table <ScheduleTableID> in a call of StartScheduleTableAbs() is not in the state SCHEDULETABLE_STOPPED, StartScheduleTableAbs() shall return E_OS_STATE.

OS351: If the input parameters of StartScheduleTableAbs() are valid and <ScheduleTableID> is in the state SCHEDULETABLE_STOPPED, StartScheduleTableAbs() shall start the processing of schedule table <ScheduleTableID> when the underlying counter next equals <Start> and shall set the state of <ScheduleTableID> to
- SCHEDULETABLE_RUNNING (for a non-synchronized / Explicitly synchronized schedule table) OR

火龙果•整理
uml.org.cn

- SCHEDULETABLE_RUNNING_AND_SYNCHRONOUS (for implicitly synchronized schedule table)
before returning to the user. (The Initial Expiry Point will be processed when the underlying counter next equals <Start>+Initial Offset).

OS522: Availability of StartScheduleTableRel(): Available in all Scalability Classes.

8.4.10 StopScheduleTable

OS006:

Service name:	StopScheduleTable	

Syntax:	`StatusType StopScheduleTable(`
	`  ScheduleTableType ScheduleTableID`
	`)`	

Service ID[hex]:	0x09	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	ScheduleTableID	Schedule table to be stopped
Parameters (inout):	None	
Parameters (out):	None	
Return value:	StatusType	E_OK: No Error E_OS_ID (only in EXTENDED status): ScheduleTableID not valid. E_OS_NOFUNC: Schedule table was already stopped
Description:	This service cancels the processing of a schedule table immediately at any point while the schedule table is running.	

OS279: If the schedule table identifier <ScheduleTableID> in a call of StopScheduleTable() is not valid, StopScheduleTable() shall return E_OS_ID.

OS280: If the schedule table with identifier <ScheduleTableID> is in state SCHEDULETABLE_STOPPED when calling StopScheduleTable(), StopScheduleTable() shall return E_OS_NOFUNC.

OS281: If the input parameters of StopScheduleTable() are valid, StopScheduleTable()shall set the state of <ScheduleTableID> to SCHEDULETABLE_STOPPED and (stop the schedule table <ScheduleTableID> from processing any further expiry points and) shall return E_OK.

OS523: Availability of StopScheduleTable(): Available in all Scalability Classes.

8.4.11 NextScheduleTable

OS191:

火龙果•整理
uml.org.cn

Service name:	NextScheduleTable	
Syntax:	`StatusType NextScheduleTable( ScheduleTableType ScheduleTableID_From, ScheduleTableType ScheduleTableID_To )`	
Service ID[hex]:	0x0a	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	ScheduleTableID_From	Currently processed schedule table
	ScheduleTableID_To	Schedule table that provides its series of expiry points
Parameters (inout):	None	
Parameters (out):	None	
Return value:	StatusType	E_OK: No error E_OS_ID (only in EXTENDED status): ScheduleTableID_From or ScheduleTableID_To not valid E_OS_NOFUNC: ScheduleTableID_From not started E_OS_STATE: ScheduleTableID_To is started or next
Description:	This service switches the processing from one schedule table to another schedule table.	

OS282: If the input parameter <ScheduleTableID_From> or <ScheduleTableID_To> in a call of `NextScheduleTable()` is not valid, `NextScheduleTable()` shall return `E_OS_ID`.

OS330: If in a call of `NextScheduleTable()` schedule table <ScheduleTableID_To> is driven by different counter than schedule table <ScheduleTableID_From> then `NextScheduleTable()` shall return an error `E_OS_ID`.

OS283: If the schedule table <ScheduleTableID_From> in a call of `NextScheduleTable()` is in state `SCHEDULETABLE_STOPPED` OR in state `SCHEDULETABLE_NEXT`, `NextScheduleTable()` shall leave the state of <ScheduleTable_From> and <ScheduleTable_To> unchanged and return `E_OS_NOFUNC`.

OS309: If the schedule table <ScheduleTableID_To> in a call of `NextScheduleTable()` is not in state `SCHEDULETABLE_STOPPED`, `NextScheduleTable()` shall leave the state of <ScheduleTable_From> and <ScheduleTable_To> unchanged and return `E_OS_STATE`.

OS484: If `OsScheduleTblSyncStrategy` of <ScheduleTableID_To> in a call of `NextScheduleTable()` is not equal to the `OsScheduleTblSyncStrategy` of <ScheduleTableID_From> then `NextScheduleTable()` shall return `E_OS_ID`.

OS284: If the input parameters of `NextScheduleTable()` are valid then `NextScheduleTable()` shall start the processing of schedule table <ScheduleTableID_To> <ScheduleTableID_From>.FinalDelay ticks after the Final Expiry Point on <ScheduleTableID_From> is processed and shall return `E_OK`.

火龙果•整理
uml.org.cn

NextScheduleTable() shall process the Initial Expiry Point on <ScheduleTableID_To> at <ScheduleTableID_From>.Final Delay + <ScheduleTable_To>.Initial Offset ticks after the Final Expiry Point on <ScheduleTableID_From> is processed .

OS324: If the input parameters of NextScheduleTable() are valid AND the <ScheduleTableID_From> already has a "next" schedule table then NextScheduleTable()shall replace the previous "next" schedule table with <ScheduleTableID_To> and shall change the old "next" schedule table state to SCHEDULETABLE_STOPPED.

OS505: If OsScheduleTblSyncStrategy of the schedule tables <ScheduleTableID_From> and <ScheduleTableID_To> in a call of NextScheduleTable() is EXPLICIT and the Operating System module already synchronizes <ScheduleTableID_From>, NextScheduleTable() shall continue synchonization after the start of processing <ScheduleTableID_To>.

OS453: If the <ScheduleTableID_From> in a call of NextScheduleTable() is stopped, NextScheduleTable() shall not start the "next" schedule table and change its state to SCHEDULETABLE_STOPPED.

OS524: Availability of NextScheduleTable(): Available in all Scalability Classes.

8.4.12 StartScheduleTableSynchron

OS201:

Service name:	StartScheduleTableSynchron	

Syntax:	`StatusType StartScheduleTableSynchron(`
	`  ScheduleTableType ScheduleTableID`
	`)`	

Service ID[hex]:	0x0b	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	ScheduleTableID	Schedule table to be started
Parameters (inout):	None	
Parameters (out):	None	
Return value:	StatusType	E_OK: No Error E_OS_ID (only in EXTENDED status): ScheduleTableID not valid E_OS_STATE: Schedule table was already started
Description:	This service starts an explicitly synchronized schedule table synchronously.	

OS387: If in a call of StartScheduleTableSynchron() the schedule table <ScheduleTableID> is not valid OR the schedule table <ScheduleTableID> is not explicitly synchronized (OsScheduleTblSyncStrategy != EXPLICIT) StartScheduleTableSynchron() shall return E_OS_ID.

火龙果•整理
uml.org.cn

OS388: If the schedule table <ScheduleTableID> in a call of `StartScheduleTableSynchron()`is not in the state `SCHEDULETABLE_STOPPED`, `StartScheduleTableSynchron()` shall return `E_OS_STATE`.

OS389: If <ScheduleTableID> in a call of `StartScheduleTableSynchron()` is valid, `StartScheduleTableSynchron()` shall set the state of <ScheduleTableID> to `SCHEDULETABLE_WAITING` and start the processing of schedule table <ScheduleTableID> after the synchronization count of the schedule table is set via `SyncScheduleTable()`. The Initial Expiry Point shall be processed when (Duration-SyncValue)+InitialOffset ticks have elapsed on the synchronization counter where:

- Duration is <ScheduleTableID>.OsScheduleTableDuration
- SyncValue is the <Value> parameter passed to the `SyncScheduleTable()`
- InitialOffset is the shortest expiry point offset in <ScheduleTableID>

OS525: Availability of `StartScheduleTableSynchron()`: Available in Scalability Classes 2 and 4.

8.4.13 SyncScheduleTable

OS199:

Service name:	SyncScheduleTable	

Syntax:	`StatusType SyncScheduleTable(`
	`  ScheduleTableType ScheduleTableID,`
	`  TickType Value`
	`)`	

Service ID[hex]:	0x0c	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	ScheduleTableID	Schedule table to be synchronized
	Value	The current value of the synchronization counter
Parameters (inout):	None	
Parameters (out):	None	
Return value:	StatusType	E_OK: No errors E_OS_ID (only in EXTENDED status): The ScheduleTableID was not valid or schedule table can not be synchronized (OsScheduleTblSyncStrategy not set or OsScheduleTblSyncStrategy = IMPLICIT) E_OS_VALUE (only in EXETENDED status): The <Value> is out of range E_OS_STATE: The state of schedule table <ScheduleTableID> is equal to SCHEDULETABLE_STOPPED
Description:	This service provides the schedule table with a synchronization count and start synchronization.	

OS454: If the <ScheduleTableID> in a call of `SyncScheduleTable()` is not valid OR schedule table can not be explicitely synchronized

火龙果•整理
uml.org.cn

(OsScheduleTblSyncStrategy is not equal to EXPLICIT) SyncScheduleTable() shall return E_OS_ID.

OS455: If the <Value> in a call of SyncScheduleTable() is greater than the OsScheduleTableDuration, SyncScheduleTable() shall return E_OS_VALUE.

OS456: If the state of the schedule table <ScheduleTableID> in a call of SyncScheduleTable() is equal to SCHEDULETABLE_STOPPED or SCHEDULETABLE_NEXT SyncScheduleTable() shall return E_OS_STATE.

OS457: If the parameters in a call of SyncScheduleTable() are valid, SyncScheduleTable() shall provide the Operating System module with the current synchronization count for the given schedule table. (It is used to synchronize the processing of the schedule table to the synchronization counter.)

OS526: Availability of SyncScheduleTable(): Available in Scalability Classes 2 and 4.

8.4.14 SetScheduleTableAsync

OS422:

Service name:	SetScheduletableAsync	
Syntax:	`StatusType SetScheduletableAsync( ScheduleTableType ScheduleTableID )`	
Service ID[hex]:	0x0d	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	ScheduleTableID	Schedule table for which status is requested
Parameters (inout):	None	
Parameters (out):	None	
Return value:	StatusType	E_OK: No Error E_OS_ID (only in EXTENDED status): Invalid ScheduleTableID
Description:	This service stops synchronization of a schedule table.	

OS362: If SetScheduleTableAsync() is called for a running schedule table, the Operating System module shall stop further synchronization until a SyncScheduleTable() call is made.

OS323: If SetScheduleTableAsync() is called for a running schedule table the Operating System module shall continue to process expiry points on the schedule table.

OS458: If OsScheduleTblSyncStrategy of <ScheduleTableID> in a call of SetScheduleTableAsync() is not equal to EXPLICIT OR if <ScheduleTableID> is invalid then SetScheduleTableAsync() shall return E_OS_ID.

火龙果•整理
uml.org.cn

OS483: If the current state of the <ScheduleTableID> in a call of SetScheduleTableAsync() equals to SCHEDULETABLE_STOPPED, SCHEDULETABLE_NEXT or SCHEDULETABLE_WAITING then SetScheduleTableAsync() shall return E_OS_STATE.

OS300: If the current state of <ScheduleTableID> in a call of SetScheduleTableAsync() equals SCHEDULETABLE_RUNNING_AND_SYNCHRONOUS (or SCHEDULETABLE_RUNNING) then SetScheduleTableAsync() shall set (or keep in case of SCHEDULETABLE_RUNNING) the status of <ScheduleTableID> to SCHEDULETABLE_RUNNING.

OS527: Availability of SetScheduleTableAsync(): Available in Scalability Classes 2 and 4.

8.4.15 GetScheduleTableStatus

OS227:

Service name:	GetScheduleTableStatus	

Syntax:	`StatusType GetScheduleTableStatus(`
	`  ScheduleTableType ScheduleTableID,`
	`  ScheduleTableStatusRefType ScheduleStatus`
	`)`	

Service ID[hex]:	0x0e	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	ScheduleTableID	Schedule table for which status is requested
Parameters (inout):	None	
Parameters (out):	ScheduleStatus	Reference to ScheduleStatusType
Return value:	StatusType	E_OK: No Error E_OS_ID (only in EXTENDED status): Invalid ScheduleTableID
Description:	This service queries the state of a schedule table (also with respect to synchronization).	

OS289: If the schedule table <ScheduleTableID> in a call of GetScheduleTableStatus() is NOT started, GetScheduleTableStatus() shall pass back SCHEDULETABLE_STOPPED via the reference parameter <ScheduleStatus> AND shall return E_OK.

OS353: If the schedule table <ScheduleTableID> in a call of GetScheduleTableStatus() was used in a NextScheduleTable() call AND waits for the end of the current schedule table, GetScheduleTableStatus() shall return SCHEDULETABLE_NEXT via the reference parameter <ScheduleStatus> AND shall return E_OK.

OS354: If the schedule table <ScheduleTableID> in a call of GetScheduleTableStatus() is configured with explicit synchronization AND <ScheduleTableID> was started with StartScheduleTableSynchron()AND no synchronization count was provided to the Operating System,

火龙果•整理
uml.org.cn

`GetScheduleTableStatus()` shall return `SCHEDULETABLE_WAITING` via the reference parameter <ScheduleStatus> AND shall return `E_OK`.

OS290: If the schedule table <ScheduleTableID> in a call of `GetScheduleTableStatus()` is started AND synchronous, `GetScheduleTableStatus()` shall pass back `SCHEDULETABLE_RUNNING_AND_SYNCHRONOUS` via the reference parameter <ScheduleStatus> AND shall return `E_OK`.

OS291: If the schedule table <ScheduleTableID> in a call of `GetScheduleTableStatus()` is started AND NOT synchronous (deviation is not within the precision interval OR the schedule table has been set asynchronous), `GetScheduleTableStatus()` shall pass back `SCHEDULETABLE_RUNNING` via the reference parameter ScheduleStatus AND shall return `E_OK`.

OS293: If the identifier <ScheduleTableID> in a call of `GetScheduleTableStatus()` is NOT valid, `GetScheduleTableStatus()` shall return `E_OS_ID`.

OS528: Availability of `GetScheduleTableStatus()`:Available in all Scalability Classes.

8.4.16 IncrementCounter

OS399:

Service name:	IncrementCounter	

Syntax:	`StatusType IncrementCounter(`
	`  CounterType CounterID`
	`)`	

Service ID[hex]:	0x0f	
Sync/Async:	Synchronous, may cause rescheduling	
Reentrancy:	Reentrant	
Parameters (in):	CounterID	The Counter to be incremented
Parameters (inout):	None	
Parameters (out):	None	
Return value:	StatusType	E_OK: No errors E_OS_ID (only in EXTENDED status): The CounterID was not valid or counter is implemented in hardware and can not be incremented by software
Description:	This service increments a software counter.	

OS285: If the input parameter <CounterID> in a call of `IncrementCounter()` is not valid OR the counter is a hardware counter, `IncrementCounter()` shall return `E_OS_ID`.

OS286: If the input parameter of `IncrementCounter()` is valid, `IncrementCounter()` shall increment the counter <CounterID> by one (if any

火龙果•整理
uml.org.cn

alarm connected to this counter expires, the given action, e.g. task activation, is done) and shall return E_OK.

OS321: If in a call of IncrementCounter() an error happens during the execution of an alarm action, e.g. E_OS_LIMIT caused by a task activation, IncrementCounter() shall call the error hook(s), but the IncrementCounter() service itself shall return E_OK.

OS529: Caveats of IncrementCounter(): If called from a task, rescheduling may take place.

OS530: Availability of IncrementCounter(): Available in all Scalability Classes.

8.4.17 GetCounterValue

OS383:

Service name:	GetCounterValue	

Syntax:	`StatusType GetCounterValue(`
	`  CounterType CounterID,`
	`  TickRefType Value`
	`)`	

Service ID[hex]:	0x10	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	CounterID	The Counter which tick value should be read
Parameters (inout):	None	
Parameters (out):	Value	Contains the current tick value of the counter
Return value:	StatusType	E_OK: No errors E_OS_ID (only in EXTENDED status): The <CounterID> was not valid
Description:	This service reads the current count value of a counter (returning either the hardware timer ticks if counter is driven by hardware or the software ticks when user drives counter).	

OS376: If the input parameter <CounterID> in a call of GetCounterValue() is not valid, GetCounterValue() shall return E_OS_ID.

OS377: If the input parameter <CounterID> in a call of GetCounterValue() is valid, GetCounterValue() shall return the current tick value of the counter via <Value> and return E_OK.

OS531: Caveats of GetCounterValue(): Note that for counters of OsCounterType = HARDWARE the real timer value (the – possibly adjusted – hardware value, see OS384) is returned, whereas for counters of OsCounterType = SOFTWARE the current "software" tick value is returned.

OS532: Availability of GetCounterValue(): Available in all Scalability Classes.

火龙果•整理
uml.org.cn

8.4.18 GetElapsedValue

OS392:

Service name:	GetElapsedValue	

Syntax:	`StatusType GetElapsedValue(`
	`  CounterType CounterID,`
	`  TickRefType Value,`
	`  TickRefType ElapsedValue`
	`)`	

Service ID[hex]:	0x11	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	CounterID	The Counter to be read
Parameters (inout):	Value	in: the previously read tick value of the counter out: the current tick value of the counter
Parameters (out):	ElapsedValue	The difference to the previous read value
Return value:	StatusType	E_OK: No errors E_OS_ID (only in EXTENDED status): The CounterID was not valid E_OS_VALUE (only in EXTENDED status): The given Value was not valid
Description:	This service gets the number of ticks between the current tick value and a previously read tick value.	

OS381: If the input parameter <CounterID> in a call of `GetElapsedValue()` is not valid `GetElapsedValue()` shall return `E_OS_ID`.

OS391: If the <Value> in a call of `GetElapsedValue()` is larger than the max allowed value of the <CounterID>, `GetElapsedValue()` shall return `E_OS_VALUE`.

OS382: If the input parameters in a call of `GetElapsedValue()` are valid, `GetElapsedValue()` shall return the number of elapsed ticks since the given <Value> value via <ElapsedValue> and shall return `E_OK`.

OS460: `GetElapsedValue()` shall return the current tick value of the counter in the <Value> parameter.

OS533: Caveats of `GetCounterValue()`:If the timer already passed the <Value> value a second (or multiple) time, the result returned is wrong. The reason is that the service can not detect such a relative overflow.

OS534: Availability of `GetCounterValue()`: Available in all Scalability Classes.

8.4.19 TerminateApplication

OS258:

Service name:	TerminateApplication
Syntax:	`StatusType TerminateApplication(` `  ApplicationType Application,`

火龙果•整理
uml.org.cn

	RestartType RestartOption)	
Service ID[hex]:	0x12	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	Application	The identifier of the OS-Application to be terminated. If the caller belongs to <Application> the call results in a self termination.
	RestartOption	Either RESTART for doing a restart of the OS-Application or NO_RESTART if OS-Application shall not be restarted.
Parameters (inout):	None	
Parameters (out):	None	
Return value:	StatusType	E_OK: No errors E_OS_ID: <Application> was not valid E_OS_VALUE: <RestartOption> was neither RESTART nor NO_RESTART E_OS_ACCESS: The caller does not have the right to terminate <Application> E_OS_STATE: The state of <Application> does not allow terminating <Application>
Description:	This service terminates the OS-Application to which the calling Task/Category 2 ISR/application specific error hook belongs.	

OS493: If the input parameter <Application> in a call of `TerminateApplication()` is not valid `TerminateApplication()` shall return `E_OS_ID`.

OS459: If the <RestartOption> in a call of `TerminateApplication()` is invalid, `TerminateApplication()` shall return `E_OS_VALUE`.

OS494: If the input parameter <Application> in a call of `TerminateApplication()` is valid AND the caller belongs to a non-trusted OS-Application AND the caller does not belong to <Application> `TerminateApplication()` shall return `E_OS_ACCESS`.

OS507: If the state of <Application> in a call of `TerminateApplication()` is `APPLICATION_TERMINATED` `TerminateApplication()` shall return `E_OS_STATE`.

OS508: If the state of <Application> in a call of `TerminateApplication()` is `APPLICATION_RESTARTING` and the caller does not belong to the <Application> then `TerminateApplication()` shall return `E_OS_STATE`.

OS548: If the state of <Application> in a call of `TerminateApplication()` is `APPLICATION_RESTARTING` AND the caller does belong to the <Application> AND the <RestartOption> is equal `RESTART` then `TerminateApplication()` shall return `E_OS_STATE`.

OS287: If the parameters in a call of `TerminateApplication()` are valid and the above criteria are met `TerminateApplication()` shall terminate <Application> (i.e. to kill all tasks, disable the interrupt sources of those ISRs which belong to the OS-Application and free all other OS resources associated with the application) AND shall activate the configured `OsRestartTask` of <Application> if <RestartOption>

火龙果•整理
uml.org.cn

equals RESTART. If the <Application> is restarted, its state is set to APPLICATION_RESTARTING otherwise to APPLICATION_TERMINATED. If the caller belongs to <Application> TerminateApplication() shall not return, otherwise it shall return E_OK.

OS535: Caveats of TerminateApplication():

- If no applications are configured the implementation shall make sure that this service is not available.
- Tasks and interrupts that are owned by a trusted application can terminate any OS-Application. Tasks and interrupts that are owned by a non-trusted application can only terminate their owning OS-Application.

OS536: Availability of TerminateApplication(): Available in Scalability Classes 3 and 4.

8.4.20 AllowAccess

OS501:

Service name:	AllowAccess	
Syntax:	`StatusType AllowAccess( void )`	
Service ID[hex]:	0x13	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	None	
Parameters (inout):	None	
Parameters (out):	None	
Return value:	StatusType	E_OK: No errors E_OS_STATE:The OS-Application of the caller is in the wrong state
Description:	This service sets the own state of an OS-Application from APPLICATION_RESTARTING to APPLICATION_ACCESSIBLE.	

OS497: If the state of the OS-Application of the caller of AllowAccess() is not APPLICATION_RESTARTING AllowAccess() shall return E_OS_STATE.

OS498: If the state of the OS-Application of the caller of AllowAccess() is APPLICATION_RESTARTING, AllowAccess() shall set the state to APPLICATION_ACCESSIBLE and allow other OS-Applications to access the configured objects of the callers OS-Application.

OS547: Availability of AllowAccess(): Available in Scalability Classes 3 and 4.

8.4.21 GetApplicationState

OS499:

火龙果•整理
uml.org.cn

Service name:	GetApplicationState	

Syntax:	`StatusType GetApplicationState(`
	`  ApplicationType Application,`
	`  ApplicationStateRefType Value`
	`)`	

Service ID[hex]:	0x14	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	Application	The OS-Application from which the state is requested
Parameters (inout):	None	
Parameters (out):	Value	The current state of the application
Return value:	StatusType	E_OK: No errors E_OS_ID: <Application> is not valid
Description:	This service returns the current state of an OS-Application.	

OS495: If the <Application> in a call of `GetApplicationState()` is not valid `GetApplicationState()` shall return `E_OS_ID`.

OS496: If the parameters in a call of `GetApplicationState()` are valid, `GetApplicationState()` shall return the state of OS-Application <Application> in <Value>.

OS537: Availability of `GetApplicationState()`: Available in Scalability Classes 3 and 4.

火龙果•整理
uml.org.cn

8.5 Hook functions

Hook functions are called by the operating system if specific conditions are met. They are provided by the user. Besides the ProtectionHook below, the hooks from [16] and/or extensions from 7.10 may be called by the OS.

8.5.1 Protection Hook

OS538:

Service name:	ProtectionHook	
Syntax:	`ProtectionReturnType ProtectionHook( StatusType Fatalerror )`	
Service ID[hex]:	0x00	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	Fatalerror	The error which caused the call to the protection hook
Parameters (inout):	None	
Parameters (out):	None	
Return value:	ProtectionReturnType	PRO_IGNORE PRO_TERMINATETASKISR PRO_TERMINATEAPPL PRO_TERMINATEAPPL_RESTART PRO_SHUTDOWN The return value defines the action the OS shall take after the protection hook.
Description:	The protection hook is always called if a serious error occurs. E.g. exceeding the worst case execution time or violating against the memory protection.	

Depending on the return value the Operating System module will either:

- forcibly terminate the Task/Category 2 ISR which causes the problem OR
- forcibly terminate the OS-Application the Task/Category 2 ISR belong (optional with restart) OR
- shutdown the system OR
- do nothing

(see 7.8.2)

OS308: If `ProtectionHook()` returns an invalid value, the Operating System module shall take the same action as if no protection hook is configured.

OS542: Availability of `ProtectionHook()`: Available in Scalability Classes 2, 3 and 4.

8.5.2 Application specific StartupHook

OS539:

Service name:	StartupHook_<App>
Syntax:	`void StartupHook_<App>(`

火龙果•整理
uml.org.cn

	`void` `)`
Service ID[hex]:	0x00
Sync/Async:	Synchronous
Reentrancy:	Reentrant
Parameters (in):	None
Parameters (inout):	None
Parameters (out):	None
Return value:	None
Description:	The application specific startup hook is called during the start of the OS (after the user has started the OS via StartOS()).

The application specific StartupHook is always called after the standard StartupHook() (see OS236) . If more than one OS-Application is configured which use startup hooks, the order of calls to the startup hooks of the different OS-Applications is not defined.

OS543: Availability of `StartupHook_<App>()`: Available in Scalability Classes 3 and 4.

8.5.3 Application specific ErrorHook

OS540:

Service name:	ErrorHook_<App>	

Syntax:	`void ErrorHook_<App>(`
	`StatusType Error`
	`)`	

Service ID[hex]:	0x00	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	Error	The error which caused the call to the error hook
Parameters (inout):	None	
Parameters (out):	None	
Return value:	None	
Description:	The application specific error hook is called whenever a Task or Category 2 ISR which belongs to the OS-Application causes an error.	

If the general `ErrorHook()` is configured, the general `ErrorHook()` is called before the application specific error hook is called (see OS246).

OS544: Availability of `ErrorHook_<App>()`: Available in Scalability Classes 3 and 4.

8.5.4 Application specific ShutdownHook

OS541:

Service name:	ShutdownHook_<App>

Syntax:	`void ShutdownHook_<App>(`
	`StatusType Fatalerror`
	`)`

火龙果•整理
uml.org.cn

Service ID[hex]:	0x00	
Sync/Async:	Synchronous	
Reentrancy:	Reentrant	
Parameters (in):	Fatalerror	The error which caused the action to shut down the operating system.
Parameters (inout):	None	
Parameters (out):	None	
Return value:	None	
Description:	The application specific shutdown hook is called whenever the system starts the shut down of itself.	

If the general `ShutdownHook()` is configured, the general `ShutdownHook()` is called after all application specific shutdown hook(s) are called (see OS237). If more OS-Applications with an application specific shutdown hook exist the order of calls to these application specific shutdown hooks is not defined.

OS545: Availability of `ShutdownHook_<App>()`: Available in Scalability Classes 3 and 4.

火龙果•整理
uml.org.cn

9 Sequence diagrams

9.1 Sequence chart for calling trusted functions

Figure 9.1: System Call sequence chart

The above sequence describes a call to the CallTrustedFunction service. It starts with a user who calls a service which requires itself a call to a trusted function. The service then packs the argument for the trusted function into a structure and calls CallTrustedFunction with the ID and the pointer as arguments. Afterwards the OS checks if the access to the requested service is valid. If no access is granted `E_OS_SERVICEID` is returned. Otherwise the trusted service itself is called and the function checks the arguments for access right, etc.

火龙果•整理
uml.org.cn

9.2 Sequence chart for usage of ErrorHook

Figure 9.2: Error Hook sequence chart

The above sequence chart shows the sequence of error hook calls in case a service does not return with E_OK. Note that in this case the general error hook and the OS-Application specific error hook are called.

火龙果•整理
uml.org.cn

9.3 Sequence chart for ProtectionHook

Figure 9.3: Protection Hook sequence chart

The sequence shows the flow of control if a protection error occurs. Depending on the return values of the ProtectionHook, either the faulty Task/ISR is forcibly terminated or the OS-Application is forcibly terminated or the system is shut down. If the action is to terminate the faulty OS-Application an option is to start afterwards the restart task, which can do a cleanup, etc.

火龙果•整理
uml.org.cn

9.4 Sequence chart for StartupHook

Figure 9.4: StartupHook sequence chart

The above sequence shows the flow of control during the startup of the OS. Like in OSEK OS the user calls the `StartOS()` service to start the OS. During the startup the startup hooks are called in the above order. The rest of the startup sequence is identical to the defined behaviour of OSEK OS.

火龙果•整理
uml.org.cn

9.5 Sequence chart for ShutdownHook

The next sequence shows the behaviour in case of a shut down. The flow is the same as in OSEK OS with the exception that the shut down hooks of the OS-Applications are called before the general ShutdownHook is called. Note that the specific shutdown hooks of the application are not allowed to block, they must return to the caller.

Figure 9.5: ShutdownHook sequence chart

火龙果•整理
uml.org.cn

10 Configuration Specification

In general, this chapter defines configuration parameters and their clustering into containers. In order to support the specification Chapter 10.1 describes fundamentals. It also specifies a template (table) you shall use for the parameter specification.

Chapter 10.2 specifies the structure (containers) and the parameters of the module Os.

Chapter 10.3 specifies published information of the module Os.

10.1 How to read this chapter

In addition to this section, it is highly recommended to read the documents:

- AUTOSAR Layered Software Architecture [1]
- AUTOSAR ECU Configuration Specification [10]
  This document describes the AUTOSAR configuration methodology and the AUTOSAR configuration metamodel in detail.

The following is only a short survey of the topic and it will not replace the ECU Configuration Specification document.

10.1.1 Configuration and configuration parameters

Configuration parameters define the variability of the generic part(s) of an implementation of a module. This means that only generic or configurable module implementation can be adapted to the environment (software/hardware) in use during system and/or ECU configuration.

The configuration of parameters can be achieved at different times during the software process: before compile time, before link time or after build time. In the following, the term “configuration class” (of a parameter) shall be used in order to refer to a specific configuration point in time.

Note that not all attributes may be available in all scalability class.

Memory protection configuration is not standardized and therefore not part of this specification.

10.1.2 Variants

Variants describe sets of configuration parameters. E.g., variant 1: only pre-compile time configuration parameters; variant 2: mix of pre-compile- and post build time-configuration parameters. In one variant a parameter can only be of one configuration class.

火龙果•整理
uml.org.cn

10.1.3 Containers

Containers structure the set of configuration parameters. This means:

- *all* configuration parameters are kept in containers.
- (sub-) containers can reference (sub-) containers. It is possible to assign a multiplicity to these references. The multiplicity then defines the possible number of instances of the contained parameters.

10.1.4 Rules for paramters

Some configuration parameters are configured as floating point values and sometimes these values must be rounded in order to be used. The following rules define the rounding of specific parameters:

- Execution times (for the timing protection) are “round down”
- Timeframes are “round down”

10.2 Containers and configuration parameters

The following chapters summarize all configuration parameters and their containers. The detailed meanings of the parameters describe Chapters 7 and 0.

For better readability OIL names of the 2.1 OS specification are given in curly braces in the namefield of configuration parameters.

10.2.1 Variants

The configuration of the AUTOSAR OS allows only pre-compile (“VARIANT-PRE-COMPILE“) time configuration parameters.

10.2.2 Os

Module Name	*Os*
Module Description	Configuration of the Os (Operating System) module.

Â

Included Containers		
Container Name	***Multiplicity***	***Scope / Dependency***
OsAlarm	0..*	An OsAlarm may be used to asynchronously inform or activate a specific task. It is possible to start alarms automatically at system start-up depending on the application mode.
OsAppMode	1..*	OsAppMode is the object used to define OSEK OS properties for an OSEK OS application mode. No standard attributes are defined for AppMode. In a CPU, at least one AppMode object has to be defined. [source: OSEK OIL Spec. 2.5] An OsAppMode called OSDEFAULTAPPMODE must always be there for OSEK compatilbility.
OsApplication	0..*	An AUTOSAR OS must be capable of supporting a collection of OS objects (tasks, interrupts, alarms, hooks etc.) that form a cohesive functional unit. This collection of objects is termed an OS-Application. All objects which belong to the same OS-Application have access to each other. Access means to allow to use these objects within API services. Access by other applications can be granted separately.

火龙果•整理
uml.org.cn

OsCounter	0..*	Configuration information for the counters that belong to the OsApplication.
OsEvent	0..*	Representation of OS events in the configuration context. Adopted from the OSEK OIL specification.
OsIoc	0..1	Configuration of the IOC (Inter OS Application Communicator).
OsIsr	0..*	The OsIsr container represents an OSEK interrupt service routine.
OsOS	1	OS is the object used to define OSEK OS properties for an OSEK application. Per CPU exactly one OS object has to be defined.
OsResource	0..*	An OsResource object is used to co-ordinate the concurrent access by tasks and ISRs to a shared resource, e.g. the scheduler, any program sequence, memory or any hardware area.
OsScheduleTable	0..*	An OsScheduleTable addresses the synchronization issue by providing an encapsulation of a statically defined set of alarms that cannot be modified at runtime.
OsSpinlock	0..*	An OsSpinlock object is used to co-ordinate concurrent access by TASKs/ISR2s on different cores to a shared resource.
OsTask	0..*	This container represents an OSEK task.

Â

10.2.3 OsAlarmSetEvent

SWS Item	**OS016_Conf :**		
Container Name	OsAlarmSetEvent{SETEVENT}		
Description	This container specifies the parameters to set an event		
Configuration Parameters			

Â

SWS Item	**OS017_Conf :**		
Name	OsAlarmSetEventRef {EVENT}		
Description	Reference to the event that will be set by that alarm action		
Multiplicity	1		
Type	Reference to [OsEvent]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS018_Conf :**		
Name	OsAlarmSetEventTaskRef {TASK}		
Description	Reference to the task that will be activated by that event		
Multiplicity	1		
Type	Reference to [OsTask]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

No Included Containers

Â

10.2.4 OsAlarm

SWS Item	**OS003_Conf :**

火龙果•整理
uml.org.cn

Container Name	OsAlarm{ALARM}
Description	An OsAlarm may be used to asynchronously inform or activate a specific task. It is possible to start alarms automatically at system start-up depending on the application mode.
Configuration Parameters	

Â

SWS Item	**OS004_Conf :**		
Name	OsAlarmAccessingApplication {ACCESSING_APPLICATION}		
Description	Reference to applications which have an access to this object.		
Multiplicity	0..*		
Type	Reference to [OsApplication]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS005_Conf :**		
Name	OsAlarmCounterRef {COUNTER}		
Description	Reference to the assigned counter for that alarm		
Multiplicity	1		
Type	Reference to [OsCounter]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

Included Containers		
Container Name	***Multiplicity***	***Scope / Dependency***
OsAlarmAction	1	This container defines which type of notification is used when the alarm expires.
OsAlarmAutostart	0..1	If present this container defines if an alarm is started automatically at system start-up depending on the application mode.

Â

10.2.5 OsAlarmAction

SWS Item	**OS006_Conf :**
Choice Container Name	OsAlarmAction{ACTION}
Description	This container defines which type of notification is used when the alarm expires.

Â

Container Choices		
Container Name	***Multiplicity***	***Scope / Dependency***
OsAlarmActivateTask	0..1	This container specifies the parameters to activate a task.
OsAlarmCallback	0..1	This container specifies the parameters to call a callback OS alarm action.
OsAlarmIncrementCounter	0..1	This container specifies the parameters to increment a counter.
OsAlarmSetEvent	0..1	This container specifies the parameters to set an event

Â

火龙果•整理
uml.org.cn

10.2.6 OsAlarmActivateTask

SWS Item	**OS007_Conf :**		
Container Name	OsAlarmActivateTask{ACTIVATETASK}		
Description	This container specifies the parameters to activate a task.		
Configuration Parameters			

Â

SWS Item	**OS008_Conf :**		
Name	OsAlarmActivateTaskRef {TASK}		
Description	Reference to the task that will be activated by that alarm action		
Multiplicity	1		
Type	Reference to [OsTask]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

No Included Containers

Â

10.2.7 OsAlarmAutostart

SWS Item	**OS009_Conf :**		
Container Name	OsAlarmAutostart{AUTOSTART}		
Description	If present this container defines if an alarm is started automatically at system start-up depending on the application mode.		
Configuration Parameters			

Â

SWS Item	**OS010_Conf :**		
Name	OsAlarmAlarmTime {ALARMTIME}		
Description	The relative or absolute tick value when the alarm expires for the first time. Note that for an alarm which is RELATIVE the value must be at bigger than 0.		
Multiplicity	1		
Type	EcucIntegerParamDef		
Range	0 .. 18446744073709551615	Â	
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS011_Conf :**		
Name	OsAlarmAutostartType		
Description	This specifies the type of autostart for the alarm..		
Multiplicity	1		
Type	EcucEnumerationParamDef		
Range	ABSOLUTE	The alarm is started on startup via SetAbsAlarm().	
	RELATIVE	The alarm is started on startup via SetAbsAlarm.	
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â

火龙果•整理
uml.org.cn

	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS012_Conf :**		
Name	OsAlarmCycleTime {CYCLETIME}		
Description	Cycle time of a cyclic alarm in ticks. If the value is 0 than the alarm is not cyclic.		
Multiplicity	1		
Type	EcucIntegerParamDef		
Range	0 .. 18446744073709551615	Â	
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS013_Conf :**		
Name	OsAlarmAppModeRef {APPMODE}		
Description	Reference to the application modes for which the AUTOSTART shall be performed		
Multiplicity	1..*		
Type	Reference to [OsAppMode]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

No Included Containers

Â

10.2.8 OsAlarmCallback

SWS Item	**OS014_Conf :**
Container Name	OsAlarmCallback{ALARMCALLBACK}
Description	This container specifies the parameters to call a callback OS alarm action.
Configuration Parameters	

Â

SWS Item	**OS087_Conf :**		
Name	OsAlarmCallbackName {ALARMCALLBACKNAME}		
Description	Name of the function that is called when this alarm callback is triggered.		
Multiplicity	1		
Type	EcucFunctionNameDef		
Default value	--		
maxLength	--		
minLength	--		
regularExpression	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

No Included Containers

Â

火龙果•整理
uml.org.cn

10.2.9 OsAlarmIncrementCounter

SWS Item	**OS302_Conf :**		
Container Name	OsAlarmIncrementCounter{INCREMENTCOUNTER}		
Description	This container specifies the parameters to increment a counter.		
Configuration Parameters			

Â

SWS Item	**OS015_Conf :**		
Name	OsAlarmIncrementCounterRef {COUNTER}		
Description	Reference to the counter that will be incremented by that alarm action		
Multiplicity	1		
Type	Reference to [OsCounter]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU		

Â

No Included Containers

Â

10.2.10 OsApplication

SWS Item	**OS114_Conf :**		
Container Name	OsApplication{APPLICATION}		
Description	An AUTOSAR OS must be capable of supporting a collection of OS objects (tasks, interrupts, alarms, hooks etc.) that form a cohesive functional unit. This collection of objects is termed an OS-Application. All objects which belong to the same OS-Application have access to each other. Access means to allow to use these objects within API services. Access by other applications can be granted separately.		
Configuration Parameters			

Â

SWS Item	**MCOS1020_Conf :**		
Name	OsApplicationCoreAssignment {CORE}		
Description	ID of the core onto which the OsApplication is bound.		
Multiplicity	0..1		
Type	EcucIntegerParamDef		
Range	0 .. 65534	Â	
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: The parameter defines onto which a single OS-Application instance is bound.		

Â

SWS Item	**OS115_Conf :**		
Name	OsTrusted {TRUSTED}		
Description	Parameter to specify if an OS-Application is trusted or not. true: OS-Application is trusted false: OS-Application is not trusted (default)		
Multiplicity	1		
Type	EcucBooleanParamDef		
Default value	false		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â

火龙果•整理
uml.org.cn

Scope / Dependency	scope: ECU dependency: Required for scalability class 3 and 4.

Â

SWS Item	**OS231_Conf :**		
Name	OsAppAlarmRef		
Description	Specifies the OsAlarms that belong to the OsApplication.		
Multiplicity	0..*		
Type	Reference to [OsAlarm]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 3 and 4		

Â

SWS Item	**OS234_Conf :**		
Name	OsAppCounterRef		
Description	References the OsCounters that belong to the OsApplication.		
Multiplicity	0..*		
Type	Reference to [OsCounter]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 3 and 4.		

Â

SWS Item	**OS221_Conf :**		
Name	OsAppIsrRef		
Description	references which OsIsrs belong to the OsApplication		
Multiplicity	0..*		
Type	Reference to [OsIsr]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 3 and 4.		

Â

SWS Item	**OS248_Conf :**		
Name	OsAppResourceRef		
Description	References the OsResources that belong to the OsApplication.		
Multiplicity	0..*		
Type	Reference to [OsResource]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 3 and 4.		

Â

SWS Item	**OS230_Conf :**		
Name	OsAppScheduleTableRef		
Description	References the OsScheduleTables that belong to the OsApplication.		
Multiplicity	0..*		
Type	Reference to [OsScheduleTable]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â

火龙果•整理
uml.org.cn

Scope / Dependency	scope: ECU dependency: Required for scalability class 3 and 4.

Â

SWS Item	**OS116_Conf :**		
Name	OsAppTaskRef		
Description	references which OsTasks belong to the OsApplication		
Multiplicity	0..*		
Type	Reference to [OsTask]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 3 and 4		

Â

SWS Item	**OS120_Conf :**		
Name	OsRestartTask {RESTARTTASK}		
Description	Optionally one task of an OS-Application may be defined as Restart Task. Multiplicity = 1: Restart Task is activated by the Operating System if the protection hook requests it. Multiplicity = 0: No task is automatically started after a protection error happened.		
Multiplicity	0..1		
Type	Reference to [OsTask]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 3 and 4.		

Â

Included Containers		
Container Name	***Multiplicity***	***Scope / Dependency***
OsApplicationHooks	1	Container to structure the OS-Application-specific hooks
OsApplicationTrustedFunction	0..*	Container to structure the configration parameters of trusted functions

Â

10.2.11 OsApplicationHooks

SWS Item	**OS020_Conf :**
Container Name	OsApplicationHooks
Description	Container to structure the OS-Application-specific hooks
Configuration Parameters	

Â

SWS Item	**OS213_Conf :**		
Name	OsAppErrorHook {ERRORHOOK}		
Description	Select the OS-Application error hook. true: Hook is called false: Hook is not called		
Multiplicity	1		
Type	EcucBooleanParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 3 and 4.		

Â

SWS Item	**OS125_Conf :**

火龙果•整理
uml.org.cn

Name	OsAppShutdownHook {SHUTDOWNHOOK}		
Description	Select the OS-Application specific shutdown hook for the OS-Application. true: Hook is called false: Hook is not called		
Multiplicity	1		
Type	EcucBooleanParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 3 and 4.		

Â

SWS Item	**OS124_Conf :**		
Name	OsAppStartupHook {STARTUPHOOK}		
Description	Select the OS-Application specific startup hook for the OS-Application. true: Hook is called false: Hook is not called		
Multiplicity	1		
Type	EcucBooleanParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 3 and 4.		

Â

No Included Containers

Â

10.2.12 OsApplicationTrustedFunction

SWS Item	**OS021_Conf :**
Container Name	OsApplicationTrustedFunction
Description	Container to structure the configration parameters of trusted functions
Configuration Parameters	

Â

SWS Item	**OS254_Conf :**		
Name	OsTrustedFunctionName		
Description	Trusted function (as part of a trusted OS-Application) available to other OS-Applications. This also supersedes the OSEK OIL attribute TRUSTED in APPLICATION because the optionality of this parameter is describing that already.		
Multiplicity	1		
Type	EcucFunctionNameDef		
Default value	--		
maxLength	--		
minLength	--		
regularExpression	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 3 and 4 and in trusted OS-Applications.		

Â

No Included Containers

Â

火龙果•整理
uml.org.cn

10.2.13 OsAppMode

SWS Item	**OS022_Conf :**
Container Name	OsAppMode{APPMODE}
Description	OsAppMode is the object used to define OSEK OS properties for an OSEK OS application mode. No standard attributes are defined for AppMode. In a CPU, at least one AppMode object has to be defined. [source: OSEK OIL Spec. 2.5] An OsAppMode called OSDEFAULTAPPMODE must always be there for OSEK compatilbility.
Configuration Parameters	

Â

No Included Containers

Â

10.2.14 OsCounter

SWS Item	**OS026_Conf :**
Container Name	OsCounter{COUNTER}
Description	Configuration information for the counters that belong to the OsApplication.
Configuration Parameters	

Â

SWS Item	**OS027_Conf :**		
Name	OsCounterMaxAllowedValue {MAXALLOWEDVALUE}		
Description	Maximum possible allowed value of the system counter in ticks.		
Multiplicity	1		
Type	EcucIntegerParamDef		
Range	1 .. 18446744073709551615	Â	
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS028_Conf :**		
Name	OsCounterMinCycle {MINCYCLE}		
Description	The MINCYCLE attribute specifies the minimum allowed number of counter ticks for a cyclic alarm linked to the counter.		
Multiplicity	1		
Type	EcucIntegerParamDef		
Range	1 .. 18446744073709551615	Â	
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item **OS029_Conf :**
Name OsCounterTicksPerBase {TICKSPERBASE}
Description The TICKSPERBASE attribute specifies the number of ticks required to reach a counterspecific unit. The interpretation is implementation-specific.
Multiplicity 1
Type EcucIntegerParamDef

火龙果•整理
uml.org.cn

Range	1 .. 18446744073709551615	Â	
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS255_Conf :**		
Name	OsCounterType {TYPE}		
Description	This parameter contains the natural type or unit of the counter.		
Multiplicity	1		
Type	EcucEnumerationParamDef		
Range	HARDWARE	This counter is driven by some hardware e.g. a hardware timer unit.	
	SOFTWARE	The counter is driven by some software which calls the IncrementCounter service.	
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU		

Â

SWS Item	**OS030_Conf :**		
Name	OsSecondsPerTick		
Description	Time of one hardware tick in seconds.		
Multiplicity	0..1		
Type	EcucFloatParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU		

Â

SWS Item	**OS031_Conf :**		
Name	OsCounterAccessingApplication {ACCESSING_APPLICATION}		
Description	Reference to applications which have an access to this object.		
Multiplicity	0..*		
Type	Reference to [OsApplication]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

Included Containers		
Container Name	***Multiplicity***	***Scope / Dependency***
OsDriver	0..1	This Container contains the information who will drive the counter. This configuration is only valid if the counter has OsCounterType set to HARDWARE. If the container does not exist (multiplicity=0) the timer is managed by the OS internally (OSINTERNAL). If the container exists the OS can use the GPT interface to manage the timer. The user have to supply the GPT channel. If the counter is driven by some other (external to the OS) source (like a TPU for example) this must be described as a vendor specific extension.

火龙果•整理
uml.org.cn

OsTimeConstant	0..*	Allows the user to define constants which can be e.g. used to compare time values with timer tick values. A time value will be converted to a timer tick value during generation and can later on accessed via the OsConstName. The conversation is done by rounding time values to the nearest fitting tick value.

Â

10.2.15 OsEvent

SWS Item	**OS033_Conf :**		
Container Name	OsEvent{EVENT}		
Description	Representation of OS events in the configuration context. Adopted from the OSEK OIL specification.		
Configuration Parameters			

Â

SWS Item	**OS034_Conf :**		
Name	OsEventMask {MASK}		
Description	If event mask would be set to AUTO in OIL, this parameter should be omitted here.		
Multiplicity	0..1		
Type	EcucIntegerParamDef		
Range	0 .. 18446744073709551615	Â	
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

No Included Containers

Â

10.2.16 OsHooks

SWS Item	**OS035_Conf :**		
Container Name	OsHooks		
Description	Container to structure all hooks belonging to the OS		
Configuration Parameters			

Â

SWS Item	**OS036_Conf :**		
Name	OsErrorHook {ERRORHOOK}		
Description	Error hook as defined by OSEK true: Hook is called false: Hook is not called		
Multiplicity	1		
Type	EcucBooleanParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS037_Conf :**
Name	OsPostTaskHook {POSTTASKHOOK}
Description	Post-task hook as defined by OSEK true: Hook is called false: Hook is not called
Multiplicity	1

火龙果•整理
uml.org.cn

Type	EcucBooleanParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS038_Conf :**		
Name	OsPreTaskHook {PRETASKHOOK}		
Description	Pre-task hook as defined by OSEK true: Hook is called false: Hook is not called		
Multiplicity	1		
Type	EcucBooleanParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS214_Conf :**		
Name	OsProtectionHook {PROTECTIONHOOK}		
Description	Switch to enable/disable the call to the (user supplied) protection hook. true: Protection hook is called on protection error false: Protection hook is not called		
Multiplicity	0..1		
Type	EcucBooleanParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 2,3 and 4		

Â

SWS Item	**OS039_Conf :**		
Name	OsShutdownHook {SHUTDOWNHOOK}		
Description	Shutdown hook as defined by OSEK true: Hook is called false: Hook is not called		
Multiplicity	1		
Type	EcucBooleanParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS040_Conf :**		
Name	OsStartupHook {STARTUPHOOK}		
Description	Startup hook as defined by OSEK true: Hook is called false: Hook is not called		
Multiplicity	1		
Type	EcucBooleanParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â

火龙果•整理
uml.org.cn

	Post-build time	--	Â
Scope / Dependency			

Â

No Included Containers

Â

10.2.17 OsIsr

SWS Item	**OS041_Conf :**		
Container Name	OsIsr{ISR}		
Description	The OsIsr container represents an OSEK interrupt service routine.		
Configuration Parameters			

Â

SWS Item	**OS042_Conf :**		
Name	OsIsrCategory {CATEGORY}		
Description	This attribute specifies the category of this ISR.		
Multiplicity	1		
Type	EcucEnumerationParamDef		
Range	CATEGORY_1	Interrupt is of category 1	
	CATEGORY_2	Interrupt is of category 2	
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS043_Conf :**		
Name	OsIsrResourceRef {RESOURCE}		
Description	This reference defines the resources accessed by this ISR.		
Multiplicity	0..*		
Type	Reference to [OsResource]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

Included Containers		
Container Name	***Multiplicity***	***Scope / Dependency***
OsIsrTimingProtection	0..1	This container contains all parameters which are related to timing protection If the container exists, the timing protection is used for this interrupt. If the container does not exist, the interrupt is not supervised regarding timing violations.

Â

10.2.18 OsIsrResourceLock

SWS Item	**OS388_Conf :**
Container Name	OsIsrResourceLock{LOCKINGTIME}
Description	This parameter contains a list of times the interrupt uses resources.
Configuration Parameters	

Â

SWS Item	**OS389_Conf :**
Name	OsIsrResourceLockBudget {MAXRESOURCELOCKTIME}
Description	This parameter contains the maximum time the interrupt is allowed to hold the given resource (in seconds).

火龙果•整理
uml.org.cn

Multiplicity	1		
Type	EcucFloatParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 2 and 4		

Â

SWS Item	**OS390_Conf :**		
Name	OsIsrResourceLockResourceRef {RESOURCE}		
Description	Reference to the resource the locking time is depending on		
Multiplicity	1		
Type	Reference to [OsResource]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 2 and 4		

Â

No Included Containers

Â

10.2.19 OsIsrTimingProtection

SWS Item	**OS326_Conf :**
Container Name	OsIsrTimingProtection{TIMING_PROTECTION}
Description	This container contains all parameters which are related to timing protection If the container exists, the timing protection is used for this interrupt. If the container does not exist, the interrupt is not supervised regarding timing violations.
Configuration Parameters	

Â

SWS Item	**OS229_Conf :**		
Name	OsIsrAllInterruptLockBudget {MAXALLINTERRUPTLOCKTIME}		
Description	This parameter contains the maximum time for which the ISR is allowed to lock all interrupts (via SuspendAllInterrupts() or DisableAllInterrupts()) (in seconds).		
Multiplicity	0..1		
Type	EcucFloatParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 2 and 4		

Â

SWS Item	**OS222_Conf :**		
Name	OsIsrExecutionBudget {EXECUTIONTIME}		
Description	The parameter contains the maximum allowed execution time of the interrupt (in seconds).		
Multiplicity	0..1		
Type	EcucFloatParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants

火龙果•整理
uml.org.cn

	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 2 and 4		

Â

SWS Item	**OS387_Conf :**		
Name	OsIsrOsInterruptLockBudget {MAXOSINTERRUPTLOCKTIME}		
Description	This parameter contains the maximum time for which the ISR is allowed to lock all Category 2 interrupts (via SuspendOSInterrupts()) (in seconds).		
Multiplicity	0..1		
Type	EcucFloatParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 2 and 4		

Â

SWS Item	**OS223_Conf :**		
Name	OsIsrTimeFrame {TIMEFRAME}		
Description	This parameter contains the minimum inter-arrival time between successive interrupts (in seconds).		
Multiplicity	0..1		
Type	EcucFloatParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 2 and 4		

Â

Included Containers		
Container Name	***Multiplicity***	***Scope / Dependency***
OsIsrResourceLock	0..*	This parameter contains a list of times the interrupt uses resources.

Â

10.2.20 OsOS

SWS Item	**OS044_Conf :**
Container Name	OsOS{OS}
Description	OS is the object used to define OSEK OS properties for an OSEK application. Per CPU exactly one OS object has to be defined.
Configuration Parameters	

Â

SWS Item	**MCOS1019_Conf :**		
Name	OsNumberOfCores		
Description	Maximum number of cores that are controlled by the OS. The OS uses the value internally. It depends on the ECU HW.		
Multiplicity	0..1		
Type	EcucIntegerParamDef		
Range	1 .. 65535	Â	
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â

火龙果•整理
uml.org.cn

Scope / Dependency	

Â

SWS Item	**OS259_Conf :**		
Name	OsScalabilityClass {SCALABILITYCLASS}		
Description	A scalability class for each System Object "OS" has to be selected. In order to customize the operating system to the needs of the user and to take full advantage of the processor features the operating system can be scaled according to the scalability classes. If the scalability class is omitted this translates to the OIL AUTO mechanism.		
Multiplicity	0..1		
Type	EcucEnumerationParamDef		
Range	SC1	--	
	SC2	--	
	SC3	--	
	SC4	--	
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU		

Â

SWS Item	**OS307_Conf :**		
Name	OsStackMonitoring {STACKMONITORING}		
Description	Select stack monitoring of Tasks/Category 2 ISRs true: Stacks are monitored false: Stacks are not monitored		
Multiplicity	1		
Type	EcucBooleanParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU		

Â

SWS Item	**OS046_Conf :**		
Name	OsStatus {STATUS}		
Description	The Status attribute specifies whether a system with standard or extended status has to be used. Automatic assigment is not supported for this attribute.		
Multiplicity	1		
Type	EcucEnumerationParamDef		
Range	EXTENDED	--	
	STANDARD	--	
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS047_Conf :**		
Name	OsUseGetServiceId {USEGETSERVICEID}		
Description	As defined by OSEK		
Multiplicity	1		
Type	EcucBooleanParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â

火龙果•整理
uml.org.cn

Scope / Dependency	

Â

SWS Item	**OS048_Conf :**		
Name	OsUseParameterAccess {USEPARAMETERACCESS}		
Description	As defined by OSEK		
Multiplicity	1		
Type	EcucBooleanParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS049_Conf :**		
Name	OsUseResScheduler {USERESSCHEDULER}		
Description	The OsUseResScheduler attribute defines whether the resource RES_SCHEDULER is used within the application.		
Multiplicity	1		
Type	EcucBooleanParamDef		
Default value	true		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

Included Containers		
Container Name	***Multiplicity***	***Scope / Dependency***
OsHooks	1	Container to structure all hooks belonging to the OS

Â

10.2.21 OsResource

SWS Item	**OS252_Conf :**
Container Name	OsResource{RESOURCE}
Description	An OsResource object is used to co-ordinate the concurrent access by tasks and ISRs to a shared resource, e.g. the scheduler, any program sequence, memory or any hardware area.
Configuration Parameters	

Â

SWS Item	**OS050_Conf :**		
Name	OsResourceProperty {RESOURCEPROPERTY}		
Description	This specifies the type of the resource.		
Multiplicity	1		
Type	EcucEnumerationParamDef		
Range	INTERNAL	The resource is an internal resource.	
	LINKED	The resource is a linked resource (a second name for a existing resource).	
	STANDARD	The resource is a standard resource.	
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS051_Conf :**
Name	OsResourceAccessingApplication {ACCESSING_APPLICATION}

火龙果•整理
uml.org.cn

Description	Reference to applications which have an access to this object.		
Multiplicity	0..*		
Type	Reference to [OsApplication]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS052_Conf :**		
Name	OsResourceLinkedResourceRef {LINKEDRESOURCE}		
Description	The link to the resource. Must be valid if OsResourceProperty is LINKED. If OsResourceProperty is not LINKED the value is ignored.		
Multiplicity	0..1		
Type	Reference to [OsResource]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

No Included Containers

Â

10.2.22 OsScheduleTable

SWS Item	**OS141_Conf :**		
Container Name	OsScheduleTable{SCHEDULETABLE}		
Description	An OsScheduleTable addresses the synchronization issue by providing an encapsulation of a statically defined set of alarms that cannot be modified at runtime.		
Configuration Parameters			

Â

SWS Item	**OS053_Conf :**		
Name	OsScheduleTableDuration		
Description	This parameter defines the modulus of the schedule table (in ticks).		
Multiplicity	1		
Type	EcucIntegerParamDef		
Range	0 .. 18446744073709551615	Â	
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS144_Conf :**		
Name	OsScheduleTableRepeating {REPEATING}		
Description	true: first expiry point on the schedule table shall be processed at final expiry point delay ticks after the final expiry point is processed. false: the schedule table processing stops when the final expiry point is processed.		
Multiplicity	1		
Type	EcucBooleanParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â

火龙果•整理
uml.org.cn

	Post-build time	--	Â
Scope / Dependency	scope: ECU		

Â

SWS Item	**OS054_Conf :**		
Name	OsSchTblAccessingApplication {ACCESSING_APPLICATION}		
Description	Reference to applications which have an access to this object.		
Multiplicity	0..*		
Type	Reference to [OsApplication]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS145_Conf :**		
Name	OsScheduleTableCounterRef {COUNTER}		
Description	This parameter contains a reference to the counter which drives the schedule table.		
Multiplicity	1		
Type	Reference to [OsCounter]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU		

Â

Included Containers		
Container Name	***Multiplicity***	***Scope / Dependency***
OsScheduleTableAutostart	0..1	This parameter specifies if and how the schedule table is started on startup of the Operating System. The options to start a schedule table correspond to the API calls to start schedule tables during runtime.
OsScheduleTableExpiryPoint	1..*	The point on a Schedule Table at which the OS activates tasks and/or sets events
OsScheduleTableSync	0..1	This parameter specifies the synchronization parameters of the schedule table.

Â

10.2.23 OsScheduleTableAutostart

SWS Item	**OS335_Conf :**
Container Name	OsScheduleTableAutostart{AUTOSTART}
Description	This parameter specifies if and how the schedule table is started on startup of the Operating System. The options to start a schedule table correspond to the API calls to start schedule tables during runtime.
Configuration Parameters	

Â

SWS Item	**OS056_Conf :**	
Name	OsScheduleTableAutostartType	
Description	This specifies the type of the autostart for the schedule table.	
Multiplicity	1	
Type	EcucEnumerationParamDef	
Range	ABSOLUTE	The schedule table is started during startup with the StartScheduleTableAbs() service.
	RELATIVE	The schedule table is started during startup with the StartScheduleTableRel() service.
	SYNCHRON	The schedule table is started during startup with the StartScheduleTableSynchron()

火龙果•整理
uml.org.cn

		service.	
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS057_Conf :**		
Name	OsScheduleTableStartValue		
Description	Absolute autostart tick value when the schedule table starts. Only used if the OsScheduleTableAutostartType is ABSOLUTE. Relative offset in ticks when the schedule table starts. Only used if the OsScheduleTableAutostartType is RELATIVE.		
Multiplicity	0..1		
Type	EcucIntegerParamDef		
Range	0 .. 18446744073709551615	Â	
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU		

Â

SWS Item	**OS058_Conf :**		
Name	OsScheduleTableAppModeRef		
Description	Reference in which application modes the schedule table should be started during startup		
Multiplicity	1..*		
Type	Reference to [OsAppMode]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU		

Â

No Included Containers

Â

10.2.24 OsScheduleTableEventSetting

SWS Item	**OS059_Conf :**
Container Name	OsScheduleTableEventSetting{SETEVENT}
Description	Event that is triggered by that schedule table.
Configuration Parameters	

Â

SWS Item	**OS060_Conf :**		
Name	OsScheduleTableSetEventRef {EVENT}		
Description	Reference to event that will be set by action		
Multiplicity	1		
Type	Reference to [OsEvent]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS061_Conf :**

火龙果•整理
uml.org.cn

Name	OsScheduleTableSetEventTaskRef		
Description	--		
Multiplicity	1		
Type	Reference to [OsTask]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

No Included Containers

Â

10.2.25 OsScheduleTableExpiryPoint

SWS Item	**OS143_Conf :**		
Container Name	OsScheduleTableExpiryPoint{ACTION}		
Description	The point on a Schedule Table at which the OS activates tasks and/or sets events		
Configuration Parameters			

Â

SWS Item	**OS062_Conf :**		
Name	OsScheduleTblExpPointOffset		
Description	The offset from zero (in ticks) at which the expiry point is to be processed.		
Multiplicity	1		
Type	EcucIntegerParamDef		
Range	0 .. 18446744073709551615	Â	
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

Included Containers		
Container Name	***Multiplicity***	***Scope / Dependency***
OsScheduleTableEventSetting	0..*	Event that is triggered by that schedule table.
OsScheduleTableTaskActivation	0..*	Task that is triggered by that schedule table.
OsScheduleTblAdjustableExpPoint	0..1	Adjustable expiry point

Â

10.2.26 OsScheduleTableTaskActivation

SWS Item	**OS066_Conf :**		
Container Name	OsScheduleTableTaskActivation{ACTIVATETASK}		
Description	Task that is triggered by that schedule table.		
Configuration Parameters			

Â

SWS Item	**OS067_Conf :**		
Name	OsScheduleTableActivateTaskRef {TASK}		
Description	Reference to task that will be activated by action		
Multiplicity	1		
Type	Reference to [OsTask]		
ConfigurationClass	***Pre-compile time***	X	All Variants

火龙果•整理
uml.org.cn

	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU		

Â

No Included Containers

Â

10.2.27 OsScheduleTblAdjustableExpPoint

SWS Item	**OS068_Conf :**		
Container Name	OsScheduleTblAdjustableExpPoint		
Description	Adjustable expiry point		
Configuration Parameters			

Â

SWS Item	**OS069_Conf :**		
Name	OsScheduleTableMaxAdvance		
Description	The maximum positive adjustment that can be made to the expiry point offset (in ticks).		
Multiplicity	1		
Type	EcucIntegerParamDef		
Range	0 .. 18446744073709551615	Â	
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS070_Conf :**		
Name	OsScheduleTableMaxRetard		
Description	The maximum negative adjustment that can be made to the expiry point offset (in ticks).		
Multiplicity	1		
Type	EcucIntegerParamDef		
Range	0 .. 18446744073709551615	Â	
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

No Included Containers

Â

10.2.28 OsScheduleTableSync

SWS Item	**OS063_Conf :**
Container Name	OsScheduleTableSync{LOCAL_TO_GLOBAL_TIME_SYNCHRONIZATION}
Description	This parameter specifies the synchronization parameters of the schedule table.
Configuration Parameters	

Â

SWS Item	**OS064_Conf :**

火龙果•整理
uml.org.cn

Name	OsScheduleTblExplicitPrecision		
Description	This configuration is only valid if the explicit synchronisation is used.		
Multiplicity	0..1		
Type	EcucIntegerParamDef		
Range	0 .. 18446744073709551615	Â	
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: System		

Â

SWS Item	**OS065_Conf :**		
Name	OsScheduleTblSyncStrategy		
Description	AUTOSAR OS provides support for synchronisation in two ways: explicit and implicit.		
Multiplicity	1		
Type	EcucEnumerationParamDef		
Range	EXPLICIT	The schedule table is driven by an OS counter but processing needs to be synchronized with a different counter which is not an OS counter object.	
	IMPLICIT	The counter driving the schedule table is the counter with which synchronisation is required.	
	NONE	No support for synchronisation. (default)	
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: System		

Â

No Included Containers

Â

10.2.29 OsTask

SWS Item	**OS073_Conf :**		
Container Name	OsTask{TASK}		
Description	This container represents an OSEK task.		
Configuration Parameters			

Â

SWS Item	**OS074_Conf :**		
Name	OsTaskActivation {ACTIVATION}		
Description	This attribute defines the maximum number of queued activation requests for the task. A value equal to "1" means that at any time only a single activation is permitted for this task. Note that the value must be a natural number starting at 1.		
Multiplicity	1		
Type	EcucIntegerParamDef		
Range	1 .. 18446744073709551615	Â	
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â

火龙果•整理
uml.org.cn

	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS075_Conf :**		
Name	OsTaskPriority {PRIORITY}		
Description	The priority of a task is defined by the value of this attribute. This value has to be understood as a relative value, i.e. the values show only the relative ordering of the tasks. OSEK OS defines the lowest priority as zero (0); larger values correspond to higher priorities.		
Multiplicity	1		
Type	EcucIntegerParamDef		
Range	0 .. 18446744073709551615	Â	
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS076_Conf :**		
Name	OsTaskSchedule {SCHEDULE}		
Description	The OsTaskSchedule attribute defines the preemptability of the task. If this attribute is set to NON, no internal resources may be assigned to this task.		
Multiplicity	1		
Type	EcucEnumerationParamDef		
Range	FULL	Task is preemptable.	
	NON	Task is not preemptable.	
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS077_Conf :**		
Name	OsTaskAccessingApplication {ACCESSING_APPLICATION}		
Description	Reference to applications which have an access to this object.		
Multiplicity	0..*		
Type	Reference to [OsApplication]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS078_Conf :**		
Name	OsTaskEventRef {EVENT}		
Description	This reference defines the list of events the extended task may react on.		
Multiplicity	0..*		
Type	Reference to [OsEvent]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

SWS Item	**OS079_Conf :**
Name	OsTaskResourceRef {RESOURCE}

火龙果•整理
uml.org.cn

Description	This reference defines a list of resources accessed by this task.		
Multiplicity	0..*		
Type	Reference to [OsResource]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

Included Containers		
Container Name	***Multiplicity***	***Scope / Dependency***
OsTaskAutostart	0..1	This container determines whether the task is activated during the system start-up procedure or not for some specific application modes. If the task shall be activated during the system start-up, this container is present and holds the references to the application modes in which the task is auto-started.
OsTaskTimingProtection	0..1	This parameter contains all parameters regarding timing protection of the task.

Â

10.2.30 OsTaskAutostart

SWS Item	**OS080_Conf :**
Container Name	OsTaskAutostart{AUTOSTART}
Description	This container determines whether the task is activated during the system start-up procedure or not for some specific application modes. If the task shall be activated during the system start-up, this container is present and holds the references to the application modes in which the task is auto-started.
Configuration Parameters	

Â

SWS Item	**OS081_Conf :**		
Name	OsTaskAppModeRef {APPMODE}		
Description	Reference to application modes in which that task is activated on startup of the OS		
Multiplicity	1..*		
Type	Reference to [OsAppMode]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency			

Â

No Included Containers

Â

10.2.31 OsTaskResourceLock

SWS Item	**OS082_Conf :**
Container Name	OsTaskResourceLock{RESOURCELOCK}
Description	This parameter contains the worst case time between getting and releasing a given resource (in seconds).
Configuration Parameters	

Â

SWS Item	**OS083_Conf :**
Name	OsTaskResourceLockBudget {RESOURCELOCKTIME}

火龙果•整理
uml.org.cn

Description	This parameter contains the maximum time the task is allowed to lock the resource (in seconds)		
Multiplicity	1		
Type	EcucFloatParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 2 and 4		

Â

SWS Item	**OS084_Conf :**		
Name	OsTaskResourceLockResourceRef {RESOURCE}		
Description	Reference to the resource used by the task		
Multiplicity	1		
Type	Reference to [OsResource]		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 2 and 4		

Â

No Included Containers

Â

10.2.32 OsTaskTimingProtection

SWS Item	**OS325_Conf :**
Container Name	OsTaskTimingProtection{TIMING_PROTECTION}
Description	This parameter contains all parameters regarding timing protection of the task.
Configuration Parameters	

Â

SWS Item	**OS085_Conf :**		
Name	OsTaskAllInterruptLockBudget {MAXALLINTERRUPTLOCKTIME}		
Description	This parameter contains the maximum time for which the task is allowed to lock all interrupts (via SuspendAllInterrupts() or DisableAllInterrupts()) (in seconds).		
Multiplicity	0..1		
Type	EcucFloatParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 2 and 4		

Â

SWS Item	**OS185_Conf :**		
Name	OsTaskExecutionBudget {EXECUTIONBUDGET}		
Description	This parameter contains the maximum allowed execution time of the task (in seconds).		
Multiplicity	0..1		
Type	EcucFloatParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants

火龙果•整理
uml.org.cn

	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 2 and 4		

Â

SWS Item	**OS086_Conf :**		
Name	OsTaskOsInterruptLockBudget {MAXOSINTERRUPTLOCKTIME}		
Description	This parameter contains the maximum time for which the task is allowed to lock all Category 2 interrupts (via SuspendOSInterrupts()) (in seconds).		
Multiplicity	0..1		
Type	EcucFloatParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Required for scalability class 2 and 4		

Â

SWS Item	**OS391_Conf :**		
Name	OsTaskTimeFrame {TIMEFRAME}		
Description	The minimum inter-arrival time between activations and/or releases of a task (in seconds).		
Multiplicity	0..1		
Type	EcucFloatParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants
	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU dependency: Only available in scalability class 2 and 4		

Â

Included Containers		
Container Name	***Multiplicity***	***Scope / Dependency***
OsTaskResourceLock	0..*	This parameter contains the worst case time between getting and releasing a given resource (in seconds).

Â

10.2.33 OsTimeConstant

SWS Item	**OS386_Conf :**		
Container Name	OsTimeConstant{TIMECONSTANTS}		
Description	Allows the user to define constants which can be e.g. used to compare time values with timer tick values. A time value will be converted to a timer tick value during generation and can later on accessed via the OsConstName. The conversation is done by rounding time values to the nearest fitting tick value.		
Configuration Parameters			

Â

SWS Item	**OS002_Conf :**		
Name	OsTimeValue		
Description	This parameter contains the value of the constant in seconds.		
Multiplicity	1		
Type	EcucFloatParamDef		
Default value	--		
ConfigurationClass	***Pre-compile time***	X	All Variants

火龙果•整理
uml.org.cn

	Link time	--	Â
	Post-build time	--	Â
Scope / Dependency	scope: ECU		

Â

No Included Containers

Â

10.3 Published Information

[OS001_PI] The standardized common published parameters as required by BSW00402 in the SRS General on Basic Software Modules [3]shall be published within the header file of this module and need to be provided in the BSW Module Description. The according module abbreviation can be found in the List of Basic Software Modules [13].

Additional module-specific published parameters are listed below if applicable.

火龙果•整理
uml.org.cn

11 Generation of the OS

Figure 11.1: Generation Activities

11.1 Read in configuration

OS172: The generator shall provide the user the ability of reading the information of a selectable configuration file.

11.2 Consistency check

The conistency check can issue warnings or errors. Warnings mean that the generation is completed successfully, only indicating a not advisable configuration. Errors mean that the generation is not performed.

OS173: The generator shall provide the user the ability of performing a consistency check of the current configuration.

OS050: If service protection is required and `OsStatus` is not equal to `EXTENDED` (all the associated error handling is provided), the consistency check shall issue an error.

OS045: If timing protection is configured together with OSEK OS Category 1 interrupts, the consistency check shall issue a warning.

火龙果•整理
uml.org.cn

OS320: If configured attributes do not match the configured scalability class (e.g. defining an execution time budget in Tasks or Category 2 ISRs and selected scalability class is 1) the consistency check shall issue a warning.

OS311: If `OsScalabilityClass` is `SC3` or `SC4` AND a Task OR Category 2 ISR OR Resources OR Counters OR Alarms OR Schedule tables does not belong to exactly one OS-Application the consistency check shall issue an error.

OS361: If `OsScalabilityClass` is `SC3` or `SC4` AND a Category 1 ISR does not belong to exactly one trusted OS-Application the consistency check shall issue an error

OS177: If `OsScalabilityClass` is `SC3` or `SC4` AND an interrupt source that is used by the OS is assigned to an OS-Application, the consistency check shall issue an error.

OS303: If `OsAlarmIncrementCounter` is configured as action on alarm expiry AND the alarm is driven directly or indirectly (a cyclic chain of alarm actions with `OsAlarmIncrementCounter`) by that counter, the consistency check shall issue a warning..

OS328: If `OsStatus` is `STANDARD` and `OsScalabilityClass` is `SC3` or `SC4` the consistency check shall issue an error.

OS343: If `OsScalabilityClass` is `SC3` or `SC4` AND a task is referenced within a schedule table object AND the OS-Application of the schedule table has no access to the task, the consistency check shall issue an error.

OS344: If `OsScalabilityClass` is `SC3` or `SC4` AND a task is referenced within an alarm object AND the OS-Application of the alarm has no access to the task, the consistency check shall issue an error.

OS440: If a schedule table has `OsScheduleTblSyncStrategy = IMPLICIT` and the `OsCounterMaxAllowedValue+1` of the associated counter is not equal to the duration of the schedule table then the consitency check shall issue an error.

OS461: If `OsScalabilityClass` is `SC2, SC3 or SC4 AND` Alarm Callbacks are configured the conistency check shall isuue an error.

11.3 Generating operating system

OS179: If the consistency check of the read-in configuration file has not run free of errors, the generator shall not generate/configure the operating system.

OS336: The generator shall generate a relocatable memory section containing the interrupt vector table.

火龙果•整理
uml.org.cn

OS370: The generator shall print out information about timers used internally by the OS during generation (e.g. on console, list file).

OS393: The generator shall create conversation macros to convert counter ticks (given as argument) into real time. The format of the macro is `OS_TICKS2<Unit>_<Counter>(ticks)` whereas `<Unit>` is one of `NS` (nanoseconds), `US` (microseconds), `MS` (milliseconds) or `SEC` (seconds) and `<Counter>` is the name of the counter; E.g. `OS_TICKS2MS_MyCounter()`)

火龙果•整理
uml.org.cn

12 Application Notes

12.1 Hooks

In OSEK OS, PreTask & PostTask Hooks run at the level of the OS with unrestricted access rights and therefore must be trusted. It is strongly recommended that these hook routines are only used during debugging and are not used in a final product.

When an OS-Application is killed the shutdown and startup hooks of the OS-Application are not called. Cleanup of OS-Application specific data can be done in the restart task.

All application-specific hook functions (startup, shutdown and error) must return (blocking or endless loops are not acceptable).

12.2 Providing Trusted Functions

Address checking shall be done before data is accessed. Special care must be taken if parameters passed by reference point to the stack space of a task or interrupt, because this address space might no longer belong to the task or interrupt when the address is used.

The following code fragment shows an example how a trusted function is called and how the checks should be done.

火龙果•整理
uml.org.cn

```
struct parameter_struct {type1 name1, type2 name2, StatusType
return_value};

/* This service is called by the user and uses a trusted function */

StatusType system_service(
               type1 parameter1,
               type2 parameter2)
{
    /* store parameters in a structure (parameter1 and parameter2) */
    struct  parameter_struct  local_struct;
    local_struct.name1 = parameter1;
    local_struct.name2 = parameter2;

    /* call CallTrustedFunction with appropriate index and
     * pointer to structure */
    if(CallTrustedFunction(SYSTEM_SERVICE_INDEX, &local_struct) !=
       E_OK)
         return(FUNCTION_DOES_NOT_EXIST);
    return(local_struct.return_value);
}

/* The CallTrustedFunction() service switches to the privileged
 * mode. Note that the example is only a fragment! */

StatusType CallTrustedFunction(
                TrustedFunctionIndexType        ix,
                TrustedFunctionParameterRefType ref)
{
    /* check for legal service index and return error if necessary */
    if(ix > MAX_SYSTEM_SERVICE)
        return(E_OS_SERVICEID);

    /* some implementation specific magic happens: the processor is
     * set to privileged mode */
    ….

    /*  indirectly call target function based on the index */
    (*(system-service_list[ix]))(ix, ref);

    /* some implementation specific magic happens: the processor is
     * set to non-privileged mode */
    ….

    return(E_OK);
}
```


火龙果•整理
uml.org.cn

```
/* This part of the system service is called by
 * CallTrustedFunction() */

void TRUSTED_system_service_part2 (TrustedFunctionIndexType a,
parameter_struct *local_struct)
{
    TaskRefType task;
    type1 parameter1;
    type2 parameter2;

    if (GetTaskID(&task) != E_OK)
        task = INVALID_TASK;

    /* get parameters out of the structure (parameter1 and
     * parameter2) */
    parameter1 = local_struct.name1;
    parameter2 = local_struct.name2;

    /* check the parameters if necessary */
    /* example is for parameter1 being an address and parameter2
     * being a size */
    /* example only for system_service called from tasks */
    if(GetISRID()!=INVALID_ISR)
    {
        /* error: not callable from ISR  */
        local_struct.return_value = E_OS_ACCESS;
    }
    else if(OSMEMORY_IS_WRITEABLE(CheckTaskMemoryAccess(
                 task,parameter1,parameter2)))
    {
        /* system_service_part3() is now the function as it
         * would be if directly called in a non-protected
         * environment */
        local_struct.return_value =
              system_service_part3(parameter1,parameter2);
    }
    else
    {
        /* error handling */
        local_struct.return_value = E_OS_ACCESS;
    }
}
```

Note: Since the service of `CallTrustedFunction()` is very generic, it is needed to define a stub-interface which does the packing and unpacking of the arguments (as the example show). Depending on the implementation the stub interface may be (partly) generated by the generation tool.

12.3 Migration hints for OSEKtime OS users

All important OSEKtime OS features are supported in AUTOSAR OS and it should be relatively easy to port applications from OSEKtime OS to AUTOSAR OS.

火龙果•整理
uml.org.cn

However, most OSEKtime OS features are implemented slightly differently and requiring some porting effort. The following steps show how to proceed.

- Dispatcher tables can be implemented by using schedule tables provided by AUTOSAR OS. Synchronization to a global time base can be done in a similar way to OSEKtime by using the `SyncScheduleTable()` API call. A more elegant synchronization solution is also available by driving the schedule table directly from the global time source. However, the AUTOSAR OS implements priority based scheduling rather than the stack based scheduling of OSEKtime. Therefore, priorities have to be chosen for the tasks.
  If a given OSEKtime dispatcher table has to be converted, all tasks can be given the same priority as long as there are no task preemptions. If this cannot be guaranteed, in each case where a task could be pre-empted at a dispatch point, the pre-empting task must be allocated a strictly higher priority than the task it pre-empts. Usually, there are few preemptions in OSEKtime systems, so the priorities are easy to calculate – a simple monotonically increasing priority assignment relative to the tasks position in the schedule table should suffice in most cases. Caveat: In OSEKtime, it is theoretically possible that task A pre-empts task B at one point in the dispatcher table and task B pre-empts task A at another point (however, this is rarely used in practice). Such behaviour is not directly possible in AUTOSAR OS. It can, however, be emulated if required, either by constructing a simple state machine in the task bodies, or by adding two tasks A' and B' using the same code as tasks A and B respectively.
  - Deadline monitoring is not supported by AUTOSAR OS - instead, worst-case execution time enforcement is provided. Schedulability analysis can be used to calculate whether given deadlines are met in a system of periodic tasks with given worst-case execution times.
  - Reenabling of interrupts defined offline is not supported by AUTOSAR OS.
  - Tasks that have precedence over interrupt service routines are not supported by AUTOSAR OS, however, this behaviour can be easily emulated by activating a low-priority task from an ISR.
  - Smooth synchronization is achieved by adjusting the delay between adjacent expiry points, generalising OSEKtime OS' approach, where the synchronization of the local time to the global time is done during several dispatcher rounds by extending or shortening the last ground state of the dispatcher round.

The OSEK time specification allows dispatcher rounds to take 3 modes:

1. Synchronous
2. Asynchronous/Hard
3. Asynchronous/Smooth

Users of OSEKtime who are migrating the AUTOSAR OS can define a schedule table that has the same range/tick resolution as their global time source (with an accompanying AUTOSAR OS counter that has the same resolution as the global time) and can synthesise these modes as follows:

火龙果•整理
uml.org.cn

1. Synchronous: Define `OsScheduleTblSyncStrategy = IMPLICIT` and start using `StartScheduleTableAbs()`. Or define `OsScheduleTblSyncStrategy = EXPLICIT` and start using `StartScheduleTableSynchron()`

2. Asynchronous/Hard: Define `OsScheduleTblSyncStrategy = EXPLICIT` and specify that the final expiry point on the schedule table has a `OsScheduleTableMaxRetard = 1` and a `OsScheduleTableMaxAdvance = OsCounterMaxAllowedValue`. Start using `StartScheduleTableRel()`.

3. Asynchronous/Smooth: Define `OsScheduleTblSyncStrategy = EXPLICIT` and specify that each expiry point on the schedule table has `OsScheduleTableMaxRetard = 1` and a `OsScheduleTableMaxAdvance < OsCounterMaxAllowedValue`. Start using `StartScheduleTableRel()`.

12.4 Software Components and OS-Applications

Trusted OS-Applications can be permitted access to IO space. As software components can not be allowed direct access to the hardware, software components can not be trusted OS-Applications because this would violate this protection feature. The configuration process must ensure that this is the case.

The AUTOSAR Virtual Function Bus (VFB) specification places no restrictions on how runnables from software components are mapped to OS tasks. However, the protection mechanisms in AUTOSAR OS apply only to OS managed objects. This means that all runnables in a task:

- Are not protected from each other at runtime
- Share the same protection boundary

If runnables need to be protected they must therefore be allocated to different tasks and those tasks protected accordingly.

A simple rule can suffice:

> *"When allocating runnables to tasks, only allocate runnables from the same software component into the same task."*

If multiple software components from the same application are to reside on the same processor, then, assuming protection is required between applications (or parts thereof) on the same processor, this rule could be modified to relax the scope of protection to the application:

> *"When allocating runnables to tasks, only allocate runnables from the same application into the same task."*

火龙果•整理
uml.org.cn

If an OS-Application is killed and the restart task is activated it can not assume that the startup of the OS-Application has finished. Maybe the fault happened in the application startup hook and no task of the application was started so far.

12.5 Global Time Synchronization

The OS currently assumes that the global time synchronization is done by the user (unless implicit synchronization is used). This allows maximum flexibility regarding the time source. For synchronization with e.g. FlexRay some glue code may be necessary which transfer the information from the time source to the OS.

12.6 Working with FlexRay

Schedule tables in the AUTOSAR OS may be synchronized with a global (network) time provided by FlexRay in essentially two ways:

1. Using the FlexRay interface's services for controlling timer interrupts related to global time to provide a "hardware" counter tick source to drive the processing of a schedule table (implicit synchronization)
2. Using the FlexRay interface's service for accessing the current global time and passing this into the OS through the SyncScheduleTable() OS service call

This section looks at the second option only.

In FlexRay time is presented as a tuple of a Cycle and a MacrotickOffset within the cycle. Cycle is an 8-bit value and MacrotickOffset is a 16-bit value.
In AUTOSAR OS a schedule table is associated with an underlying counter that has a notion of ticks. It is therefore possible to synchronize with either the Cycle or the tuple of Cycle/MacrotickOffset to give the resolution of synchronization required by the application.
If Cycle only resolution is required then an OS COUNTER object should be configured to have a OsCounterMaxAllowedValue equal to the maximum number of Cycles. If Cycle/MacrotickOffset is required then an OS COUNTER object should be configured with a OsCounterMaxAllowedValue of the maximum number of Cycles multiplied by the MacrotickOffset. This provides the OS with a time base against which a ScheduleTable can be synchronized.

Synchronization between the OS and an external global time source is provided by telling the OS the global time through the SyncScheduleTable() service call. This call takes a scalar parameter of TickType so to interface this to FlexRay's representation of time a small conversion needs to be done. The following example assumes a Cycle of 255 with 65535 Macroticks per Cycle. TickType is at least 24-bits wide.

```
#define OSTIME(x) (TickType)(x);
FrIf_GetGlobalTime(Controller, &Cycle, &Macrotick);
SyncScheduleTable(Tbl, ((OSTIME(Cycle) << 16)+(OSTIME(Macrotick))));
```


火龙果•整理
uml.org.cn

Telling the ScheduleTable that GlobalTime can be done when the application detects that the FlexRay controller has lost synchronization with the network (by polling the controller sync status). The following code indicates how this can be used to force an associated ScheduleTable into the `SCHEDULETABLE_RUNNING` state from the `SCHEDULETABLE_RUNNING_AND_SYNCHRONOUS` state.

```
Fr_SyncStateType CurrentSyncStatus;
if (FrIf_GetSyncState(Controller, &CurrentSyncStatus) == E_OK) {
  if (CurrentSyncStatus == FR_ASYNC ) {
    SetScheduleTableAsync(Table);
  }
}
```

Of course, other actions are possible here, like stopping the ScheduleTable, as best fits user requirements.

12.7 Migration from OIL to XML

This version of the AUTOSAR OS specification does not directly support the configuration via OIL. The support for OIL was dropped in favour of XML because XML is the standard configuration language in AUTOSAR and is essential if configuration data has to be imported / exported from / to other AUTOSAR modules or between different tools during development.

Since OIL and XML are both ASCII formats a tool vendor may offer a possibility to import (old) OIL files and to store them as (AUTOSAR OS) XML files. Currently all known vendors support at least the import of existing OIL configurations.

Note that for showing conformance to the OSEK OS specification, each OSEK OS vendor must support OIL. This means that practically each AUTOSAR OS vendor will offer some sort of import of OIL configurations – at least to show the OSEK OS conformance.

12.8 Migrating RES_SCHEDULER in AUTOSAR OS

As stated in 7.1.2.1 AUTOSAR OS treats `RES_SCHEDULER` as a normal resource. If you have legacy code which is migrated to AUTOSAR OS please take care of the following aspects:

- In OSEK OS there is no need to configure the `RES_SCHEDULER` in the OIL file. If you migrate to AUTOSAR OS the configuration is done in XML and each resource must be properly configured. The easiest way to do this is to configure a resource `RES_SCHEDULER` in XML (OsResource) and allow any Task in your system to use this resource[3].
- Avoid that ISRs are using the `RES_SCHEDULER`. In OSEK OS this is also not possible.

[3] This work can be done automatically by a configuration tool duirng importing an OIL file

火龙果•整理
uml.org.cn

- Make the `RES_SCHEDULER` a `STANDARD` resource (at least not an `INTERNAL` resource). The symbol `RES_SCHEDULER` must be present which is not the case if the resource is an `INTERNAL` resource.
- If you are using OS-Applications, the `RES_SCHEDULER` should belong to a trusted OS-Application. Tasks of other OS-Applications should be configured to have the right to access the resource.

12.9 Debug support

For the AUTOSAR OS the following information may be useful for users and should be considert for debug support (and may be published, e.g. in the BSWMD):

- General information about how to retrieve the current (active) Task or ISR and their (current) priority and (current) stack.
- For ISRs: Information about the name of interrupts, their mapping to the ISR identifier, the associated hardware and the used stack(s).
- For Tasks: Information about the name of the Task, its identifier, the task state, the possible priorities, the event mask (if its an extended task), the OS-Application to whom the Task belongs (if existant) and the used stack.
- For Resources: Information about the name of the Resource, its mapping to the identifier, its priority and the current owner (the Task/ISR which currently holds the Resource)
- For Alarms: Information about the name of the Alarm, its mapping to the identifier, the counter to whom it belong, the action which is executed on expiry and the current state (running or stopped). In running state the next expiry in ticks and the possible cycle time shall be also published.
- For Counters: Information about the name of the Counter, its mapping to the identifier, its associated alarms and the current counter value.
- For Schdule Tables: Information about the name of the Schedule Table, its mapping to the identifier, its current state and the next expiry point (if the table is running).
- For OS-Applications: Information about the name of the OS-Application, its mapping to the identifier, its current state and the memory sections assigned to it (if memory protection is used).

User documentation should contain information about the implemeted debug features.

火龙果•整理
uml.org.cn

13 AUTOSAR Service implemented by the OS

13.1 Scope of this Chapter

This chapter is an addition to the specification of the Operating System. Whereas the other parts of the specification define the behavior and the C-interfaces of the OS module, this chapter formally specifies the corresponding AUTOSAR Service in terms of the SWC Template. The interfaces described here will be visible on the VFB and are used by the RTE generator to create the glue code between the application software (SWC) and the OS.

13.1.1 Package

The following definitions are interpreted to be in
`ARPackage AUTOSAR/Services/Os`

13.2 Overview

The AUTOSAR Operating System is normally not used directly by SWCs. Even the other BSW modules which are below the RTE are using the BSW Scheduler to have access to OS services. The BSW Scheduler of course uses the OS to implement its features, e.g. critical sections.

Nevertheless there are some cases, where it makes sense to allow SWCs access to services of the OS:

- Timer services
  Since the number of timers in an ECU is limited it make sense to share these units across several SWCs. The functionality of the timer services of the OS which are offered to the SWCs are:
  - A service to get the current value of a – hardware or software – counter
  - A service which calculates the time difference between the current timer value and a given (previouls read) timer value

- Application modes
  An application mode is always used to start the OS. To get the current application mode the corresponding OS service is avalible to SWCs.

- OS-Application handling
  To enable SWCs to start and stop OS-Applications the following services are available:
  - A service to terminate and optionally restart an OS-Application
  - A service to get the current state of the OS-Application

火龙果•整理
uml.org.cn

13.3 Specification of the Ports and Port Interfaces

This chapter specifies the ports and port interfaces which are needed in order to operate the timer services of the OS over the VFB. Note that there are ports on both sides of the RTE: The SW-C description of the OS service will define the ports below the RTE. Each SW-Component, which uses the Service, must contain “service ports” in its own SW-C description which will be connected to the ports of the OS, so that the RTE can be generated.

13.3.1 Data Types and Port Interface

13.3.1.1 General Approach

It is appropriate to model the requests issued from a client to the services by ports using the client/server interfaces.

13.3.1.2 Data Types

This chapter describes the data types which will be used in the port interfaces for service requests. In general the interfaces are using the following types:

- `CounterType` – This type is the reference to the requested Counter
- `TickType` – This type holds a timer value
- `TickRefType` – This is a reference (pointer) to a `TickType`
- `AppModeType` – This type holds the current mode of the OS
- `ApplicationType` – This type is the reference to a OS-Application
- `RestartType` – This type holds the restart parameter
- `ApplicationStateRefType` – This is a reference (pointer) to a location which contains the state of an OS-Application

The APIs of the services have a return type of `StatusType`. This means that a successful call returns 0 and a return value not equal 0 represents an error.

13.3.1.3 Port Interface

The operations correspond to the function calls of the OS C-API (notation in pseudo code; must be transferred into XML).

The notation of possible error codes resulting from server calls follows the approach in the meta-model. It is a matter of the RTE specification [9], how those error codes will be passed via the actual API.

```
ClientServerInterface OsService {
      PossibleErrors {
            E_OS_ACCESS = 1
            E_OS_ID = 3,
            E_OS_STATE = 7
```


火龙果•整理
uml.org.cn

```
            E_OS_VALUE = 8

        };

        // The timer services

         GetCounterValue(       IN  CounterType  CounterID,
                                OUT TickRefType  Value
                                ERR{E_OS_ID});

         GetElapsedValue(       IN  CounterType  CounterID,
                                INOUT  TickType  PreviousValue,
                                OUT TickRefType  Value,
                                ERR{E_OS_ID, E_OS_VALUE});

         // Service to access the current AppMode (which was
         // used in StartOS()).

         GetActiveApplicationMode(OUT AppModeType CurrentMode);

        // Services to terminate applications and to access the current
       // application state.

       TerminateApplication( IN  ApplicationType  Application,
                             IN  RestartType      RestartOption,
                             ERR{E_OS_ID,_E_OS_VALUE,
                                 E_OS_STATE, E_OS_ACCESS});

       GetApplicationState(  IN  ApplicationType  Application,
                             OUT ApplicationStateRefType Value,
                             ERR{E_OS_ID}));

};
```

13.3.1.4Ports

We end up with the following structure for the AUTOSAR Interface of the OS:

```
Service Os
{
      ProvidePort OsService OsService;
};
```

It is obvious that the existence of all these port definitions depends on the ECU.

火龙果•整理
uml.org.cn

14 Outlook on Memory Protection Configuration

As stated before, memory protection configuration is not standardized yet. Nevertheless it seems helpful to contribute a recommendation in this chapter, how the configuration might work.

14.1 Configuration Approach

Both, SW-Components and BSW modules, map code and variables to dedicated, disjoined memory sections (see meta-class»ObjectFileSection« in chapter 7.3 of »Software Component Template«, Version 2.0.1, and »module specific sections« in chapter 8.2 of »Specification of Memory Mapping«, Version 1.0.1).

This essential precondition (avoid an inseparable conglomeration of variables in the default section) can be used to support configuration of memory protection domains:

1. The generator can save for each OS-Application a (processor-specific) maximum number of output sections for data in a file (to be used in the linker file).

2. The generator can uniquely identify the address spaces of the data output sections with symbols using the naming convention (see »memory allocation keywords« `_STOP_SEC_VAR` and `_START_SEC_VAR` for start and stop symbols) in the specification mentioned above.

The input data sections in the object files of an OS-Application can then be assigned to the output sections (with potential tool support). Usually, this is one segment for global data, and one segment for code.

To archieve portability, the user shall group all variables belonging to a private data section (Task/ISR or OS-Application) in separate files.

火龙果•整理
uml.org.cn

15 Changes to Release 3.0/3.1

- Many small correction (wording, typos, clarifications)
- Added additional services to the service interface for SWCs
- Changes caused by R4.0 concepts (e.g. debugging concept, error handling concept, multicore concept, …)
    - Added states to OS-Applications
    - Added 2 new services: GetApplicationState() and AllowAccess()
    - Extended API to terminate other OS-Applications

火龙果•整理
uml.org.cn